



# CERTIGNA EMAIL PROTECTION

**EMAIL SIGNATURE** 

Last update: 2025-03-19

Version: 1.3

OID: 1.2.250.1.177.1.0.1 CERTIGNA

1.2.250.1.177.2.0.1 CERTIGNA ROOT CA

1.2.250.1.177.8.0.1.1 CERTIGNA EMAIL PROTECTION ROOT CA

1.2.250.1.177.17.0.1.1 CERTIGNA EMAIL PROTECTION EU ROOT CA

Classification: Public

# **SUMMARY**

1	INTE	RODUCTION	5
	1.1	Overview	5
	1.2	Document Name and Identification	7
	1.3	PKI Participants	8
	1.4	Certificate Usage	13
	1.5	Policy Administration	14
	1.6	Definitions and Acronyms	16
2	PUB	BLICATION AND REPOSITORY RESPONSIBILITIES	22
	2.1	Repositories	22
	2.2	Publication of Certification Information	22
	2.3	Time or Frequency of Publication	24
	2.4	Access Controls on Repositories	25
3	IDEN	NTIFICATION AND AUTHENTICATION	26
	3.1	Naming	26
	3.2	Initial identity validation	29
	3.3	Identification and Authentication for Re-key Requests	48
	3.4	Identification and authentication for revocation request	49
4	CER	RTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS	51
	4.1	Certificate Application	51
	4.2	Certificate Application Processing	52
	4.3	Certificate Issuance	55
	4.4	Certificate Acceptance	56
	4.5	Key Pair and Certificate Usage	57
	4.6	Certificate Renewal	57
	4.7	Certificate Re-key	58
	4.8	Certificate modification	59
	4.9	Certificate Revocation and Suspension	60
	4.10	Certificate Status Service	69
	4.11	End of Subscription	70
	4.12	Key Escrow and Recovery	70



5	FA	CILITY, MANAGEMENT, AND OPERATIONAL CONTROLS	71
	5.1	Physical Controls	71
	5.2	Procedural Controls	73
	5.3	Personnel Controls	74
	5.4	Audit Logging Procedures	77
	5.5	Records Archival	80
	5.6	Key Changeover	82
	5.7	Compromise and Disaster Recovery	83
	5.8	CA or RA Termination	85
6	TEC	CHNICAL SECURITY CONTROLS	87
	6.1	Key Pair Generation and Installation	87
	6.2	Private Key Protection and Cryptographic Module Engineering Controls	90
	6.3	Other Aspects of Key Pair Management	94
	6.4	Activation Data	95
	6.5	Computer Security Controls	96
	6.6	Life Cycle Technical Controls	96
	6.7	Network Security Controls	97
	6.8	Time-stamping	97
7	CE	RTIFICATE AND CRL PROFILES	98
	7.1	Certificate profile	98
	7.2	Profile of CRL	115
	7.3	OCSP Profile	117
8	CC	MPLIANCE AUDIT AND OTHER ASSESSMENT	119
	8.1	Frequency or Circumstances of Assessment	119
	8.2	Identity/Qualifications of Assessor	119
	8.3	Assessor's Relationship to Assessed Entity	120
	8.4	Topics Covered by Assessment	120
	8.5	Actions Taken as a Result of Deficiency	120
	8.6	Communication of Results	121
	8.7	Self-Audits	121
9	ОТ	HER BUSINESS AND LEGAL MATTERS	123



	9.1	Fees	123
	9.2	Financial Responsibility	123
	9.3	Confidentiality of Business Information	124
	9.4	Privacy of Personal Information	125
	9.5	Intellectual Property Rights	126
	9.6	Representations and Warranties	126
	9.7	Disclaimers of Warranties	131
	9.8	Limitations of Liability	132
	9.9	Indemnities	132
	9.10	Term and Termination	133
	9.11	Individual Notices and Communications with Participants	134
	9.12	Amendments	134
	9.13	Dispute Resolution Provisions	134
	9.14	Governing Law	135
	9.15	Compliance with Applicable Law	135
	9.16	Miscellaneous Provisions	135
	9.17	Other Provisions	136
10	) APPE	ENDIX 1: SECURITY REQUIREMENTS FOR THE CA'S CRYPTOGRAPHIC MODULE	137
	10.1	Security Objectives Requirements	
	10.2	Qualification Requirements	
11	APPI	NDIX 2: SECURITY REQUIREMENTS FOR THE DEVISE USED BY THE SUBJECT	138
.,	11.1	Security objectives requirements	
	11.2	Qualification Requirements	139



# 1 INTRODUCTION

#### 1.1 Overview

CERTIGNA, formerly DHIMYOTIS, is a TESSI group company which specializes in providing digital trust services.

CERTIGNA has set up several Certification Authority (CA) to provide electronic certificates to legal and natural persons. This document is the Certificate Policy/Certification Practice Statement (CP/CPS) outlines the practices that CERTIGNA applies and undertakes to comply in the delivery of its electronic certification services. The reader's attention is drawn to the fact that the understanding of this CP/CPS guess he is familiar with the concepts related to the technology of Public Key Infrastructure (PKI).

CERTIGNA is audited by LSTI, a French certification body. The status of CERTIGNA's product qualifications and certifications can be consulted on the following websites:

- RGS Qualifications and ETSI certifications: Link to the LSTI website
- eIDAS Qualifications: Link to the European TSL

This CP/CPS aims to comply:

- with the current version of the Baseline Requirements for the Issuance and Management of Publicly-Trusted S/MIME Certificates published at http://www.cabforum.org.
- with the following standards and security levels.

[ROOT CA] CERTIGNA EMAIL PROTECTION ROOT CA				
CERTIGNA EMAIL PROTECTION LEGAL PERS	ON CA	RGS	ETSI	RSA
Advanced seal for mails	1.2.250.1.177.8.1.1.1.1		EN 319 411-1 LCP	>=3072
Advanced seal for mails with	1.2.250.1.177.8.1.1.3.1		EN 319 411-2 QCP-I	>=3072
eIDAS qualified certificate				
Advanced seal for mails	1.2.250.1.177.8.1.1.1.2		EN 319 411-1 LCP	4096
RGS * Advanced seal for mails	1.2.250.1.177.8.1.1.2.1	<u>*</u>	EN 319 411-1 LCP	<del>3072</del>
RGS * Advanced seal for mails	1.2.250.1.177.8.1.1.2.2	<u>*</u>	EN 319 411-1 LCP	4096
Advanced seal for mails with	1.2.250.1.177.8.1.1.3.2		EN 319 411-2 QCP-I	4096
eIDAS qualified certificate				
CERTIGNA EMAIL PROTECTION NATURAL PE	ERSON CA	RGS	ETSI	
Advanced signature for mails	1.2.250.1.177.8.2.1.1.1		EN 319 411-1 LCP	>=3072
Advanced signature for mails with	1.2.250.1.177.8.2.1.3.1		EN 319 411-2 QCP-n	>=3072
eIDAS qualified certificates				
eIDAS qualified signature for mails	1.2.250.1.177.8.2.1.4.1		EN 319 411-2 QCP-n-qscd	>=3072
RGS * Advanced signature for mails	1.2.250.1.177.8.2.1.2.1	<u>*</u>	EN 319 411-1 LCP	<del>3072</del>
RGS ** eIDAS qualified signature for mails	1.2.250.1.177.8.2.1.5.1	**	EN 319 411-2 QCP-n-qscd	<del>3072</del>



[ROOT CA] CERTIGNA EMAIL PROTECTION EU ROOT CA				
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA		RGS	ETSI	RSA
Advanced seal for mails	1.2.250.1.177.17.1.1.1.1	*	EN 319 411-1 LCP	>=3072
Advanced seal for mails with	1.2.250.1.177.17.1.1.2.1	**	EN 319 411-2 QCP-I	>=3072
eIDAS qualified certificate				
eIDAS qualified seal for mails	1.2.250.1.177.17.1.1.3.1	**	EN 319 411-2 QCP-I-qscd	>=3072
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA		RGS	ETSI	
Advanced signature for mails	1.2.250.1.177.17.2.1.1.1	*	EN 319 411-1 LCP	>=3072
Advanced signature for mails with	1.2.250.1.177.17.2.1.2.1	**	EN 319 411-2 QCP-n	>=3072
eIDAS qualified certificates				
eIDAS qualified signature for mails	1.2.250.1.177.17.2.1.3.1	**	EN 319 411-2 QCP-n-qscd	>=3072

[ROOT CA] CERTIGNA & CERTIGNA ROOT CA				
CERTIGNA IDENTITY PLUS CA		RGS	ETSI	RSA
Authentication & signature	1.2.250.1.177.2.4.1.1.1	**	EN 319 411-2 QCP-n-qscd Pro	2048
Authentication & signature	1.2.250.1.177.2.4.1.1.2	**	EN 319 411-2 QCP-n-qscd Pro	3072
Authentication & signature	1.2.250.1.177.2.4.1.7.1		EN 319 411-2 QCP-n Pro	2048
Authentication & signature	1.2.250.1.177.2.4.1.7.2		EN 319 411-2 QCP-n Pro	3072
Authentication & signature	1.2.250.1.177.2.4.1.8.1		EN 319 411-2 QCP-n-qscd Pro	2048
Authentication & signature	1.2.250.1.177.2.4.1.8.2		EN 319 411-2 QCP-n-qscd Pro	3072
Signature	1.2.250.1.177.2.4.1.3.1	***	EN 319 411-2 QCP-n-qscd Pro	2048
Signature	1.2.250.1.177.2.4.1.3.2	***	EN 319 411-2 QCP-n-qscd Pro	<del>3072</del>
Authentication & signature	1.2.250.1.177.2.4.1.4.1	**	EN 319 411-2 QCP-n-qscd	2048
Authentication & signature	1.2.250.1.177.2.4.1.4.2	**	EN 319 411-2 QCP-n-qscd	<del>3072</del>
Signature	1.2.250.1.177.2.4.1.6.1	***	EN 319 411-2 QCP-n-qscd	2048
Signature	1.2.250.1.177.2.4.1.6.2	***	EN 319 411-2 QCP-n-qscd	<del>3072</del>

In the event of any inconsistency between this CP/CPS and those Requirements, those Requirements take precedence over this CP/CPS.



# 1.2 Document Name and Identification

This CP/CPS can be identified by several OID linked to the root CAs grouped in this document:

• 1.2.250.1.177.1.0.1 CERTIGNA

1.2.250.1.177.2.0.1 CERTIGNA ROOT CA

1.2.250.1.177.8.0.1.1 CERTIGNA EMAIL PROTECTION ROOT CA
 1.2.250.1.177.17.0.1.1 CERTIGNA EMAIL PROTECTION EU ROOT CA

Intermediate and final CA certificates issued under each root CA also have an OID that clearly identifies the practices of this applicable CP/CPS.

#### 1.2.1 Revisions

This CP/CPS brings together all the CPs and CPSs of the various root and intermediate CAs used to issue Email Protection certificates. To facilitate access to information, it was decided to group all these documents together in a single CP/CPS. The table below shows the history of the previous versions of the CP and CPS grouped together in this document, which can be consulted on the following page: https://www.certigna.com/autorites-de-certification/

Ver.	Date	Document change
1.0	2024-04-05	Creation of this CP dedicated to Email Protection CAs  Integration of our new Certigna Email Protection CA  Integration of historical CAs:  CERTIGNA and associated CA and end-entity certificates  CERTIGNA ROOT CA and associated CA and end-entity certificates
1.1	2024-06-25	<ul> <li>Revision of the document and clarification on:</li> <li>Duration of use of registration documents (see 4.1.2.2);</li> <li>Application file retention period (see 9.4.1);</li> <li>Obligations of CMs, Subjects and applicants (see 9.6.3 and 9.6.4);</li> <li>Use of test certificates (see 9.17.1).</li> </ul>
1.2	2024-09-13	Revision of the document and clarification on:  - All sections are structured in accordance with section 6 of RFC 3647;  - Identification and Authentication for Routine Re-key (see 3.3.1.2 and 3.3.1.3);  - Validation usage delay (see 4.2.1.2)1;
1.3	2025-03-19	Combining CP and CPS in a single document.  Transfer of Email Protection CAs from "Certigna Root CA" CP/CPS to this document.  Revision of the document and clarification on:  - The addition of new certificate profiles;  - Requirement to check Active statut of legal entity SMC06 (See 3.2.3.2.1);  - Introduction CAA for S/MIME SMC05 (See 4.2.2.1);  - The router and firewall activities logging SMC07 (See 5.4.1.1);  - Deprecate Legacy Generation Profiles SMC08 (See 6.3.2.2, 7.1.12.5);  - Linting of S/MIME certificates SMC09 (See 4.3.1, 8.7);  - The multi-perspective issuance corroboration SMC10 (See 4.2.2.2, 5.4.1);  - The retention period for application files (cf. 5.5.2.1).



# 1.3 PKI Participants

#### 1.3.1 Certification authorities

The CA is responsible for the provision of certificate management services throughout their life cycle (generation, distribution, renewal, revocation, ...) and relies on a technical infrastructure: a PKI. The CA is responsible for the implementation of the CP/CPS to the PKI set in place. For certificates signed in its name, the CA has the following functions:

- Registration and renewal functions;
- Certificate generation function;
- Secret generation function;
- Publication function of the general conditions of the CP/CPS, CA certificates and certificate application forms;
- Revocation management function;
- Information function on the status of certificates via the Certificate Revocation List (CRL) updated at regular intervals and in a query mode / real-time response (OCSP).

The CA provides these functions directly or outsourcing them, some or all. In all cases, the CA retains responsibility. CA is committed to respecting the obligations described in this CP/CPS. It is also committed that the components of the PKI, internal or external to the CA, which they incumbent also respect them.

Finally, the parties of the CA concerned with certificate generation and revocation management are independent from other organizations regarding their decisions on the establishment, supply, maintenance and suspension of services; managers, support personnel and personnel with trusted roles are free from any pressure from commercial, financial or otherwise, could adversely affect the confidence in the services provided by the CA. The parties of the CA concerned with certificate generation and revocation management have a documented structure, which safeguards impartiality of operations.

# 1.3.2 Registration authorities

Registration authority provides the following functions, delegated by the CA under this CP/CPS:

- The acquisition and verification of future information of Certificate Manager (CM) or Subject and his/her entity and the constitution of the corresponding registration files;
- The acquisition and verification of information, if applicable, of the future certification agent (\*) and his/her business entity and the constitution of the corresponding registration files;
- The establishment and transmission of the certificate request to the CA;
- The archiving of the certificate request files;
- Conservation and protection of confidentiality and integrity of personal authentication data of the RC, Subject or of the Certification Agent;
- Verification of certificate revocation requests.

The RA performs these functions directly or with the contribution of Delegate Registration Authorities. In all cases, the RA remains responsible and the archiving of the registration files (electronic and / or paper) is the responsibility of the RA.



Before the CA authorizes a Delegated Third Party to perform a delegated function, the CA contractually requires the Delegated Third Party to:

- Meet the qualification requirements of Section 5.3, when applicable to the delegated function;
- Retain documentation in accordance with Section 5.5.2;
- Abide by the other provisions of these Requirements that are applicable to the delegated function; and
- Comply with the CA's CP/CPS or the Delegated Third Party's practice statement that the CA has verified complies with these requirements.

Unless stated otherwise, in this document, "RA" covers the Registration Authority and Delegated Registration Authorities.

(\*): The RA offers the possibility to the client entity to use a designated Certification Agent who is under its responsibility to carry out all or part of the information verification. In this case, the RA ensures that applications are complete and carried out by an authorized Certification Agent.

The CA does not designate an Enterprise RA to verify certificate requests from the Enterprise RA's own organization.

#### 1.3.3 Subscribers

A Subscriber is a natural person attached or not to the entity designated in the requested certificate, who orders one or more certificates for himself or in the name of a Certificate Subject or Manager. A Subscriber is responsible for the obligations incumbent on the Subscribers, as well as those incumbent on the Subjects or Certificate Manager, if applicable.

#### 1.3.3.1 Certificate Manager or Subject

Two different terms are used in this CPS when it comes to referring to the person who is issued a certificate and who is in charge of managing it:

- We will refer to the "Certificate Manager" (CM) when the issued certificate is intended for an application service or a server, such as a seal service or a web server. The CM is the person in charge of managing the certificate but is not explicitly designated in this legal person certificate.
- We will refer to the "Subject" when the issued certificate is intended for a natural person, for signing, authenticating or encrypting data. The Subject is then the natural person explicitly named in the certificate.

The CM or Subject must meet the conditions and obligations that are set in the CP/CPS and Terms and Conditions of Sale and Use (TCSU).

# 1.3.3.2 Certificate Manager for a CA

For the root CA and the intermediate CAs, the CM can only be the CERTIGNA Certification Authority.



# 1.3.3.3 Certificate Manager for an application service or a web server

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for Mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

CM can only be a natural person. It is responsible for the use of the certificate (and associated private key) in which the application service or the web server concerned is identified and the entity for which he/she uses the certificate and with which it maintains a contractual / reporting relationship / regulatory. The certificate is attached to the application service or the web server and not to the CM. In case of change of CM, the entity shall report it to the CA and appoint a successor. The CA revokes certificates for which there is no more CM explicitly identified.

# 1.3.3.4 Subject of a natural person certificate

CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA CERTIGNA IDENTITY PLUS CA	Authentication/signature  Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature

A subject can only be a natural person, player in the private or public sector. This person uses his/her private key and the corresponding certificate in the context of his/her personal activities or in relation to the entity identified in the certificate and with which he has a contractual, hierarchical, or regulatory relationship.

# 1.3.4 Relying Parties

Certificate users must take all the precautions described in the CP/CPS as well as in the TCSU.

#### 1.3.4.1 CA Certificate

#### Root CA

Entity or physical person who uses a CA certificate and trusts it to verify the origin and the validity of a certificate issued by this CA.

#### Intermediate CAs

Entity or physical person who uses an intermediate CA certificate and trusts it to verify the origin and the validity of a certificate issued by this CA.

# 1.3.4.2 Legal Person Certificate

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for Mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

An electronic seal certificate user can be:

- A user recipient of signed data by a seal application service that uses the electronic seal certificate and a seal verification module to authenticate the origin of the transmitted data.
- An application service recipient of data from another application service and which uses the electronic seal certificate and a seal verification module to authenticate the origin of the transmitted data.
- An application service which signs electronic data.



#### 1.3.4.3 Natural Person Certificate

CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA IDENTITY PLUS CA	Authentication/signature

#### **Authentication and Signature**

An authentication and signature certificate user can be:

- An online service that uses a certificate and an authentication verification device to validate an
  access request made by the certificate subject in the context of an access control or to
  authenticate the origin of a message or data transmitted by the Subject of the certificate;
- An online service that uses a signature verification device to verify the electronic signature on the data or a message of the subject of the certificate;
- A user recipient of a message or data and who uses a certificate and an authentication verification device to authenticate its origin.
- A user who electronically sign a document or a message;
- A user recipient of a message or data and who uses a certificate and a signature verification device to verify the electronic signature created by the Subject of the certificate on this message or data.

#### Signature

A signature certificate user can be:

- An online service that uses a signature verification device to verify the electronic signature on the data or a message of the Subject of the certificate;
- A user who electronically sign a document or a message;
- A user recipient of a message or data and who uses a certificate and a signature verification device to verify the electronic signature by the Subject of the certificate on this message or data.

# 1.3.5 Other Participants

# 1.3.5.1 Delegated Registration Authority

CA also relies on Delegated Registration Authorities (DRA) to outsource a part of RA's functions. A DRA operator has the power to:

- process a certificate generation or renewal;
- process a certificate revocation;
- record, if appropriate, the Certification Agents belonging to the entities which request certificates.

A DRA operator performs for the authority, in the context of issuance of the certificate, the verification of future CM or Subject identity under the same conditions and with the same level of safety as those required for the RA operator. For this it is directly related to RA.

The commitments of the DRA operator against CA are specified in a written agreement with the responsible entity of the operator and in the commitment letter to be signed by the latter. Both documents include state that the operator must perform impartial and scrupulous verification of the identity and of the possible future CM or Subject attributes and application services. He/she must also respect the parts of the CP/CPS incumbent on him.



# 1.3.5.2 Certification Agent

CA offers the opportunity for the client's entity to designate one or more Certification Agents. The Certification agent has, by law or by delegation, the power to:

- request a certificate generation or renewal certificate on behalf of the entity;
- request a certificate revocation on behalf of the entity.

The certification agent can be a legal representative of the entity or any person that the latter has formally designated. He or she provides for the CA, in the context of the issuance of certificates, the identity verification of future Certificate Managers under the same conditions and with the same level of safety as those required for the RA operator. For this it is directly in contact with the Registration Authority.

The commitments of the Certification Agent in respect of the CA are specified in a written agreement with the entity responsible of the Certification Agent and in the commitment letter to be signed by the Certification Agent. Both documents specify that the Certification Agent must perform impartial and scrupulous verification of the identity and of the possible future CM or Subject attributes and application services. He/she must also respect the parts of this CP/CPS incumbent on him.

The entity shall promptly report to CA, the Certification Agent's departure from office and possibly appoint a successor. The Certification Agent shall not have access to the private key activation data associated with the certificate issued to CM or Subject.

# 1.3.5.3 National Competent Authority

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for Mails	
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails	
TS 119 495 DSP2		

According to PSD2 and Capital Requirements Directive, the National Competent Authority (NCA) responsible for payment services approves or rejects authorization of PSPs in their own country. If authorization is granted, the NCA lists the respective PSP in the national public register, together with an identification number, which could be, but is not necessarily, an authorization number.

Subject to NCA approval PSPs can exercise the right of establishment and freedom to provide services in other Member States. This is called passporting. Information about passporting is published in the public register in the home country of the PSP or the EBA PSD2 Register.

Certificates issued according to the requirements laid down in the present document do not include any attributes regarding passporting.

#### 1.3.5.4 Customer service

To ensure a responsive service that meets requirements, Certigna can use a provider specializing in "Customer services" to assist its prospects and customers in their requests relating to certificates. To this end, the operators of this entity are recruited as operator of DRA to allow them to access the application files and to assist subscribers in their procedures.



A contract of DRA is established with the entity in charge of this service. The provider thus undertakes to respect the parts of the CP/CPS incumbent on him/her, and in particular the commitments of Chapters 3 and 4.

#### 1.3.5.5 Hosts of the technical infrastructure

Certigna may use a provider for the physical hosting of its technical infrastructure. A contract is established with the provider to guarantee the security of the services in accordance with the commitments of chapter 5.1 of the CP/CPS.

# 1.3.5.6 Providers of cryptographic device

The cryptographic device, delivered, if necessary, by Certigna to the Subject or to the CM, to store and use the private key and the certificate, can be acquired from a supplier with whom a contract is established aiming to guarantee the conformity of the cryptographic device with a or several qualifications and / or certifications cited in chapter 11 of the CP/CPS.

Despite these provisions, it is important to remember that if one of these qualifications or certifications is no longer maintained or suspended for reasons such as the identification of a vulnerability or the cessation of production of the product, Certigna will inform the Subject or the CM and revoke their certificate, without any condition of reimbursement.

# 1.4 Certificate Usage

# 1.4.1 Appropriate Certificate Uses

#### QCP-I-qscd / QCP-n-qscd

The electronic certificates are used for applications where security needs are very strong given the high risks that threaten them.

#### RGS \*\* / QCP-I / QCP-n

The electronic certificates are used for applications where security needs are strong given the high risks that threaten them.

#### RGS \* / LCP

The electronic certificates are used for applications where security needs are moderate given the risks that threaten them.

#### 1.4.1.1 CA Certificate

#### **Root CAs**

The root CA key pair is used for signing intermediate CA certificates and Authorities Revocation Lists (ARLs).

#### Intermediate CAs

The intermediate CA key pair is used for signing final certificates and Certificate Revocation Lists (CRLs).



# 1.4.1.2 Legal Person Certificate

C	ERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for Mails
C	ERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails
Seal for mails		
Th	The uses are the electronic seal of emails and the electronic seal verification.	

#### 1.4.1.3 Natural Person Certificate

CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature	
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature	
CERTIGNA IDENTITY PLUS CA	Authentication/signature	
Signature		
The uses are the electronic signature of emails and the electronic signature verification.		
Authentication and signature		
The uses are the authentication and email signature uses.		

#### 1.4.2 Prohibited Certificate Uses

Uses other than those mentioned in the previous paragraph are prohibited. The CA agrees to comply with these restrictions and to enforce compliance by Certificate Managers, Subjects and certificate users. To this end, it publishes to the CM, Subjects, Certification Agent and potential users the TCSU that can be found on the site <a href="https://www.certigna.com">https://www.certigna.com</a> before any request or use of a certificate.

# 1.5 Policy Administration

# 1.5.1 Organization Administering the Document

The CA has a Security Committee responsible for the development, monitoring and modification of this CP/CPS. It shall act on any necessary changes to be made to this CP/CPS at regular intervals.

The formal validation of this CP/CPS and the TCSU is ensured at a minimum by one person in a trusted role of controller and one person in a trusted role of security officer.

#### 1.5.2 Contact Person

# 1.5.2.1 FAQs et customer support

Answers to frequently asked questions can be found in our FAQ section at <a href="https://www.certigna.com/faq/">https://www.certigna.com/faq/</a>.

If you have any other questions, you can contact our Customer Service department as follows:

- Contact e-mail: contact@certigna.fr;
- Telephone: 0 806 115 115 (Free service) available Monday to Friday from 09:00 to 18:00;
- Chat on the https://www.certigna.com website, available Monday to Friday from 09:00 to 18:00.



# 1.5.2.2 Requesting a révocation

As mentioned in chapter 3.4.2, the certificate revocation request by the CM or Subject, a legal representative of the entity, an DRA operator or, where applicable, a CA, can be made in one of the following ways:

- From the customer area of the CERTIGNA website <a href="https://www.certigna.com">https://www.certigna.com</a> by selecting the certificate to be revoked;
- By post: by completing and signing the certificate revocation form available on the CERTIGNA website <a href="https://www.certigna.com">https://www.certigna.com</a>. The applicant authenticates himself by attaching a photocopy of his identity document to the mail sent.

Information on the processing of your personal data is available in the Policy on the use of personal data, which can be accessed at the following address: <a href="https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/">https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/</a>.

# 1.5.2.3 Reporting a malicious or dangerous certificate

For reporting a malicious or dangerous certificate (suspected Private Key compromise, certificate misuse, or other types of fraud, compromise, inappropriate conduct, etc.) or any other matter related to certificates, use the contact form available at <a href="https://www.certigna.com/contactez-nous/">https://www.certigna.com/contactez-nous/</a> by selecting "Certificate considered malicious or dangerous".

# 1.5.2.4 Making a complaint

To bring a complaint to CERTIGNA's attention, please use the contact form available at the following address https://www.certigna.com/contactez-nous/ and select the "Réclamation" reason.

You can also make a complaint to our customer service department using the following contact details:

- Contact e-mail: contact@certigna.fr;
- Telephone: 0 806 115 115 (Free service) available Monday to Friday from 09:00 to 18:00;
- Chat on the https://www.certigna.com website, available Monday to Friday from 09:00 to 18:00;
- Mail addressed to

# CERTIGNA 20 allée de la Râperie Zone de la plaine 59650 Villeneuve d'Ascq, France

Information on the processing of your personal data is available in the Policy on the use of personal data, which can be accessed at the following address: <a href="https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/">https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/</a>.



# 1.5.3 Person Determining CPS Suitability for the Policy

The Security Committee ensures the compliance of this CP/CPS. IT can optionally be assisted by external experts to ensure compliance.

# 1.5.4 CPS approval procedures

Initially, the CPS translates into technical, organizational, and procedural terms the requirements of the CP based on the company's "Information security policy". The Security Committee shall ensure that the means used and described in this CP/CPS meet these requirements as the approval process in place. A compliance check of the CP/CPS is made through the internal and external audits for the CA qualification. Any update request of the CP/CPS also follows this process. Any new approved version of the CP/CPS is published without delay.

# 1.6 Definitions and Acronyms

#### 1.6.1 Definitions

Useful terms to the understanding of the CP are the followings:

**Affiliate** - A corporation, partnership, joint venture or other entity controlling, controlled by, or under common control with another entity, or an agency, department, political subdivision, or any entity operating under the direct control of a Government Entity.

**Administrative authorities** - This term refers to government departments, local authorities, public administrative institutions, the bodies administering social protection systems and other bodies responsible for the management of an administrative public service.

**Agent –** Individual acting on behalf of an administrative authority.

Application Developer - A manager of a service of the public sphere electronically accessible.

**Audit Report** - A report from a Qualified Auditor stating the Qualified Auditor's opinion on whether an entity's processes and controls comply with the applicable requirements.

**Authorities Revocation List** - List including the serial numbers of the certificates of intermediate authorities which have been revoked, and signed by the root CA.

**Business Entity**: Any entity that is not a Private Organization, Government Entity, or Non-Commercial Entity as defined herein. Examples include, but are not limited to, general partnerships, unincorporated associations, sole proprietorships, etc.

**Certification Authority Authorization (or CAA)** - From RFC 9495: "The Certification Authority Authorization (CAA) DNS resource record (RR) provides a mechanism for domains to express the allowed set of Certification Authorities that are authorized to issue certificates for the domain."



**Certification Authority** - In a CSP, a Certification Authority is responsible, on behalf and under the responsibility of this CSP, applying at least one certification policy and is identified as such, as an issuer («issuer" field of the certificate).

**Certificate Manager** - Person in charge and responsible of the electronic certificate used by an application service.

**Certification Policy** - A set of rules, identified by a name (OID), defining the requirements that a CA comply in the implementation and delivery of its services and indicating the applicability of a certificate to a specific community and / or a class of applications with common security requirements. A CP can also, if necessary, identify the obligations and requirements on other stakeholders including Subject and certificate users.

**Certification Practice Statement -** A CPS identifies practices (organization, operational procedures, technical and human resources) that the CA applies under the provision of its certification services to users and in accordance with the policies or certification that it has committed.

**Certificate revocation list -** List including serial numbers of certificates that have been revoked, and signed by the issuing CA.

**Certification service provider -** Any person or entity who is responsible for the management of electronic certificates throughout their life cycle, towards the Subject and users of these certificates.

**Certificate Subject** - Person identified in the certificate and is the holder of the private key corresponding to the public key.

**Certificate user** - Entity or natural person who uses a certificate which it relies to verify an electronic signature or an authentication value from a certificate holder or encrypt data to a certificate holder.

**Component** - Platform operated by an entity and comprised of at least one computer station, an application and, where applicable, cryptographic means. Component play a specific role in the operational implementation of at least one function of PKI. The entity may be the CSP itself or an external entity related to CSP contractual, regulatory or hierarchical.

Cross Certificate - A certificate that is used to establish a trust relationship between two Root CAs.

**CSPRNG** - A random number generator intended for use in a cryptographic system.

**Electronic Certificate** - Electronic file certifying the link between a public key and the identity of its owner (natural or legal person or system). This certificate takes the form of an electronic signature made by a CSP. It is issued by a CA. The certificate is valid for a given period specified therein.

**Electronic Seal** - Digital Seal done by an application server with data to be used either as part of an authentication service data origin, either as part of a service non-repudiation.

**Entity** - Means an administrative authority or a company in the broadest sense, namely also legal persons of private law type associations. It can be a Private Organization, Government Entity, Business



Entity, or Non-Commercial Entity.

**European Banking Authority PSD2 Register** - Register of payment institutions and e-money institutions developed, operated and maintained by the EBA under article 15 of Directive (EU) 2015/2366.

**FQDN -** Fully qualified domain name indicating the absolute position of a node in the DNS tree and specifying the top-level domains to the root.

**Information System** - Any set of means to develop, process, store or transmit information subject to electronic exchange between users and administrative authorities and between administrative authorities.

**Jurisdiction of Incorporation -** In the context of a Private Organization, the country and (where applicable) the state or province or locality where the organization's legal existence was established by a filing with (or an act of) an appropriate government agency or entity (e.g., where it was incorporated). In the context of a Government Entity, the country and (where applicable) the state or province where the Entity's legal existence was created by law.

**Jurisdiction of Registration -** In the case of a Business Entity, the state, province, or locality where the organization has registered its business presence by means of filings by a Principal Individual involved in the business.

**Legal existence -** A Private Organization, Government Entity, Business Entity or Non-Commercial Entity has Legal Existence if it has been validly formed and not otherwise terminated, dissolved, or abandoned.

**Legal representative (principal individual)** - An individual of a Private Organization, Government Entity, or Business Entity who is either an owner, partner, managing member, director, or officer, as identified by their title of employment, or an employee, contractor or agent authorized by such entity or organization to conduct business related to the request, issuance, and use of certificates.

**Linting** - A process in which the content of digitally signed data such as a Precertificate [RFC 6962], Certificate, CRL, or OCSP response, or data-to-be-signed object such as a tbsCertificate (as described in RFC 5280, Section 4.1.1.1) is checked for conformance with the profiles and requirements defined in these Requirements.

**Multipurpose Profile -** The S/MIME Multipurpose Generation profiles are aligned with the more defined Strict Profiles, but with additional options for extKeyUsage and other extensions. This is intended to allow flexibility for crossover use cases between document signing and secure email.

**Multi-Perspective Issuance Corroboration** - A process by which the determinations made during domain validation and CAA checking by the Primary Network Perspective are corroborated by other Network Perspectives before Certificate issuance.

**Network Perspective -** Related to Multi-Perspective Issuance Corroboration. A system (e.g., a cloud-hosted server instance) or collection of network components (e.g., a VPN and corresponding



infrastructure) for sending outbound Internet traffic associated with a domain control validation method and/or CAA check. The location of a Network Perspective is determined by the point where unencapsulated outbound Internet traffic is typically first handed off to the network infrastructure providing Internet connectivity to that perspective.

Online Certificate Status Protocol (OCSP) - An online Certificate-checking protocol that enables relying-party application software to determine the status of an identified Certificate.

**Primary Network Perspective -** The Network Perspective used by the CA to make the determination of 1) the CA's authority to issue a Certificate for the requested domain(s) or IP address(es) and 2) the Applicant's authority and/or domain authorization or control of the requested domain(s) or IP address(es).

**Private organization -** A non-governmental legal entity (whether ownership interests are privately held or publicly traded) whose existence was created by a filing with (or an act of) the Incorporating Agency or equivalent in its Jurisdiction of Incorporation. In France, incorporation is done with Business and Society Register.

**Payment Service Provider (PSP) – Provider** authorized by its national competent authority (NCA) to act in one or more of the following roles:

- account servicing (PSP\_AS);
- payment initiation (PSP\_PI);
- account information (PSP\_AI);
- issuing of card-based payment instruments (PSP\_IC).

**Protection device secret elements** - Refers to a storage device of secret elements given to CM or Subject (e.g. private key, PIN, ....). It can take the form of a smart card, USB key with cryptographic capability or report to software format (ex. PKCS # 12 file).

**Public Key Infrastructure -** Components, functions and procedures dedicated to the management of cryptographic keys and certificates used for trusted services. PKI can be composed of a CA, a certification operator, a centralized registration authority and / or local certification agents, an archiving entity, a publishing entity, ...

**Qualification of electronic certification service provider** - The RGS Decree and elDAS Regulation describe the CSP qualification procedure. A CSP being a specific Trust Service Provider, the qualification of a CSP is an act by which a certification body certifies the compliance of all, or part of the electronic certification service provided by a CSP (family of certificates) to certain requirements of a CP for a given level of security and for the service covered by the certificates.

**Qualification of a security product** – Act by which ANSSI attests to the ability of a product to ensure with a given level of robustness, security features purpose of qualification. The qualification certificate states in the ability of the product to participate in the realization at some level of security of one or more functions covered in the RGS. The qualification procedure for security products is described in the decree RGS. The RGS specifies three qualification process: basic level qualification, standard level qualification and level strengthened qualification.



**Qualified Government Information Source (QGIS)** - A regularly-updated and current, publicly available, database designed for the purpose of accurately providing the information for which it is consulted, and which is generally recognized as a dependable source of such information provided that it is maintained by a Government Entity, the reporting of data is required by law, and false or misleading reporting is punishable with criminal or civil penalties.

**Qualified Government Tax Information Source (QTIS) -** An Information Source that specifically contains tax information relating to Private Organizations, Business Entities or Individuals.

**Qualified Independent Information Source (QIIS) -** A regularly-updated and publicly available database that is generally recognized as a reliable source for certain information.

**Regulatory Technical Standard for PSD2** - Regulatory Technical Standard for PSD2 strong customer authentication and common and secure open standards of communication.

RSA - Public key algorithm (Rivest, Shamir and Adleman).

**Security product** - a software or hardware that implements security features necessary for securing information or system.

**Seal verification application -** This is the application implemented by the user to check the seal of the data received from the server's public key contained in the certificate.

Timestamping Authority - Authority responsible for the management of a timestamp service.

**User** - Individuals acting for its own account or on behalf of a corporation and making electronic communications with administrative authorities.

**User applications -** Application services operating certificates issued for the Certification Authority seal service needs which the certificate is associated.

Note - An agent of an administrative authority which conducts electronic exchange with another administrative authority is, for the latter, a user.

Note - The term "entity" is used to designate a company or an administration. The name "enterprise" covers enterprises in the broadest sense, namely all legal persons governed by private law: companies, associations as well as craftsmen and self-employed workers.

# 1.6.2 Acronyms

Useful abbreviations for the understanding of this CP/CPS are the followings:

**AA** Administrative Authority

**ACME** Automatic Certificate Management Environment

ARL Authority Revocation List
BCP Business Continuity Plan
CA Certification Authority

**CAA** Certification Authority Authorization



CAG **Certification Agent** СМ Certificate Manager

National Commission for Computing and Liberties CNIL

CP **Certification Policy** 

Certification Practice Statement **CPS** 

Certificate revocation list **CRL CSP** Certification Service Provider **CSR** Certificate Signing Request

DBA Doing Business As DN Distinguished Name Domain Name System **DNS** 

DRA Delegate Registration Authority European Banking Authority **EBA** 

European Telecommunications Standards Institute **ETSI** 

ΕV **Extended Validation** 

**FIPS** (US Government) Federal Information Processing Standard

**FQDN** Fully Qualified Domain Name International Code Designator **ICD** 

INPI National Institute of Industrial Property

ISS Information systems security

**MPIC** Multi-perspective issuance corroboration

**NCA** National Competent Authority

**NIST** (US Government) National Institute of Standards and Technology

**OCSP** Online Certificate Status Protocol

OID Object Identifier PΡ **Protection Profile** 

**RSA** 

**PKCS** Public Key Cryptographic Standards

PKI Public Key Infrastructure PSD2 Payment Services Directive 2 **PSP** Payment Service Provider RA Registration Authority

Rivest Shamir Adleman RTS Regulatory Technical Standard for PSD2

SCT Signed Certificate Timestamp

S/MIME Secure MIME (Multipurpose Internet Mail Extensions)

SSL Secure Sockets Layer

**TCSU** Terms and Conditions of Sale and Use

**TLS Transport Layer Security TSP** Trust Service Provider URL Uniform Resource Locator UTC Universal Time Coordinated



# 2 PUBLICATION AND REPOSITORY RESPONSIBILITIES

The CA develops, implements, enforces, and at least once every 366 days update this CP/CPS that describes in detail how the CA implements the latest version of applicable Requirements.

# 2.1 Repositories

# 2.1.1 Entity in charge of providing information

The CA provides to users and applications using certificates it issues, information about the revocation status of valid certificates issued by the CA.

# 2.1.2 Information to be Published

The CA issues to the CM, Subjects and certificate users:

- The CP/CPS;
- The Terms and Conditions of Sale and Use (TCSU) of CA certification services;
- The various forms required for certificate management (certificate request, revocation request);
- The Root CA certificate and valid intermediate CA certificates;
- The Certificate Revocation List (ARL / CRL);

Note: Due to the complexity of reading a CP for Subjects or certificate users not experts in the field, the CA publishes outside the CP, the CPS and TCSU that the future CM or Subjects is obliged to read and to accept in all certificate request (initial and subsequent requests, in case of renewal) to the RA.

# 2.2 Publication of Certification Information

The CP/CPS is structured in accordance with RFC 3647. The CP/CPS and TCSU are annually updated.

# 2.2.1 Publication of CP, Terms and conditions, and forms

The CP/CPS, the TCSU, and the various forms required for certificate management are published in electronic format at http://cps.certigna.com.

#### 2.2.2 Publication of CPS

The CA issues, to the CM and certificate users, the CPS to make possible the assessment of compliance with this CP/CPS. Sensitive details on its practices are however not made public.



# 2.2.3 Publication of CA Certificate

The CM, Subjects and certificate users can access the CA certificates that are issued at the following URL https://www.certigna.com/autorites-de-certification/ or directly via the URLs listed in the following table.

CERTIGNA EMAIL PROTECTION ROOT CA		
CA certificate	http://cert.certigna.com/CertignaEmailProtectionRootCA.cer	
CERTIGNA EMAIL PROTECTION LEGAL PERSON CA		
CA certificate	http://cert.certigna.com/CertignaEmailProtectionLegalPersonCA.cer	
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA		
CA certificate	http://cert.certigna.com/CertignaEmailProtectionLegalPersonEUCA.cer	
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA		
CA certificate	http://cert.certigna.com/CertignaEmailProtectionNaturalPersonCA.cer	
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA		
CA certificate	http://cert.certigna.com/CertignaEmailProtectionNaturalPersonEUCA.cer	

CERTIGNA		
CA certificate	http://autorite.certigna.fr/certigna.der http://autorite.dhimyotis.com/certigna.der	
CERTIGNA ROOT CA		
CA certificate	http://autorite.certigna.fr/certignarootca.der http://autorite.dhimyotis.com/certignarootca.der	
CERTIGNA IDENTITY PLUS CA		
CA certificate	http://autorite.certigna.fr/identityplusca_rootca.der http://autorite.dhimyotis.com/identityplusca_rootca.der	

CA certificates are also available at the following address: https://www.certigna.com/autorites-decertification/.

All publication services are hosted by the CA on several information systems to ensure a high availability. To detect and correct as soon as possible any incident occurring during the operation of one of these sites, the following measures have been deployed:

- Introduction of on-call during non-business hours.
- Subscription to a security monitoring service (24 hours a day).
- Installation and operation of a monitoring software to monitor all the components of the technical platform (servers, equipment, processes) and to send real-time alerts in case of detection of an incident.
- Development and implementation of scripts to automate and simplify load balancing from one site to another.

# 2.2.4 Publication of Test Certificates

No stipulation.



# 2.2.5 Publication of LAR

The Authority certificate revocation list is published electronically at the URLs described in the table above. These URLs are also indicated in the certificates.

CERTIGNA EMAIL PROTECTION ROOT CA & Intermediate CAs		
LAR	http://crl.certigna.com/CertignaEmailProtectionRootCA.crl	
CERTIGNA EMAIL PROTECTION ROOT CA & Intermediate CAs		
LAR	http://crl.certigna.com/CertignaEmailProtectionEURootCA.crl	
CERTIGNA & Intermediate CAs		
LAR	http://crl.certigna.fr/certigna.crl	
LAK	http://crl.dhimyotis.com/certigna.crl	
CERTIGNA ROOT CA & Intermediate CAs		
LAR	http://crl.certigna.fr/certignarootca.crl	
LAR	http://crl.dhimyotis.com/certignarootca.crl	

# 2.2.6 Publication of CRL

The certificate revocation list is published electronically at the URLs described in the table above. These URLs are also indicated in the certificates issued by the CA.

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA		
CRL	http://crl.certigna.com/CertignaEmailProtectionLegalPersonCA.crl	
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA		
CRL	http://crl.certigna.com/CertignaEmailProtectionLegalPersonEUCA.crl	
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA		
CRL	http://crl.certigna.com/CertignaEmailProtectionNaturalPersonCA.crl	
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA		
CRL	http://crl.certigna.com/CertignaEmailProtectionNaturalPersonEUCA.crl	
CERTIGNA IDENTITY PLUS CA		
CRL	http://crl.certigna.fr/identityplusca.crl http://crl.dhimyotis.com/identityplusca.crl	

# 2.3 Time or Frequency of Publication

# 2.3.1 Publication of documentation

The CP/CPS, the TCSU and the various forms required for certificate management are annually updated, if necessary, to ensure consistency at any time between the published information and the



CA's actual commitments, means and procedures. These documents are available on a 24x7 basis. The publication function based on this information (excluding certificate status information) is available on workdays.

#### 2.3.2 Publication of CA certificates

CA certificates are published prior to any publication of certificates issued by the CA and corresponding CRLs. Availability of systems publishing CA certificates is guaranteed 24/7 on a 24x7 basis.

#### 2.3.3 Publication of ARL

The ARL is updated at least once every year, and at each new revocation.

# 2.3.4 Publication of CRL

The CRL is updated at least every 24 hours, and at each new revocation.

# 2.4 Access Controls on Repositories

Access to information published to users is free. Access to change the publishing systems (add, delete, change the information published) is strictly limited to authorized internal functions of the PKI, through a strong access control, based on a two-factor authentication. Access to the publishing system requires a double authentication: user session and the use of a user certificate stored in a dedicated device.

The CP/CPS, and the TCSU are published in a read-only manner.



# IDENTIFICATION AND AUTHENTICATION

#### 3.1 Naming

#### 3.1.1 Types of names

In each certificate compliant with X.509 Standard, the issuing CA (corresponding to the "issuer" field) and the legal or natural person ("subject" field) are identified by a "Distinguished Name" conform with the requirements of the X.501 Standard.

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails	
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails	
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature	
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature	
CERTIGNA IDENTITY PLUS CA  Authentication/signature		
Names consisting of multiple words are permitted.		
Given names joined with a hyphen are considered as one single given name.		

Subjects with more than one given name may choose one or several of their given names in the sequence specified in their official identification document.

#### 3.1.2 Need for Names to Be Meaningful

The certificate DN identifies the legal or natural person and is built from the identity of the service, the server or the Subject specified in his/her identity document provided during the registration with the RA or the Certification Agent.

The DN format is defined at chapter "7.2 Profile of certificates and CRL" of this CP/CPS.

#### 3.1.3 Anonymity or Pseudonymity of Subscribers

The CA does not issue certificates with an anonymous identity.

#### Rules for Interpreting Various Name Forms 3.1.4

#### 3.1.4.1 Non-ASCII character substitution

The CA can operate the following conversion of non-ASCII characters:	
CERTIGNA IDENTITY PLUS CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails



- Accent characters may be represented by their ASCII equivalent. For example, é, à, í, ñ, or ç may be represented by e, a, i, n, or c, respectively.
- Umlaut-accented characters such as ä, ö, ü MAY be represented by either ae, oe, ue or a, o, u, respectively.

# 3.1.5 Uniqueness of Names

Note: The attribute serialNumber present in the DN field and the certificate serialNumber field are distinct data.

#### 3.1.5.1 CA Certificate

#### Root CAs & intermediate CAs

CA ensure that names positioned in the CN field of Intermediate CA certificates are unique in the CA perimeter.

# 3.1.5.2 Legal Person Certificate

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

The combination of the country of the entity and the identity of seal creation service uniquely identifies the certificate holder. The "serialNumber" field attribute also ensures the uniqueness of the DN. Throughout the lifetime of the CA, the name of the seal creation service attached to an entity cannot be assigned to another entity. The "serialNumber" attribute is made up from a unique random number generated by the CA and begin with one or more letters which indicates certificate's usage(s) and its storage mode:

- "S" for « Seal for e-mails »,
- "ST" for « Seal for e-mails » on hardware device.

#### 3.1.5.3 Natural Person Certificate

CERTIGNA IDENTITY PLUS CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature

The combination of the country, the name and the email address of the Certificate Subject uniquely identifies the Certificate Subject. The "serialNumber" attribute, unique value assigned to each certificate issued by the CA and present in the DN, also ensures the uniqueness of the DN. This field is made up from a unique random number generated by the CA and begin with a letter which indicates certificate's usage(s):

- "I" for "Authentication" and "Signature",
- "S" for "Signature" only.



# 3.1.6 Recognition, Authentication, and Role of Trademarks

The CA is responsible for the uniqueness of the names of legal or natural person used in its certificates and the resolution of disputes over the demand for use of a name. This commitment of responsibility rests on the assured level of control when processing license applications. The CA may possibly check the membership of the trademark with the INPI.

If the Subject Identity Information is to include a DBA or tradename, the CA verifies the Applicant's right to use the DBA/tradename using at least one of the following:

- Documentation provided by, or communication with, a government agency in the jurisdiction of the Applicant's legal creation, existence, or recognition,
- A Reliable Data Source,
- Communication with a government agency responsible for the management of such DBAs or tradenames,
- An Attestation Letter accompanied by documentary support; or
- A utility bill, bank statement, credit card statement, government-issued tax document, or other form of identification that the CA determines to be reliable.

The "organizationName" field can contain the organization's name and/or DBA/tradename. The CA can include information in this field that differs slightly from the verified name, such as common variations or abbreviations, provided that the CA documents the difference and any abbreviations used are locally accepted abbreviations, e.g. if the official record shows "Company Name Incorporated", the CA can use "Company Name Inc." or "Company Name". If both are included, the DBA/tradename appears first, followed by the organization's name in parentheses.



# 3.2 Initial identity validation

Registering a CM or Subject can be done either directly from the RA (RA or DRA) or via a Certification Agent of the entity. In the latter case, the Certification Agent must first be registered with the RA.

During the certificate request, the email address of the CM or Subject is verified through sending multiple emails that allow the CM or Subject to access to his/her CERTIGNA or DRA customer account and certain activation data enabling him/her to recover and to use its certificate.

The RA verifies that the entity has an operational existence by checking the QIIS or the QTIS in order to make sure that the entity appears there.

The certificate request can be communicated to the RA or the DRA in paper format signed by hand by the CM or the Subject and the co-signers. The request can also be communicated to the RA or the DRA in electronic format under the following conditions:

EN 319 411-2 QCP-n

EN 319 411-2 QCP-n-qscd

EN 319 411-2 QCP-I

EN 319 411-2 QCP-I-qscd

In electronic format if signed by each signatory using a qualified electronic signature certificate within the meaning of the elDAS Regulation. The certificate must be valid when registering by the RA.

RGS \*\*\*

In electronic format if signed using an electronic signature process that meets at least the requirements of the RGS level \*\*\*. The signature and associated certificate must be valid upon registration by the RA.

**RGS** \*\*

In electronic format if signed using an electronic signature process that meets at least the requirements of the RGS level \*\*. The signature and associated certificate must be valid upon registration by the RA.

EN 319 411-1 LCP

RGS \*

In electronic format if possible signed using an electronic signature process that meets at least the requirements of the RGS level \*.

# 3.2.1 Method to Prove Possession of Private Key

CA ensures the detention of the private key by the CM or the Subject before certifying the public key. For this, the RA, the CM or the Subject generates the key pair in a device compliant with the requirements of the chapter 11 and provides to the CA the proof of possession of the private key by signing his certificate request (Certificate signing request with the PKCS # 10 format).

The RA verifies beforehand the validity of the signature during the processing of the certificate requests received. This treatment is automated and therefore requires no human intervention. Any



signature error, due in particular to the non-possession of the private key associated with the public key to be certified, is systematically detected and causes the rejection of the request.

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

#### QCP-I-qscd

#### **RGS** \*\*

Evidence that the device complies with the requirements of Chapter 11 (At a minimum, the device's purchase invoice and the screen shots / prints of the hardware and software features of the device and the associated serial number) must be provided, when the application, by the Certificate Manager to attest to the possession of the device. The CA reserves the right to refuse the certificate application if it is found that this device does not meet these requirements.

The CA records the characteristics of the device, whether it is provided by the CA and checks monthly until the end of the validity period of the entity's certificate, maintaining the certification status of the device. In case of loss of the certification of the device, the CA will ask the Certificate Manager for proof that the key pair is stored in a device that meets the requirements of Chapter 11. The Certificate Manager undertakes to provide these evidence (E.g., Invoice of purchase of a new device certified QSCD, Minutes of ceremony of the keys in case of key migration, Minutes of update of the device for the maintenance of the certification, etc.) within a deadline 15 days following the request. If no evidence is provided or that the latter do not make it possible to determine if the storage conditions of the key pair, and transfer in another device if any, meet the requirements of this CP, the CA gives himself the right to revoke the certificate.

#### QCP-I-qscd

In the event that the device is managed by a Trust Service Provider other than CERTIGNA and the entity which is subject of the certificate, the Certificate Manager must provide at the certificate request, the evidences (E.g.: Certificate of qualification as a Certification Operator, certificate of qualification in as PSCE for the QCP-I-qscd level and associated signed contractual agreement between the entity designated in the certificate and that service provider, etc.) certifying that the provider is able to meet the requirements of this CP and in particular Chapter II.

#### 3.2.2 Validation of mailbox authorization or control

The CA verifies that CM or Subject controls the email accounts associated with all Mailbox Fields referenced in the Certificate or has been authorized by the email account holder to act on the account holder's behalf.

The CA do not delegate the verification of mailbox authorization or control.

# 3.2.2.1 Validating authority over mailbox via domain

No stipulation.



# 3.2.2.2 Validating control over mailbox via email

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA IDENTITY PLUS CA	Authentication/signature

The CA confirm the RC's or Subject's control over each Mailbox Field to be included in his/her Certificate by sending a Random Value via email and then receiving a confirming response utilizing the Random Value (e.g. Clickable link with a token allowing the Subject to access a confirmation page).

Control over each Mailbox Address is confirmed using a unique Random Value. The Random Value is sent only to the RC's or Subject's email address being validated and is not shared in any other way. The Random Value is unique in each email. The Random Value remains valid for use in a confirming response for no more than 24 hours from its creation.

The Random Value is reset upon each instance of the email sent by the CA to a Mailbox Address, and previous random values sent to this mailbox address are no longer valid.

# 3.2.2.3 Validating applicant as operator of associated mail server(s)

No stipulation.



# 3.2.3 Authentication of Organization Identity

The CA inspects any document relied upon under this Section for alteration or falsification.

# 3.2.3.1 Attribute collection of organization identity

The CA collects and retains evidence supporting the following identity attributes for the Entity:

- Formal name of the Legal Entity;
- A registered Assumed Name for the Legal Entity (if included in the Subject);
- An organizational unit of the Legal Entity (if included in the Subject);
- An address of the Legal Entity (if included in the Subject);
- Jurisdiction of Incorporation or Registration of the Legal Entity; and
- Unique identifier and type of identifier for the Legal Entity. The unique identifier is included in the subject:organizationIdentifier field of the certificate.

# 3.2.3.2 Validation of organization identity

# 3.2.3.2.1 Verification of name, address and unique identifier

The RA verifies the full legal name and an address (if included in the Certificate Subject) of the Legal Entity Applicant using documentation provided by, or through communication with, at least one of the following:

- A government agency in the jurisdiction of the Legal Entity's creation, existence, or recognition:
   The RA verifies that the status of the Applicant is not designated by labels such as "ceased," "inactive," "invalid," "not current," or the equivalent.
- An Attestation which includes a copy of supporting documentation used to establish the
  Applicant's legal existence, such as a certificate of registration, articles of incorporation,
  operating agreement, statute, or regulatory act) and its current status. The RA verifies that the
  status of the Applicant is not designated by labels such as "ceased," "inactive," "invalid," "not
  current," or the equivalent.
- A Legal Entity Identifier (LEI) data reference: the RA verifies that the RegistrationStatus is ISSUED and the EntityStatus is ACTIVE. The CA only allows use of an LEI if the ValidationSources entry is FULLY\_CORROBORATED. An LEI is not used if ValidationSources entry is PARTIALLY\_CORROBORATED, PENDING, or ENTITY\_SUPPLIED\_ONLY.

#### 3.2.3.2.2 Verification of assumed name

Applicants MAY request an Assumed Name to be included in the Certificate. The CA or RA verifies that:

- The Applicant has registered its use of the Assumed Name with the appropriate government agency for such filings in the jurisdiction of its incorporation or registration; and
- The Assumed Name filing continues to be valid. The CA may rely on an Attestation that
  indicates the Assumed Name under which the Applicant conducts business, the government
  agency with which the Assumed Name is registered, and that such filing continues to be valid.



#### 3.2.3.3 Disclosure of verification sources

Verification that the entity has the exclusive legal use of the name specified in the "Organization" field of the certificate is performed by reconciliation with information retrieved from official database (QIIS, QGIS, QTIS) confirming the existence of the entity. These databases contain reliable information provided by a trusted source that registered the entity. The information that is checked during the authentication of the entity's identity includes the SIREN or SIRET number, the VAT return number, the D-U-N-S number (Dun & Bradstreet). The controls applied are as follows:

For private organizations, checks are carried out in the QIIS or the QGIS (ex: directory of companies of France, registries of commercial courts, Dun & Bradstreet) to check:

- Legal existence: the RA checks that the entity's legal existence is established by the political subdivision in which the entity operates and is not designated on the records of the Incorporating or Registration Agency by labels such as "inactive", "invalid," "not current," or the equivalent,
- The name of the entity: the RA checks that the formal name as registered with the incorporating or registration agency of the entity's jurisdiction corresponds to that specified in the certificate request,
- The registration number: a registration number assigned by the incorporating or registration agency must be provided by the entity. In case of non-attribution of registration number by this organization the date of registration must be provided.
- The legal representative: the RA must obtain the name and address of a legal representative designated by the incorporating or registration agency of its jurisdiction.

For public entities, checks are carried out in the QIIS or the QGIS to verify:

- Legal existence: the RA checks that the entity is a legally recognized Government Entity, in existence in the political subdivision in which such Government Entity operates,
- The name of the entity: the RA checks that the entity's formal legal name as recognized by the Registration Agency in the entity's Jurisdiction of Registration matches the entity's name in the certificate request,
- The registration number: Attempt to obtain the specific unique Registration Number assigned to the entity by the registration agency in its Jurisdiction of registration. Where the registration agency does not assign a registration number, the CA integrates in the DN of the certificate that the entity is a public entity.

For business entities, checks are carried out in the QIIS or the QGIS to check:

- Legal existence: the RA checks that the applicant is engaged in business under the name submitted in the request.
- The name of the entity: the RA checks that the formal name as registered with the incorporating or registration agency of the entity's jurisdiction corresponds to that specified in the certificate request,
- The registration number: a registration number assigned by the incorporating or registration agency must be provided by the entity. In case of non-attribution of registration number by this organization the date of registration must be provided.
- The legal representative: the RA verifies the identity of the identified Principal Individual.



For non-commercial entities, checks are carried out in the QIIS or the QGIS to check:

- Legal existence: the RA checks that the entity is a legally recognized International Organization Entity,
- The name of the entity: the RA checks that the entity's formal legal name as recognized by the Registration Agency in the entity's Jurisdiction of Registration matches the entity's name in the certificate request,
- The registration number: the RA must obtain the Applicant's date of formation, or the identifier for the legislative act that created the International Organization Entity. In circumstances where this information is not available, the CA integrates in the DN of the certificate that the entity is an international organization entity.

In the case of a LEI data reference, the CA or RA SHALL verify the associated data record with the "Global Legal Entity Identifier Foundation" available at the following address: https://search.gleif.org/#/search/.

#### 3.2.3.4 Verification of PSD2 Authorization Number

#### CERTIGNA EMAIL PROTECTION LEGAL PERSON CA

Seal for mail

#### TS 119 495 DSP2

For PSD2 certificates, the identification of the PSP by the RA operator is achieved also with the authorization number of the PSP available in the NCA public register. In case there is no PSD2 Authorization Number, other form of registration number recognized by the NCA can be used in place of the PSD2 Authorization Number. If necessary, to ensure uniqueness, the authorization or registration number can contain a prefix including the type of the institution.

The information on the PSP and the NCA to be placed in the certificate is verified by the RA by checking the official information published on one of the following registers:

- the register of the national NCA in connection with the PSP. For example, in France, the NCA which is the APCR provides a Register of Financial Agents (REGAFI) to verify this information at the following address: https://www.regafi.fr;
- the register of the EBA, named "Payment Institutions Register" accessible at the following address https://euclid.eba.europa.eu/register/pir/disclaimer.



# 3.2.4 Validation of individual identity

Verification of the identity targets:

- A Certificate Manager for a legal person;
- A subject for a natural person;
- The legal representative of the organization attached to the certificate, if applicable;
- The Certification Agent associated with the organization, if applicable.

The CA collects and retains evidence supporting the following identity attributes for the subject or the CM:

- Given name(s) and surname(s), which are current names,
- Further information as needed to uniquely identify the subject or the CM.

The RA complies with applicable data protection legislation in the gathering and retention of evidence relating to Individual identity supporting this Requirement in accordance with Section 9.4.

# 3.2.4.1 Attribute collection of individual identity

The RA is using the following methods to collect Individual identity attributes.

# 3.2.4.1.1 From a physical identity document

To authenticate an individual's identity, verification of a photocopy of an individual's identification is required. It could be an official identity document valid (National Identity Card, passport, or residence permit) or a professional card issued by an administrative authority (if that authority maintaining a register of identities ensuring the link between the agent and the professional card) with an ID photo or a reference to the administrative file of the agent). The CA inspects the copy for any indication of alteration or falsification. The existence of the alleged identity is known to an authoritative source and the CA must be able to assume that the person is who he claims to be.

# 3.2.4.1.2 From a digital identity document

This method is not technically implemented and used by the CA for the moment.

If digital identity documents (passports or national ID cards including a chip bearing digitally signed information about the holder) are used as evidence, the RA only accepts eMRTD digital identity documents according to ICAO 9303 part 10. This method does not include "eID" as described in Regulation (EU) 910/2014.

# 3.2.4.1.3 Using electronic identification schemes (eID)

This method is not technically implemented and used by the CA for the moment.

If an eID is used as evidence, the CA or RA SHALL only accept "notified" eID schemes according to Article 9 of the eIDAS Regulation and the eID shall conform to eIDAS LoA "Substantial" or "High".



# 3.2.4.1.4 From a certificate supporting a digital signature applied by the Applicant

If a digital signature is to be used as evidence, the RA has the Applicant digitally sign the Certificate Request using a valid personal Certificate that was issued under an Approved Framework (Signature with a valid eIDAS or RGS/ETSI certificate as described below).

Identity attributes are evidenced by the signing Certificate, not by the content of the signed document. The RA only relies upon the signing Certificate as evidence for identity attributes if the digital signature is valid in accordance with the requirements of the relevant Approved Framework describe below.

# 3.2.4.1.5 From Enterprise RA records

In the case of Sponsor-validated Certificates approved by an Enterprise RA, records maintained by the Enterprise RA can be accepted as evidence of Individual identity. The CA still verifies the identity of the Individual in accordance with Section 3.2.4 and the Organization in accordance with Section 3.2.3.

#### 3.2.4.1.6 Affiliation from company attestation

In the case of Sponsor-validated Certificates not approved by an Enterprise RA, the CA verifies the authority or affiliation of an Individual to represent an Organization to be included in the subject:organizationName of the Certificate using an Attestation provided by the Organization and verified in accordance with Section 3.2.8. The RA still verifies the identity of the Individual in accordance with Section 3.2.4 and the Organization in accordance with Section 3.2.3.

#### 3.2.4.1.7 From a general attestation

Evidence for Individual identity attributes can be gathered using an Attestation from a qualified legal practitioner or notary in the Applicant's jurisdiction.

# 3.2.4.1.8 From authorized reference sources as supplementary evidence

Evidence for Individual identity attributes uses at least one of the following sources for authoritative evidence: a physical or digital identity document, digital signature supported by certificate, Enterprise RA records, or suitable Attestation.

The CA can additionally gather and verify supplementary evidence using authorized sources such as additional official documents, government or regulatory registers, or national population registers. Examples of this method include:

- If the Subject presents an ID featuring an Applicant name that has subsequently been changed, the evidence MAY be complemented by inspection of an official document such as a marriage certificate or court order documenting the change.
- If a professional Title of a regulated profession in the subject: country, or a corporate Title linked to the subject: organizationName, is to be used it can be verified against supporting documentation, a Reliable Data Source, or Attestation.



- In cases where the "role" LEI is included in an extension of a Sponsor-validated Certificate, the CA verifies that the LEI is assigned to the Individual and the subject:organizationName in the Certificate Subject.
- The CA can verify the address (but not the identity) of the Applicant using a governmentissued tax document, or other form of identification that the CA determines to be reliable.

#### 3.2.4.1.9 CA Certificate

#### Root and intermediate CAs

The registration of a new CA certificate request is achieved through the RA by the CA responsible. This request is formalized through a script during the key ceremony used for certificate generation.

#### 3.2.4.1.10 Legal Person Certificate

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

Registration of a service or server to which a certificate should be issued is performed via the registration of the corresponding Certificate Manager. A Certificate Manager may have to change valid corresponding server certificate. In this case, any new Certificate Manager shall also be subject to a registration procedure.

The Certificate Manager is either the legal representative of the entity or a natural person formally designated by the legal representative. The registration of a Certificate Manager, and the corresponding server can be done either directly from the RA, a DRA or via a Certification Agent of the entity. In this last case, the Certification Agent must have been registered by the RA.

The registration of the future Certificate Manager requires the "legal person" identity verification (the entity attached to the future Certificate Manager), and the "natural person" identity verification (the future Certificate Manager), his/her authorization to be a CM for the concerned service or server and the concerned entity.

The Certificate Manager is informed that personal identity information can be used as authentication data during a possible revocation request.



# 3.2.4.1.11 Certificate Manager Registration

CERTIGNA EM.	AIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EM	AIL PROTECTION LEGAL PERSON EU CA	Seal for Mails
The certificat	e request files shall be completed with the f	orms available on CERTIGNA website or DRA
website. The 1	files sent to RA shall include the following eler	ments:
Certificate r	equest form	
	Designation of a legal representative of th	
Subject  Designation of the future CM and his/her information  Designation of the identity of the entity attached to the service or server		
		ached to the service or server
	Designation of applicable TCSU	
Date	Signed less than 3 months ago	
Signature	Signed by a legal representative to manda	
	Signed by the future CM to accept this role	e and the TCSU
Official iden	tification document of the Certificate Manag	er
	A photocopy of a valid CM identification el	ement, recognized by the Member State in
Subject	which the request for a certificate is filed	· ,
Date	Piece valid at the time of registration	
Agent	tification document of the legal representativ  A photocopy of a valid identification ele	ement of the legal representative or the
Subject Certification Agent, recognized by the Member State in which the request for a certificate is filed		
Date	Piece valid at the time of registration	
Document o	attesting to the quality of legal representative	9
	recognized. e.g. a copy of the articles of t	ne quality of legal representative nationally the company, valid, bearing the signature
Subject	of its representatives.	
Subject	<b>For an administrative authority</b> , one piece of responsible authority of the administrat	e, support of delegation or sub-delegation tive structure nationally recognized.
Date	Piece valid at the time of registration	
Document b	pearing the SIREN number of the company	
	For a company, any document, valid at t	the time of registration, bearing the SIREN
Subject		Certificate of Identification at the National
Subject		ablishments) or, failing that, another valid
	document certifying the unique identificate certificate.	tion of the company to be included in the
Date	Piece valid at the time of registration	



#### TS 119 495 DSP2

For a PSD2 certificate, a document listing the characteristics of the PSP and referencing it in the NCA or EBA register if applicable.

#### EN 319 411-2 QCP-I

#### EN 319 411-2 QCP-I-qscd

The authentication of the CM by the RA is carried out via one of the following means:

- Face-to-face authentication with the CM with presentation of valid ID at the face-to-face (National Identity Card, Passport or Residence Card).
- Remote authentication using a means of electronic identification qualified at substantial or high level within the meaning of the eIDAS Regulation.
- Authentication using a nationally recognized identification method that provides equivalent assurance in terms of reliability to face to face authentication. The equivalent warranty is confirmed by a conformity assessment body.
- Authentication of the CM using a qualified electronic signature certificate as defined in the eIDAS Rules.

#### EN 319 411-1 LCP

Authentication of the Certificate Manager by the RA (RA or DRA operator) is performed by sending the files by postal mail or in a dematerialized form (scanned files which are sent by email).

#### **RGS** \*\*

Authentication of the Certificate Manager by the RA is performed during a physical face-to-face or in a dematerialized form at the condition that the request is signed by the Certificate Manager with an electronic signature process compliant with the minimum requirements of the RGS level \*\*, the signature is verified and valid at the time of registration.

#### RGS \*

Authentication of the Certificate Manager by the RA (RA or DRA operator) is performed by sending the files by postal mail or in a dematerialized form (scanned files which are sent by email).



# 3.2.4.1.12 Natural Person Certificate

# 3.2.4.1.12.1 Subject registration [Individual]

CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA IDENTITY PLUS CA	Authentication/signature

The certificate request files shall be completed with the forms available on CERTIGNA website or DRA website. The files sent to RA shall include the following elements:

Certificate re	equest form	
Cubinat	Designation of the future Subject and his/her contact information	
Subject	Designation of applicable TCSU	
Date	Signed less than 3 months ago	
Signature	Signed by the future Subject to accept this role and the TCSU	

	Official identification document of the Subject	
	Subject	A photocopy of an identity official document valid of the Subject with an ID photo. <i>E.g.:</i> national identity card, passport or residence permit
Date Piece valid at the time of registration		

#### EN 319 411-2 QCP-n

#### EN 319 411-2 QCP-n-qscd

The authentication of the Subject by the RA is carried out via one of the following means:

- Face-to-face authentication with the Subject with presentation of valid ID at the face-to-face (National Identity Card, Passport or Residence Card).
- Remote authentication using a means of electronic identification qualified at substantial or high level within the meaning of the elDAS Regulation.
- Authentication using a nationally recognized identification method that provides equivalent assurance in terms of reliability to face to face authentication. The equivalent warranty is confirmed by a conformity assessment body.
- Authentication of the Subject using a qualified electronic signature certificate as defined in the eIDAS Rules.

#### **RGS** \*\*\*

Identification of the Certificate Subject is performed by the RA during a physical face-to-face

#### RGS \*\*

Authentication of the Subject by the RA is performed during a physical face-to-face or in a dematerialized form at the condition that the request is signed by the Subject with an electronic signature process compliant with the requirements of RGS level \*\*\* minimum, the signature is verified and valid at the time of registration.

#### RGS \*

Authentication of the Subject by the RA (RA or DRA operator) is performed by sending the files by postal mail or in a dematerialized form (scanned files which are sent by email).



# 3.2.4.1.12.2 Subject registration [Company] [Administrative Authority]

	AIL PROTECTION NATURAL PERSON CA	Authentication/signature	
	AIL PROTECTION NATURAL PERSON EU CA	Authentication/signature	
	NTITY PLUS CA	Authentication/signature	
	·	e forms available on CERTIGNA website or DRA	
website. The	files sent to RA shall include the following e	elements:	
Certificate r	equest form		
	Designation of a legal representative of the entity and his/her information		
	Designation of the future Subject and his/her information		
Subject	Designation of the identity of entity attached to the service or server		
	Designation of applicable TCSU		
Date	Signed less than 3 months ago		
Signature	Signed by a legal representative to mar Signed by the future Subject to accept t	•	
Official iden	tification document of the Subject		
Subject		element of the Subject, recognized by the	
Member State in which the request for a certificate is filed		a certificate is filed	
Date	Piece valid at the time of registration		
Agent		element of the legal representative or the	
Subject	Certification Agent, recognized by the certificate is filed	Member State in which the request for a	
Date	Piece valid at the time of registration		
Document of	attesting to the quality of legal represental	tive	
		o the quality of legal representative nationally	
		the company, valid, bearing the signature of	
Subject	its representatives.		
For an administrative authority, one piece, support of delegation or sub-delegation			
	of responsible authority of the administ	rative structure nationally recognized.	
Date	Piece valid at the time of registration		
Document b	pearing the SIREN number of the company		
	For a company, any document, valid o	at the time of registration, bearing the SIREN	
Subject		or Certificate of Identification at the National	
oubject.	document certifying the unique identifi	stablishments) or, failing that, another valid cation of the company to be included in the	
Date	certificate.  Piece valid at the time of registration		
Dute	riece valid at the time of registration		



#### EN 319 411-2 QCP-n

#### EN 319 411-2 QCP-n-qscd

The authentication of the Subject by the RA is carried out via one of the following means:

- Face-to-face authentication with the Subject with presentation of valid ID at the face-to-face (National Identity Card, Passport or Residence Card).
- Remote authentication using a means of electronic identification qualified at substantial or high level within the meaning of the elDAS Regulation.
- Authentication using a nationally recognized identification method that provides equivalent assurance in terms of reliability to face to face authentication. The equivalent warranty is confirmed by a conformity assessment body.
- Authentication of the Subject using a qualified electronic signature certificate as defined in the eIDAS Rules.

#### **RGS** \*\*\*

Identification of the Certificate Subject is performed by the RA during a physical face-to-face

#### **RGS** \*\*

Authentication of the Subject by the RA is performed during a physical face-to-face or in a dematerialized form at the condition that the request is signed by the Subject with an electronic signature process complies with the requirements of RGS level \*\*\* minimum, the signature is verified and valid at the time of registration.

#### RGS \*

Authentication of the Subject by the RA (RA or DRA operator) is performed by sending the files by postal mail or in a dematerialized form (scanned files which are sent by email).



# 3.2.4.1.13 Registration of a Certification Agent

The Certification Agent must register with the RA to substitute for RA in the processing of registration of certificate requests. The registration of a Certification Agent requires the verification of the "legal person" identity of the entity for which the Certification Agent is attached, the verification of the "natural person» identity of the future Certification Agent, and the relation between the future Certification Agent and this entity. The certificate request files shall be completed with the forms available on CERTIGNA website or DRA website. The files sent to RA shall include the following elements:

Certification	Agent registration form	
Designation of a legal representative of the entity and his/her informati		
Subject	Designation of the future Certification Agent and his/her information	
	Designation of applicable Terms and conditions	
Date	Signed less than 3 months ago	
Signature	Signed by a legal representative to mandate the Certification Agent	
	Signed by the future Certification Agent to accept this role and the TCSU	

Letter of com	nmitment from the Certification Agent	
	Designation of the future Certification Agent and its information	
	Designation of the role and responsibilities of Certification Agent with:	
Subject	- Conduct impartial and scrupulous identity checks of the future Subjects as defined in the CP,	
	- Notify the RA on leaving the entity.	
Date	Signed less than 3 months ago	
Signature	Signed by the future Certification Agent to accept these responsibilities	

Official identification document of the Certification Agent		
Subject	A photocopy of a valid identification element of the Certification Agent, recognized by the Member State in which the request for a certificate is filed	
Date Piece valid at the time of registration		

	Document a	cument attesting to the quality of legal representative		
Subject its representatives.	Subject	[Administrative authority] One piece, support of delegation or sub-delegation of		
Date Piece valid at the time of registration	Date	Piece valid at the time of registration		



#### EN 319 411-2 QCP-I

#### EN 319 411-2 QCP-I-qscd

The authentication of the Certification Agent by the RA is carried out via one of the following means:

- Face-to-face authentication with the Certification Agent with presentation of valid ID at the face-to-face (National Identity Card, Passport or Residence Card).
- Remote authentication using a means of electronic identification qualified at substantial or high level within the meaning of the elDAS Regulation.
- Authentication using a nationally recognized identification method that provides equivalent assurance in terms of reliability to face to face authentication. The equivalent warranty is confirmed by a conformity assessment body.
- Authentication of the Certification Agent using a qualified electronic signature certificate as defined in the eIDAS Rules.

#### **RGS** \*\*

Authentication of the Certification Agent by the RA is performed during a physical face-to-face or in a dematerialized form at the condition that the request is signed by the Certification Agent with an electronic signature process complies with the requirements of RGS level \*\*\* minimum, the signature is verified and valid at the time of registration.

#### EN 319 411-1 LCP

#### RGS \*

The authentication of the Certification Agent by the RA is carried out by sending the paper file by postal mail accompanied by a photocopy of the identity documents of each of the signatories of the documents in the file (legal representative, Certification Agent).

This authentication can also be done in dematerialized form on condition that the various supporting documents of the file are signed using an electronic signature process in accordance with the requirements of the RGS level \* and that the signature is verified and valid at the time of recording. If the Certification Agent is not equipped with a certificate of RGS level \* or higher, the files cannot be sent in dematerialized form. In this case, each file will only be validated after receipt of the original documents by postal mail.



#### 3.2.4.2 Validation of individual identity

The CA or RA validates all identity attributes of the Individual to be included in the Certificate.

If the evidence has an explicit validity period, the CA verifies that the time of the identity validation is within this validity period. In context this can include the notBefore and notAfter fields of a digital signature Certificate or the date of expiry of an identity document. The CA can reuse existing evidence to validate Individual identity subject to the age restrictions in Section 4.2.1.

#### 3.2.4.2.1 Validation of a physical identity document

The physical identity document shall be presented in its original form.

The CA employes procedures to ensure the evidence presented by the Applicant is a genuine identity document that is not counterfeited or falsified/modified. The CA uses manual (in person with a physical face to face) or remote procedures.

A remote process ensures that the Applicant has the document in hand and presents the document in real-time in front of a camera. The CA or RA registration agent makes a visual comparison of the physical appearance of the Applicant and the face photo and/or other information on the physical identity document. For this process, CERTIGNA is using a service provider qualified on the French standard "Prestataire de verification d'identité à distance" (PVID).

The CA or RA registration agent has access to authoritative sources of information on document appearance and validation for forms of identity document accepted by the CA. The CA or RA retains information sufficient to evidence the fulfillment of the identity validation process and the verified attributes.

In addition to identity attributes, the CA or RA records the following information: issuer, validity period, and the document's unique identification number.

#### 3.2.4.2.2 Validation of a digital identity document

This method is not technically implemented and used by the CA for the moment.

The CA or RA will only accept digital identity documents if the issuer's digital signature on the document is successfully validated according to ICAO 9303 part 11. The CA or RA will record information obtained from the digital identity document to evidence the identity proofing process. In addition to identity attributes and face photo, the following information will be recorded: issuer, validity period, and the document's unique identification number. The CA or RA registration agent will make a visual comparison of the physical appearance of the Applicant and the face photo and/or other information on the digital identity document.



#### 3.2.4.2.3 Validation of eID

#### This method is not technically implemented and used by the CA for the moment.

If authentication using an eID is used as evidence, the CA or RA will confirm that the eID scheme is suitable (i.e., that the eID is accessible via a "notified" eIDAS-Node), and that the individual eID is valid (i.e., not expired, suspended, or revoked). The authentication using the eID will be created as part of the identity validation process, and evidence of the validation with the eID's Identity Provider (IdP) will be retained by the CA or RA.

# 3.2.4.2.4 Validation of digital signature with certificate

If a digital signature with Certificate is used as evidence, the signature shall be created as part of the identity validation process. The CA or RA validates the digital signature and uses only the signing Certificate as evidence for identity attributes if the signature is valid. If required identity attributes to be collected are not present in the Certificate, the CA or RA collects these attributes from other sources and validate them accordingly.

#### 3.2.4.2.5 Validation of an Attestation

If an Attestation is used as evidence for the validation of Individual identity attributes, then the reliability of the Attestation is verified according to Section 3.2.8.

#### 3.2.4.2.6 Validation using an Enterprise RA record

An Enterprise RA issuing a Sponsor-validated Certificate validates all identity attributes of an Individual to be included in the Certificate. The Enterprise RA relies upon existing internal records to validate Individual identity.

#### 3.2.5 Non-verified subscriber information

Subject or service information that has not been verified in accordance with these Requirements is not included in Publicly-Trusted S/MIME Certificates.

# 3.2.6 Validation of Authority

This step is performed simultaneously with the validation of the identity of the legal representative, the CM or the Subject (directly by the RA or the Certification Agent).

Before commencing to issue Organization-validated and Sponsor-validated Certificates for an Applicant, the CA or RA uses a Reliable Method of Communication to verify the authority and approval of an Applicant Representative to perform one or more of the following:

- to act as an Enterprise RA;
- · to request issuance or revocation of Certificates; or
- to assign responsibilities to others to act in these roles.



The CA or RA establishes a process that allows an Applicant to specify the individuals who may act as Applicant Representatives on an ongoing basis. The CA provides an Applicant with a list of its authorized Applicant Representatives upon the Applicant's verified written request.

The CA or RA may use the sources listed in Section 3.2.3.2.1 to verify the Reliable Method of Communication. Provided that the CA or RA uses a Reliable Method of Communication, the CA or RA may establish the authenticity of the Certificate Request directly with the Applicant Representative or with an authoritative source within the Applicant's organization, such as the Applicant's main business offices, corporate offices, human resource offices, information technology offices, or other department that the CA or RA deems appropriate.

#### 3.2.7 Criteria for Interoperation

The CA disclose all Cross Certificates that identify the CA as the Subject, provided the CA has arranged for or accepted the establishment of the trust relationship (i.e. the Cross Certificate at issue).

# 3.2.8 Reliability of verification sources

Before relying on a source of verification data to validate Certificate Requests, the CA verifies its suitability as a Reliable Data Source. Enterprise RA records are a Reliable Data Source for Individual Subject attributes included in Sponsor-validated Certificates issued to the Enterprise RA's Organization.

The CA or RA may rely upon a letter attesting that Subject Information or other fact is correct. The CA or RA verifies that the letter was written by an accountant, lawyer, government official, or other reliable third party in the Applicant's jurisdiction customarily relied upon for such information.

An Attestation shall include a copy of documentation supporting the fact to be attested. The CA or RA uses a Reliable Method of Communication to contact the sender and to confirm the Attestation is authentic.



# 3.3 Identification and Authentication for Re-key Requests

# 3.3.1 Identification and Authentication for Routine Re-key

The CA does not issue a new certificate for previously issued key pair. Renewal involves through the generation of a new key pair and a new certificate request.

#### 3.3.1.1 CA Certificate

Identifying and authenticating a current CA certificate renewal request is the same as the original request.

#### 3.3.1.2 Legal Person Certificate

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails

At the first renewal, the CA at a minimum ensures that the information in the initial registration request is still valid and that the certificate to be renewed exists and is still valid.

At the next renewal, the RA identifies the Certificate Manager and the application service or the server according to the same procedure as for the initial registration

Documents provided to validate the identity of the Subject, the CM, the Legal Representative and the entity may be used in compliance with requirements of section 4.2.1.2.

For validation of Domain Names according to Section 3.2.2.4, any data, document, or completed validation used is obtained no more than the delay described at section 4.2.1.2.

#### 3.3.1.3 Natural Person Certificate

CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA IDENTITY PLUS CA	Authentication/signature

At the first renewal, the CA at a minimum ensures that the information in the initial registration request is still valid and that the certificate to be renewed exists and is still valid.

At the next renewal, the RA identifies the Subject and the entity if applicable, through the same procedure as for the initial registration

Documents provided to validate the identity of the Subject, the CM, the Legal Representative and the entity may be used in compliance with requirements of section 4.2.1.2.

# 3.3.2 Identification and Authentication for Re-key After Revocation

Identification and authentication for re-key after revocation is the same as the original request.



# 3.4 Identification and authentication for revocation request

#### 3.4.1 CA Certificate

A CA certificate revocation can only be decided by the entity responsible of the CA, or by legal authority through a justice decision.

The revocation of other component certificates is decided by the entity operating the component concerned, which must inform the CA without delay.

# 3.4.2 Legal or Natural Person Certificate

#### 3.4.2.1 Current request

The certificate revocation request sent by the Certificate Manager, the Subject, the legal representative of the entity, a DRA operator, or if appropriate a Certification Agent can be done by one of the following means:

- Mail: request completed and signed from the form of revocation of a certificate available on the website of CERTIGNA <a href="https://www.certigna.com">https://www.certigna.com</a>. The requester is authenticated by sending its Official identification document with the mail.
- From the customer area of the CERTIGNA website https://www.certigna.com selecting the certificate to be revoked.

The mailing address of the revocation service is available on the website of CERTIGNA https://www.certigna.com.

The paper request must include the following:

- The first and last name of the subject or name of the service or the server,
- The email address of the Subject if applicable,
- The reason for the revocation.

If the Certificate Manager or the Subject is not the subscriber:

- The first and last name of the subscriber,
- The quality of the subscriber (legal representative, DRA operator, Certification Agent),
- The subscriber's phone number.

The paper form can also be transmitted electronically. The electronic application can be performed by an authorized person with a certificate of the same level or higher (a DRA operator or if appropriate a Certification Agent). The application will be electronically signed with this certificate of the same level or higher. The revocation request processing by the RA is detailed in the "Operational Revocation Request Procedure". As with certificate applications, periodic audits may consider sample checks of revocation requests processed by the RA to ensure compliance with procedures.



#### 3.4.2.2 Request from a NCA

An authenticated NCA is authorized to request the revocation of the certificate of a PSP present in its registry. This request must be made by email to security@certigna.com by enclosing a request for revocation in French or in English language. This revocation request must be electronically signed using an advanced signature or an advanced seal process based on a qualified certificate as defined in elDAS regulation and whose organization designated as the subject in the certificate is the NCA.

The certificate revocation request must specify the following information:

- NCA identifier
- Contact details of the applicant,
- Identifier of the PSP subject of the revocation request,
- Reason for which the certificate must be revoked:
  - o The authorization of the PSP has been revoked,
  - o Any PSP included in the certificate has been revoked.

Upon NCA's request and confirmation by CERTIGNA, the CA will be able to provide a certificate in accordance with its issuance process and to authenticate NCA requests.

One of the following cases may lead the CA to reject the revocation request or to request additional information:

- If the authenticity of the request is not verifiable,
- If the request does not clearly indicate the reason for revocation of the certificate,
- If the reason for the revocation of the certificate is not the responsibility of the requesting NCA.



# 4 CERTIFICATE REQUIREMENTS

# LIFE-CYCLE

# **OPERATIONAL**

# 4.1 Certificate Application

## 4.1.1 Who Can Submit a Certificate Application

#### 4.1.1.1 CA Certificate

The certificate request must come from a legal representative of the entity.

# 4.1.1.2 Legal or Natural Person Certificate

For certificates attached to an organization, the certificate request must come from a legal representative of the entity or from a Certification Agent duly mandated for this entity, with the prior consent of the future Certificate Manager or Subject.

# 4.1.2 Enrolment Process and Responsibilities

#### 4.1.2.1 CA Certificate

The registration files are established directly by the Certification Authority during the Key ceremony.

# 4.1.2.2 Legal or Natural Person Certificate

Prior to the issuance of a Certificate, the CA obtains the following documentation from the Applicant:

- A Certificate Request; and
- An executed Subject or CM Agreement and/or Terms of Use.

The Certificate Request and Subject or CM Agreement or Terms of Use is in a form prescribed by the CA and complies with these Requirements including Section 9.6.3.

The Certificate Request contains a request from, or on behalf of, the Subject or service for the issuance of a Certificate, and a certification by, or on behalf of, the Subject or CM that all of the information contained therein is correct.

One Certificate Request may suffice for multiple Certificates to be issued to the same Subject or Service, subject to the validation reuse periods described in Section 4.2.1, provided that each Certificate is supported by a valid, current Certificate Request signed by the Subject, the CM on behalf of the Subject or service.

The registration files are established directly by the future CM or the Subject from the evidence provided by his entity if applicable, or by the entity and signed by the CM or the Subject. The files are



transmitted directly to the RA if the entity has not implemented the use of Certification Agent. The files are delivered to it otherwise.

When recording of the future CM or Subject, it must provide an email address that allows the RA to contact for any questions regarding registration. The Certification Agent must also provide an email address when registering for allows the RA to contact him on any matter relating to the registration of the CM or the Subject. The certificate application must contain the elements described in section 3.2.3.

A certificate requiring authentication of the Subject or CM by means of a physical face-to-face, an eID, or an electronic signature using an eIDAS-qualified certificate, can only be renewed after reauthentication of the Subject or CM via one of these processes. The process used for renewal (e.g. an eIDAS-qualified certificate to sign the renewal application) must itself have been issued on the basis of a physical face-to-face.

The email address of the Certificate Manager or the Subject, and where applicable the Certification Agent, is stored in the RA databases. These addresses are used to transmit service messages when processing certificate or revocation requests, or for additional requests made by RA operators processing these requests.

# 4.2 Certificate Application Processing

# 4.2.1 Performing Identification and Authentication Functions

#### 4.2.1.1 CA Certificate

The request is validated by all witnesses which participate to the key ceremony comprising one RA administrator.

#### 4.2.1.2 Legal or Natural Person Certificate

Applicant information include, but not be limited to, at least one Mailbox Field to be included in the Certificate's subjectAltName extension. Section 6.3.2 limits the validity period of Subject or service Certificates.

The CA may reuse completed validations and/or supporting evidence performed in accordance with Section 3.2 within the following limits:

- Validation of mailbox authorization or control: Completed validation of control of a mailbox in accordance with Section 3.2.2.2 is obtained no more than 30 days prior to issuing the Certificate.
- Authentication of organization identity: Completed validation of organization identity in accordance with Section 3.2.3 is obtained no more than 825 days prior to issuing the Certificate. Validation of authority in accordance with Section 3.2.6 is obtained no more than 825 days prior to issuing the Certificate, unless a contract between the CA and the Applicant specifies a different term. For example, the contract may include the perpetual assignment of roles until revoked by the Applicant or CA, or until the contract expires or is terminated.



 Authentication of individual identity: Completed validation of Individual identity in accordance with Section 3.2.4 is obtained no more than 825 days prior to issuing the Certificate.

A prior validation is not reused if any data or document used in the prior validation was obtained more than the maximum time permitted for reuse of the data or document prior to issuing the Certificate. Documents provided to validate the identity of the Subject, the CM, the Legal Representative and the entity may be used for 825 days to issue a certificate, only if they are still valid at the time the certificate application validation.

The RA does the following operations when processing a certificate request:

- Validation of the service, or the Subject's identity,
- Validation of the identity of the entity,
- Validation of the identity of the signatory of the request (CM or Subject, legal representative, or Certification Agent),
- Validation of the files and the consistency of evidence presented,
- Assurance that the future CM or Subject is informed of the applicable requirements to the use of the certificate.

All the operations mentioned above are carried out by the RA, but in the case of a request made via a DRA or a Certification Agent, the latter retransmits the request to the RA after having carried out the following checks:

- Ensure that the future Certificate Manager or the Subject has been informed of the TCSU, in addition to their distribution operated by the CA.
- Check the identity of the CM or the Subject and the original documents attesting to his identity to identify and authenticate him/her.
- Check the completeness of the request file.

The RA then ensures that the request corresponds to the mandate of the DRA operator or the Certification Agent. The identity of the future Subject and the legal representative is approved if the supporting documents provided are valid at the date of receipt.

#### CERTIGNA EMAIL PROTECTION LEGAL PERSON CA

Seal for mails

#### TS 119 495 DSP2

For PSD2 certificates, the CA verifies information from the PSP and the associated NCA (PSP identifier and its roles, identifier and country of the NCA) through information officially provided by NCA on its register or on the register of the EBA. In the case where the associated NCA recommends specific validations to be carried out, these will be carried out by the CA if necessary.

# 4.2.2 Approval or Rejection of Certificate Applications

After processing the request, in case of rejection, the RA notifies the CM or the Subject, if applicable the operator of DRA, or the Certification Agent. The justification for any refusal is made by the RA specifying the cause:

The request files are incomplete (missing document),



- One of the documents is invalid (the date of validity of a document is exceeded, etc.),
- The request does not match with the mandate of the DRA operator or the Certification Agent.

If accepted by the RA, after generation of the certificate by the CA, the RA sends a mail to the RC or the Subject to complete the certificate acceptation and the acquisition of activation data.

#### 4.2.2.1 Certification authority authorization

Starting on March 15, 2025 prior to issuing a Certificate that includes a Mailbox Address, the CA retrieves and processes CAA records in accordance with Section 4 of RFC 9495: Certification Authority Authorization (CAA) Processing for Email Addresses.

Some methods relied upon for validating the Applicant's control over the domain portion of the Mailbox Address to be used in the Certificate (see Section 3.2.2.1 and Section 3.2.2.3) require CAA records to be retrieved and processed from additional remote Network Perspectives before Certificate issuance (see Section 4.2.2.2). To corroborate the Primary Network Perspective, a remote Network Perspective's CAA check response is interpreted as permission to issue, regardless of whether the responses from both Perspectives are byte-for-byte identical. Additionally, the CA can consider the response from a remote Network Perspective as corroborating if one or both of the Perspectives experience an acceptable CAA record lookup failure, as defined in this section.

When processing CAA records, the CA processes the issuemail property tag as specified in RFC 9495. Additional property tags may be supported, but shall not conflict with or supersede the authorizations to issue S/MIME Certificates as specified in the issuemail property tag.

If the CA issues a Certificate following a CAA check, they shall do so within the TTL of the CAA record, or 8 hours, whichever is greater. This stipulation does not prevent the CA from checking CAA records at any other time.

If the Certificate includes more than one Mailbox Address, then the CA performs the above procedure for each Mailbox Address.

The CA do not issue a Certificate unless the CA determines that Certificate Request is consistent with the applicable CAA RRset. The CA logs all actions taken, if any, consistent with its CAA processing practice.

The CA is permitted to treat a record lookup failure as permission to issue if:

- the failure is outside the CA's infrastructure; and
- the lookup has been retried at least once; and
- the domain's zone does not have a DNSSEC validation chain to the ICANN root.

#### 4.2.2.2 Multi-perspective issuance corroboration

Effective May 15, 2025 CAs implements Section 3.2.2.9 of the TLS Baseline Requirements.



# 4.2.3 Time to Process Certificate Applications

#### 4.2.3.1 CA Certificate

As the request for a CA certificate is formally established during the key ceremony, the concerned certificate is generated within hours of the request.

#### 4.2.3.2 Legal or Natural Person Certificate

As from the receipt of the full registration files and electronic request (CSR), the certificate is issued within 30 days.

#### 4.3 Certificate Issuance

# 4.3.1 CA Actions during Certificate Issuance

#### 4.3.1.1 Manual authorization of certificate issuance for Root CAs

Keys pairs of Root CA and intermediate CA are generated during the key ceremony. The operations for generating and signing certificates issued by the root CA are carried out under the same controlled circumstances as the generation of CA key pairs (see section 6.1.1), in the presence of people in authorized trusted roles by CA and as part of "key ceremonies". The CA administrator performs commands to generate and sign certificates by the root CA in the presence of trusted roles which ensure that practices comply with security requirements and the defined script.

# 4.3.1.2 Linting of to-be-signed Certificate content

Effective September 15, 2025 the CA implements a Linting process testing compliance with the Requirements for S/MIME Certificates.

#### 4.3.1.3 Linting of issued Certificates

The CA uses a linting process to test each issued certificate.

#### 4.3.1.4 Legal or Natural Person Certificate

After validation by the RA, the CA initiates the certificate generation process for the CM or the Subject. The conditions for generating keys and certificates and security measures to meet are described in Chapters 5 and 6 below, including the separation of trusted roles. (See section 5.2). Request validation on the RA component and certificate generation on the CA component are detailed in the "Certificate request operating procedure".



# 4.3.2 Notification to Subscriber by the CA of Issuance of Certificate

#### 4.3.2.1 CA Certificate

The delivery of the CA certificate is carried out during the key ceremony, to a CA administrator authorized by the CA in charge of its exploitation and dissemination.

#### 4.3.2.2 Legal or Natural Person Certificate

Complete and accurate certificate is made available to the CM or the Subject on the customer area or on the device provided by CA if applicable. The CM or the Subject authenticates on the customer area to accept the certificate or complete a paper form.

# 4.4 Certificate Acceptance

# 4.4.1 Conduct Constituting Certificate Acceptance

#### 4.4.1.1 CA Certificate

The authority representant and the witnesses, which participate to the key ceremony, control the compliance of the certificate with the request. The acceptance is formalized through the record of the key ceremony.

#### 4.4.1.2 Legal or Natural Person Certificate

The acceptance of the certificate is carried out by the CM or the Subject, from their customer area and before downloading their certificate or retrieving the activation data from their support. The CM or the Subject explicitly chooses whether to accept the certificate and the notification of acceptance or refusal is automatically transmitted to the CA.

In case of detection of inconsistency between the information in the contractual agreement and the content of the certificate, the CM or the Subject must refuse the certificate, which will result in its revocation.

#### 4.4.2 Publication of the Certificate by the CA

# 4.4.2.1 CA Certificate

Root CA and intermediate certificates are published by CA. See Section 2.

# 4.4.2.2 Legal or Natural Person Certificate

Certificates issued by the CA are not published.



# 4.4.3 Notification of Certificate Issuance by the CA to Other Entities

The RA is informed of the generation of the certificate by the CA which is responsible for issuing the generated certificate.

# 4.5 Key Pair and Certificate Usage

# 4.5.1 Subject Private Key and Certificate Usage

The CA, the CM, or the Subject must strictly respect the permitted uses of key pairs and certificates described at chapter 1.5.1. In the opposite case, they could be held liable.

The authorized use of the key pair and of the associated certificate is also specified in the certificate itself, via the extensions relating to the key usage, if applicable.

As part of the registration files, the Terms and condition are made known to the CM, to the Subject or to the Certification Agent by the CA before entering in a contractual relationship. They are consulted prior to any online certificate request. They are available on the <a href="https://www.certigna.com">https://www.certigna.com</a> website.

The TCSU accepted by the Subject during the certificate request shall remain valid for the entire life of the certificate, or if necessary to the acceptance and signature by the CM or the Subject of new Terms and Conditions issued and made available to it by CA via <a href="https://www.certigna.com">https://www.certigna.com</a> website. Signed new Terms and Conditions must be provided by the CM or the Subject to the CA to be applicable.

# 4.5.2 Relaying Party Public Key and Certificate Usage

Certificate users must strictly respect the permitted uses of certificates mentioned at section 1.5.1. In the opposite case, they could be held liable.

#### 4.6 Certificate Renewal

The CA does not issue a new certificate for previously issued key pair. Renewal involves the generation of a new key pair and a new certificate request (see section 4.1). If the CM or the Subject generates his/her key pair, he is committed, accepting the TCSU, to generate a new key pair for each request.

#### 4.6.1 Circumstance for Certificate Renewal

No stipulation.

#### 4.6.2 Who May Request Renewal

No stipulation.



# 4.6.3 Processing Certificate Renewal Requests

No stipulation.

#### 4.6.4 Notification of new certificate issuance to subscriber

No stipulation.

#### 4.6.5 Conduct constituting acceptance of a renewal certificate

No stipulation.

# 4.6.6 Publication of the renewal certificate by the CA

No stipulation.

#### 4.6.7 Notification of certificate issuance by the CA to other entities

No stipulation.

# 4.7 Certificate Re-key

# 4.7.1 Circumstance for Certificate Re-key

The key pairs must be periodically renewed to minimize the possibilities of cryptographic attacks. Thus, the key pairs of CAs, services, servers, the Subjects, and the corresponding certificates, are renewed regularly (cf. validity period chapter 6.3.2). Moreover, a key pair and a certificate can be renewed early, following the revocation of the certificate.

# 4.7.2 Who may Request Certification of a New Public Key

The triggering of the provision of a new certificate is initiated by the CM or the Subject (no existence of automated process). The entity, through its Certification Agent if necessary, can also be at the initiative of a new certificate request for a CM or a Subject attached to it.

#### 4.7.3 Processing certificate re-keying requests

See section 4.2.1.

# 4.7.4 Notification of new certificate issuance to subscriber

See section 4.3.2.



# 4.7.5 Conduct constituting acceptance of a re-keyed certificate

See section 4.4.1.

# 4.7.6 Publication of the re-keyed certificate by the CA

See section 4.4.2.

#### 4.7.7 Notification of certificate issuance by the CA to other entities

See section 4.4.3.

#### 4.8 Certificate modification

Changing Subject certificates is not allowed. In case of need to change information in the certificate (mainly DN), a new certificate must be issued after revocation of the old.

#### 4.8.1 Circumstance for Certificate Modification

No stipulation.

# 4.8.2 Who May Request Certificate Modification

No stipulation.

# 4.8.3 Processing Certificate Modification Requests

No stipulation.

# 4.8.4 Notification of New Certificate Issuance to Subscriber

No stipulation.

#### 4.8.5 Conduct Constituting Acceptance of Modified Certificate

No stipulation.

# 4.8.6 Publication of the Modified Certificate by the CA

No stipulation.



# 4.8.7 Notification of Certificate Issuance by the CA to Other Entities

No stipulation.

# 4.9 Certificate Revocation and Suspension

#### 4.9.1 Circumstances for Revocation

#### 4.9.1.1 Reasons for Revoking a Legal or Natural Person Certificate

The CA revokes a Certificate within 24 hours and uses the corresponding CRLReason if one or more of the following occurs:

- The Subscriber requests in writing that the CA revoke the Certificate;
- Privilege withdrawn (RFC 5280 CRLReason #9) The subscriber, The legal representative of the entity to which the service, or the Subject belongs notifies the CA that the original certificate request was not authorized and does not retroactively grant authorization,
- Key compromise (RFC 5280 CRLReason #1) The CA obtains verifiable evidence that the private key corresponding to the public key in the certificate is suspected of being compromised or is compromised,
- Key compromise (RFC 5280 CRLReason #1) The CA is made aware of a demonstrated or proven method that exposes the Private Key to compromise or if there is clear evidence that the specific method used to generate the Private Key was flawed. Methods have been developed that can easily calculate it based on the Public Key (such as a Debian weak key, see <a href="http://wiki.debian.org/SSLkeys">http://wiki.debian.org/SSLkeys</a>),
- The CA obtains evidence that the validation of domain authorization or mailbox control for any Mailbox Address in the Certificate should not be relied upon.

The CA should revoke a Certificate within 24 hours and revokes a Certificate within 5 days if one or more of the following occurs:

#### Key compromise (RFC 5280 CRLReason #1)

- The CA is made aware of a demonstrated or proven method that exposes the Private Key to compromise or if there is clear evidence that the specific method used to generate the Private Key was flawed.
- The CM or the Subject, the legal representative of the entity to which it belongs, if any Certification Agent or DRA operator request the revocation of the certificate (especially in the case of destruction or alteration of the private key and / or its support) because they have reason to believe that the private key of the certificate has been compromised, e.g. an unauthorized person has had access to the private key of the certificate.

#### Privilege withdrawn (RFC 5280 CRLReason #9)

- o The CA obtains evidence that the certificate was misused,
- The CA is made aware that the subject has violated one or more of its material obligations under these TCSU



- o The CA is made aware of a material change in the information contained in the Certificate
- The CA determines or is made aware that any of the information appearing in the certificate is inaccurate or misleading,
- The cryptographic device used to store the certificate and the private key of the Subject or of the CM no longer complies or will no longer comply with the requirements of chapter 11 of the CP/CPS (Ex: a qualification or certification would no longer be maintained or would be suspended),
- The legal representative of the entity to which the service, the server or the Subject belongs notifies the CA that the original certificate request was not authorized and does not retroactively grant authorization,

#### - **Cessation of operation** (RFC 5280 CRLReason #5)

- The CA is made aware of any circumstance indicating that use of an email address, a Fully–Qualified Domain Name or IP address in the Certificate is no longer legally permitted (e.g. a court or arbitrator has revoked a Domain Name Registrant's right to use the email address or the Domain Name, a relevant licensing or services agreement between the Domain Name Registrant and the Applicant has terminated, or the Domain Name Registrant has failed to renew the Domain Name).
- o The final shutdown of the service or the cessation of activity of the CM entity,
- The departure of the Subject from the entity or the cessation of activity of the entity attached to the Subject,
- The CM no longer controls, or is no longer authorized to use, all of the domain names in the certificate,

#### - Affiliation changed (RFC 5280 CRLReason #3)

- The information of the service, or the Subject contained in its certificate, is not in accordance with the identity or purpose in the certificate (eg, change in the identity or function of the server), this before the normal expiry of certificate,
- Information in the Public Register has changed to substantially affect the validity of the PSD2 attributes in the certificate,
- o the authorization status granted by that NCA has changed (e.g., that PSP is no longer authorized or one of its roles has been revoked).

#### - **Superseded** (RFC 5280 CRLReason #4)

- The certificate no longer complies with the requirements of Sections 6.1.5 and 6.1.6 of the CP/CPS.
- o The CA is made aware that the certificate was not issued in accordance with this CP/CPS;
- The CM, the subject, the entity, if any Certification Agent or DRA operator, has not fulfilled its obligations under this CP/CPS,
- o The CM or the Subject has requested a new certificate to replace an existing certificate,



# - Other reason of revocation which results in no reasonCode extension being provided in the CRL:

- The CA's right to issue certificates under CA/Browsers Forum Requirements expires or is revoked or terminated, unless the CA has made arrangements to continue maintaining the CRL/OCSP Repository,
- The CM or the Subject, the legal representative of the entity to which it belongs, requests in writing, without specifying a CRLreason, that the CA revoke the Certificate,
- The CA obtains evidence that the private key corresponding to the public key in the certificate is suspected of being lost or stolen (or possibly the activation data associated with the private key),
- The CM or the Subject, the legal representative of the entity to which it belongs, if any Certification Agent or DRA operator request the revocation of the certificate (especially in the case of destruction or alteration of the private key and / or its support),
- Revocation is required by this CP/CPS for a reason that is not otherwise required to be specified by this section,
- The CA ceases operations for any reason and has not made arrangements for another CA to provide revocation support for the certificate,
- The CA signing the certificates is revoked (which results in the revocation of all valid certificates signed by the corresponding private key),
- The technical content or format of the certificate presents an unacceptable risk to Application Software Suppliers or Relying Parties (e.g., the CA/Browser Forum might determine that a deprecated cryptographic/signature algorithm or key size presents an unacceptable risk and that such certificates should be revoked and replaced by CA within a given period of time),
- An error (intentional or not) was detected in the certificate request and the associated registration files,
- o For technical reasons (failure to send the certificate ...).

#### 4.9.1.2 Reasons for Revoking a CA Certificate

One or more of the following occurs can conduct of revocation the subordinate certificate within 7 days:

- The CA requests revocation in writing,
- The CA notifies the Issuing CA that the original certificate request was not authorized and does not retroactively grant authorization,
- The Issuing CA obtains evidence that the Subordinate CA's Private Key corresponding to the Public Key in the Certificate suffered a Key Compromise or no longer complies with the requirements of Sections 6.1.5 and 6.1.6,
- The Issuing CA obtains evidence that the Certificate was misused
- The Issuing CA is made aware that the Certificate was not issued in accordance with or that CA has not complied with this document or the applicable CP/CPS,
- The Issuing CA determines that any of the information appearing in the Certificate is inaccurate or misleading,
- The CA ceases operations for any reason and has not made arrangements for another CA to provide revocation support for the Certificate,



 The CA's right to issue Certificates under these Requirements expires or is revoked or terminated, unless the Issuing CA has made arrangements to continue maintaining the CRL/OCSP Repository.

## 4.9.2 Who Can Request Revocation

#### 4.9.2.1 CA Certificate

The revocation of a CA certificate can only be decided by the entity responsible of the CA, or by the judicial authorities via a court order.

The revocation of the other components of certificates is decided by the entity operating the concerned component, which must inform the CA immediately.

#### 4.9.2.2 Legal or Natural Person Certificate

Individuals or entities may request revocation of a Subject certificate are:

- The CM or the Subject;
- A legal representative of the entity to which is attached the Subject;
- If appropriate, a Certification Agent;
- The CA;
- The RA or DRA operators.

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails	
TS 119 495 DSP2		
- An authenticated NCA. See Section 3.4.2.2		

The Certificate Manager or the Subject is informed, particularly through the TCSU accepted by him/her, persons or entities that may request a revocation of the certificate for which he/she is responsible. In addition, applicants, application service providers, or third parties may submit Certificate Problem Reports informing the issuing CA of reasonable cause to revoke the certificate.

# 4.9.3 Procedure for Revocation Request

#### 4.9.3.1 CA Certificate

In case the CA decides to revoke the intermediate CA certificate (following the compromise of the private key of the CA), the latter informed by email all CMs and Subjects that their certificates are no longer valid because one of the certificates in the certificate chain is no longer valid. This information will also be relayed directly from the entities and where appropriate their Certification Agent. The contact identified on the site of ANSSI (https://www.ssi.gouv.fr) is immediately informed in case of revocation of a certificate of the certification chain. The revocation mechanism is described in the "Operational revocation request procedure". The process is detailed in the "Cryptographic key management procedure" and in the "Component certificate management procedure".



#### 4.9.3.2 Legal or Natural Person Certificate

The revocation request is made by the RA, a Certification Agent or the CA. The revocation management function is available 24h/24 7D/7 for revocations online. For a request made from the customer area, the user authenticates with his/her account and select the certificate to be revoked.

For a request by mail, the following information must be included in the certificate revocation request (form to download on the website):

- The identity of the CM or the Subject,
- The email address of the CM or the Subject,
- The reason of the revocation.

If the CM or the Subject is not the subscriber:

- The first and last name of the subscriber,
- The quality of the subscriber (legal representative, if appropriate DRA operator or Certification Agent),
- The subscriber's phone number.

If the application is sent by mail, it must be signed by the subscriber (the signature is verified by the RA with that of the certificate request files).

If the request is made online, the empowerment of the person to perform this request is checked (authentication with the user account). In this case the person making the request can be:

- The CM or the Subject,
- If appropriate, a Certification Agent,
- The CA,
- The RA or DRA operators.

#### The steps are:

- The applicant for revocation sends his/her request to the RA by mail or online,
- The RA authenticates and validates the revocation request to the requirements described in Chapter 3.4,
- The certificate serial number is registered in the CRL,
- In all cases, the CM or the Subject is notified of the revocation by email,
- The transaction is recorded in the event logs with, if necessary, sufficient information on the underlying causes that led to the revocation of the certificate.

The CA can revoke a certificate presumed to exist, if revocation of the certificate is required under this Certification Policy, even if the final certificate does not actually exist. The CA is providing CRL and OCSP services and responses in accordance with this CP/CPS for all certificates presumed to exist based on the presence of a precertificate, even if the certificate does not actually exist.

For reporting a malicious or dangerous certificate (suspected Private Key compromise, certificate misuse, or other types of fraud, compromise, inappropriate conduct, etc.) or any other matter related to certificates, use the contact form available at <a href="https://www.certigna.com/contactez-nous/">https://www.certigna.com/contactez-nous/</a> by selecting "Certificate considered malicious or dangerous".



# 4.9.4 Revocation Request Grace Period

As soon as the CM or the Subject or an authorized person has knowledge that a possible cause for revocation is effective, it must make its revocation request without delay.

# 4.9.5 Time within which CA Must Process the Revocation Request

#### 4.9.5.1 CA Certificate

The revocation of a certificate of a PKI component is performed upon detection of an event described in the possible causes of revocation for this type of certificate.

The revocation of the signing CA certificate (signing certificates / CRL / OCSP responses) is performed immediately, particularly in the case of compromise of the key. The organization and the means implemented in the event of revocation of a certificate of a component of the PKI are described in the "Cryptographic key management procedure" and in the "Component certificate management procedure".

# 4.9.5.2 Legal or Natural Person Certificate

In all cases, the maximum period for processing revocation request is 24 hours. This delay means between the receipt of the authenticated revocation request and the provision of revocation information from users.

Within 24 hours after receiving a Certificate Problem Report, the CA investigates the facts and circumstances related to a Certificate Problem Report and provide a preliminary report on its findings to both the Certificate Manager and the entity who filed the Certificate Problem Report.

After reviewing the facts and circumstances, the CA works with the Certificate Manager and any entity reporting the Certificate Problem Report or other revocation-related notice to establish whether or not the Certificate will be revoked, and if so, a date on which the CA will revoke the Certificate.

The period from receipt of the Certificate Problem Report or revocation-related notice to published revocation will not exceed the time frame set forth in Section 4.9.1. The date selected by the CA can consider the following criteria:

- The nature of the alleged problem (scope, context, severity, magnitude, risk of harm);
- The consequences of revocation (direct and collateral impacts to Subscribers and Relying Parties):
- The number of Certificate Problem Reports received about a particular Certificate or Subscriber;
- The entity making the complaint (for example, a complaint from a law enforcement official should be addressed with higher priority); and 5. Relevant legislation.

The revocation management function is available 24h/24 7D/7 for revocations online.



#### **RGS** \*\*\*

The maximum downtime of the revocation management function:

- per interruption (failure or maintenance) is 1 hour.
- per month is 4 hours.

#### **RGS** \*\*

The maximum downtime of the revocation management function:

- per interruption (failure or maintenance) is 2 hours.
- per month is 8 hours.

#### RGS \*

The maximum downtime of the revocation management function:

- per interruption (failure or maintenance) is 2 hours (workdays).
- per month is 16 hours (workdays).

# 4.9.6 Revocation Checking Requirement for Relying Parties

The user of a service or Subject certificate must check before its use, the status of certificates of all the relevant certificate chain. The method used (CRL or OCSP) is at the discretion of the user based on their availability and constraints in its implementation.

# 4.9.7 CRL Issuance Frequency

An ARL is issued at least every year. In addition, a new ARL is published systematically and immediately after the revocation of a certificate.

A CRL from an intermediate CA is issued at least every 24 hours. In addition, a new CRL is published systematically and immediately after the revocation of a certificate.

#### 4.9.8 Maximum Latency for CRLs

An ARL or a CRL is issued within a maximum of 30 minutes after its generation.

# 4.9.9 On-line Revocation/status Checking Availability

In addition to the CRL publication on the online websites, CA make available an OCSP responder conform to RFC6960 and/or RFC5019. The OCSP responder meets the requirements of integrity, availability and deadline for the publication described in this CP/CPS.

OCSP responses are signed by an OCSP Responder whose certificate is signed by the CA that issued the certificate whose revocation status is being checked. The OCSP signing Certificate contains an extension of type "id-pkix-ocsp-nocheck", as defined by RFC6960.



# 4.9.10 On-line Revocation Checking Requirements

OCSP responders operated by the CA supports the "HTTP GET" method, as described in RFC 6960 and/or RFC 5019. OCSP responders meet integrity, availability and timeless requirements described in the CP. The information provided by OCSP responder for certificates are updated every four (4) days at most, and OCSP responses are valid for seven (7) days. Revoked and expired certificates are maintained in CRLs and OCSP responders.

The information provided by OCSP responder for subordinate CA certificates are updated at least every twelve months and within 24 hours after revoking a subordinate CA certificate.

If the OCSP responder receives a request for the status of a certificate serial number that is "unused", then the responder does not respond with a "good" status.

For the status of Subordinate CA Certificates, the CA updates information provided via OCSP:

- at least every twelve months; and
- within 24 hours after revoking a Subordinate CA Certificate.

A certificate serial number within an OCSP request is one of the following options:

- "assigned" if a Certificate with that serial number has been issued by the CA, using any current or previous key associated with that CA subject; or
- "unused" if neither of the previous conditions are met.

In addition to the CRL publication on the online websites, CA make available an OCSP responder available at the following addresses:

CERTIGNA EMAIL PROT	RTIGNA EMAIL PROTECTION LEGAL PERSON CA	
OCSP	http://ocsp.certigna.com	
CERTIGNA EMAIL PROTECTION NATURAL PERSON		
OCSP	http://ocsp.certigna.com	
CERTIGNA IDENTITY PLUS CA		
OCSP	http://identityplusca.ocsp.certigna.fr	
	http://identityplusca.ocsp.dhimyotis.com	

The OCSP responder meets the integrity, availability and release time requirements described in this CPS. The OCSP responder supports the "http GET" method, as described in RFC 6960 and/or RFC 5019.

The information provided by the OCSP responder for certificates is updated every 4 days at most, and OCSP responses are valid for 7 days. Revoked and expired certificates are maintained in OCSP CRLs and responders.

#### 4.9.11 Other Forms of Revocation Advertisements Available

No stipulation.



# 4.9.12 Special Requirements Re Key Compromise

The Certificates Manager, the Subject or the Certification Agent must request the certificate revocation promptly after becoming aware of the compromise of the private key.

For CA certificates, in addition to the requirements of Section 4.9.3 above, the revocation following a compromise of the private key is being clear information distributed at least on the website of the CA and possibly relayed by other means (other institutional websites, newspapers, etc.). The implemented measures are defined in the "Cryptographic key management procedure" and in the "Component certificate management procedure".

#### **CERTIGNA IDENTITY PLUS CA**

Authentication/signature

RGS \*\*\*

In case of compromise of his/her private key or knowledge of the compromise of the private key of the CA that issued the certificate, the Subject is obligated to immediately and permanently stop the use of the Subject certificate and private key that it is associated. Remember, this commitment is made upon acceptance of the TCSU.

The following methods may be used to report to the contact information described in section 4.9.3.2, a key Compromise of a CERTIGNA Certificate:

- Submitting a CSR signed by the Private Key and verifiable with the Public Key;
- Submitting a test file/challenge response signed by the Private Key and verifiable with the Public Key;
- Providing references to vulnerability and/or security incident sources from which the Compromise is verifiable;
- Submitting the Compromised Private Key to CERTIGNA. This method is not recommended but will be considered proof of Key Compromise.

CERTIGNA MAY allow additional methods that do not appear in this section at its own discretion and will update the CP/CPS if a new method is accepted.

## 4.9.13 Circumstances for Suspension

The certificates issued by the CA cannot be suspended.

#### 4.9.14 Who can Request Suspension

Not applicable.

#### 4.9.15 Procedure for Suspension Request

Not applicable.

# 4.9.16 Limits on Suspension Period

Not applicable.



#### 4.10 Certificate Status Service

# 4.10.1 Operational characteristics

The CA provides to certificate users the information needed to verify and validate, prior to their use, the status of their certificates and all the corresponding certificate chain (up to and including Root CA), i.e. to also check the signatures of the certificates in the chain, signatures guaranteeing the origin and integrity of the CRL/LAR and the state of the certificate of Root CA. The information based on the status of certificates makes available to certificates users a free consultation mechanism CRL/ARL. These CRL/ARL are in CRL V2 format published on the publication website <a href="http://www.certigna.com">http://www.certigna.com</a> (available with the HTTP protocol).

The CRL and the OSCP responder can provide a different response as to the status of a certificate for a maximum of 30 minutes after its revocation has been validated. As a reminder, when a revocation is validated, the OCSP responder is updated immediately, while the CRL is produced and then published within a maximum of 30 minutes.

The publishing service activities are defined in the "<u>Publishing Service Management Procedure</u>". Revocation entries on a CRL or OCSP Response are not removed until after the Expiry Date of the revoked Certificate.

# 4.10.2 Service Availability

The information function on the status of certificates is available 24/7. The CA maintains a continuous 24x7 ability to respond internally to a high-priority Certificate Problem Report, and where appropriate, forward such a complaint to law enforcement authorities, and/or revoke a Certificate that is the subject of such a complaint.

#### RGS \*\*\*

The maximum downtime of the information function on the status of certificates:

- per interruption (failure or maintenance) is 2 hours.
- per month is 8 hours.

#### RGS \*\*

The maximum downtime of the information function on the status of certificates:

- per interruption (failure or maintenance) is 4 hours.
- per month is 16 hours.

#### RGS \*

The maximum downtime of the information function on the status of certificates:

- per interruption (failure or maintenance) is 4 hours (workdays).
- per month is 32 hours (workdays).

If check online of the status of a certificate, the OCSP server response time to the received request is a maximum of 10 seconds. This is the time measured at the server (request received by the server and response from the latter). The replication of services on several information systems ensures



automatic continuity of services in the event of a disaster. The CA also relies on its staff on-call during non-working hours to supervise the availability alerts for these functions.

# 4.10.3 Optional Features

No stipulation.

# 4.11 End of Subscription

In case of termination of the contractual or the statutory relationship between the CA and the entity attached to the service, the server or the Subject before the end of validity of the certificate, the certificate is revoked.

# 4.12 Key Escrow and Recovery

# 4.12.1 Key escrow and recovery policy and practices

The escrow of private keys is prohibited.

# 4.12.2 Session Key Encapsulation and Recovery Policy and Practice

Not applicable.



# 5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

REMINDER – CA conducted a risk analysis to determine the specific security objectives, to cover the business risks of the entire PKI, and technical and non-technical security measures to implement. Its CP/CPS was developed based on this analysis. This CP/CPS is established based on this risk analysis. The management of information security risks is described in the "IS Risk Management Procedure" and in the "IS Risk Management Form".

This CP/CPS also aims to comply with the current version of the « Network and Certificate System Security Requirements » from the CA/Browser Forum.

# 5.1 Physical Controls

#### 5.1.1 Site Location and Construction

The information systems used for CA functions are hosted in several production centers with the same security features. The location of the sites does not present major risks.

The risks are identified in the document "Risk Management IS".

# 5.1.2 Physical Access

A strict control of physical access to the components of PKI is performed, with access logging and video surveillance: the defined security perimeter around the systems hosting the PKI components is limited to people within a trusted role on this PKI.

Outside working hours, the implementation of physical and logical intrusion detection means strengthening the security of the PKI. In addition, any person (external service provider, etc.) entering in this physically secure area cannot be left without the supervision of an authorized person. Physical access to production centers is restricted through physical access control measures. The measures implemented are described in the "Safety Policy".

#### 5.1.3 Power and Air Conditioning

Measures concerning the supply of electricity and air conditioning are taken to meet the commitments of the CA described in this CP on ensuring the level of availability of its functions, including revocations management features and information functions on the status of certificates. The production centers are equipped with inverters and generators. The measures implemented are described in the "Safety Policy".



# 5.1.4 Water Exposures

Measures for protection against water damage are taken to address the CA commitments described in this CP/CPS on ensuring the level of availability of its functions, including revocations management functions and information functions on the status of certificates. Means for the detection of water leaks are positioned in the production centers. The measures implemented are described in the "Safety Policy".

#### 5.1.5 Fire Prevention and Protection

Measures for prevention and protection against fire are taken to address the CA commitments described in this CP/CPS on ensuring the level of availability of its functions, including revocations management functions and information functions on the status of certificates.

The computer rooms of the production centers are equipped with inert gas extinguishing systems. The measures implemented are described in the "Safety Policy".

# 5.1.6 Media Storage

The information and their supporting assets involved in the activities of the IGC are identified, inventoried and their security needs defined in terms of availability, integrity and confidentiality.

The assets are listed in the "Asset Inventory" document, and the security requirements in the "IS Risk Management Form".

Specific measures are implemented to avoid compromise or theft of information. The assets corresponding to this information are managed according to procedures conforming to these security needs. They are handled in a secure manner to protect the assets from damage, theft and unauthorized access. Management procedures protect media against obsolescence and deterioration during the period during which the CA agrees to keep the information contained therein.

The measures implemented allow to cover the risks identified through the form "IS risk management".

The "Security Policy", the "<u>Asset Management Procedure</u>" and the "<u>Materiel Management Procedure</u>" describe the measures implemented.

#### 5.1.7 Waste Disposal

The measures taken for the disposal of media are compliant with the level of confidentiality of the corresponding information.

The "<u>Security Policy</u>", the "<u>Asset Management Procedure</u>" and the "<u>Materiel Management Procedure</u>" describe the measures implemented.



## 5.1.8 Off-site Backup

Outsourced backups are implemented and organized in such a way as to ensure that the IGC functions are available as soon as possible after an incident, and in accordance with the commitments of this PC, in particular regarding the availability and protection of the confidentiality and integrity of saved information.

The "Backup Procedure", the "<u>Asset Management Procedure</u>" and the "<u>Materiel Management Procedure</u>" describe the measures implemented.

#### 5.2 Procedural Controls

#### 5.2.1 Trusted Roles

Each PKI component distinguishes at least the seven following functional trust roles:

- **Security officer**: The security officer is responsible of implementing the component's security policy. He manages the controls on the physical access to the component's system hardware. He is authorised to review the archives and is responsible of analysing the event logs to detect any incident, anomaly, attempted compromise, etc.
- **Application manager**: Within the component to which he is attached, the application manager is responsible of implementing the certification policy and the declaration of the PKI's certification practices on the level of the application for which he is responsible. His responsibility includes all the functions provided by this application and the corresponding performances.
- **System administrator**: He is responsible of the start-up, configuration and technical maintenance of the component's IT hardware. He provides the technical administration of the component's systems and networks.
- **Operator**: Within a PKI component, based on his duties, an operator runs applications for the functions implemented by the component.
- Controller: Designated by a competent authority, this person's role is to regularly perform
  verifications on the compliance of the implementation of the functions provided by the
  component relative to the certification policies, to the PKI's declarations of certification practices,
  and to the component's security policies.
- Registration Officer: Responsible for approving end entity Certificate generation and revocation.
- **Secret share holder**: It has the responsibility to ensure the confidentiality, integrity and availability of the secrets assigned to him.

The different roles are defined in the description of functions specific to any entity operating a component of the PKI on the principles of separation of duties and least privilege. These roles determine the sensitivity of the functions, depending on responsibilities and access levels, background checks and employee training and awareness.

The documents "Roles, Responsibilities and Authorities", "Personnel Management Procedure" and "Staff Monitoring" describe the measures implemented.



Measures are in place to prevent equipment, information, media and software relating to CA services are removed from the site without permission.

The "<u>Security Policy</u>", the "<u>Asset Management Procedure</u>" and the "<u>Materiel Management Procedure</u>" describe the measures implemented.

## 5.2.2 Number of Individuals Required per Task

For reasons of availability, each task must be performed by at least two people. For some sensitive tasks like operations on HSM (e.g. key ceremony), many people are required for security reasons and "dual control."

The documents "Roles, Responsibilities and Authorities", "Personnel Management Procedure" and "Staff Monitoring" describe the measures implemented.

#### 5.2.3 Identification and Authentication for Each Roles

Each role assignment to a member of the PKI staff is attributed and accepted formally. This role is clearly mentioned and described in his/her job description. CA checks the identity and permissions of any member of its staff before assigning privileges to its functions. Assigning a role to a member of staff following the PKI particularly strict procedure with signing of the minutes for the allocation of all elements necessary for the performance of this role in the PKI (keys, access codes, cryptographic keys, etc.).

The documents "Roles, Responsibilities and Authorities", "Personnel Management Procedure" and "Staff Monitoring" describe the measures implemented.

## 5.2.4 Role Requiring Separation of Duties

About trusted roles, the following rollups are prohibited within the PKI:

- Security officer and system administrator / operator,
- Controller and any other role,
- System operator and administrator.

The document "Roles, Responsibilities and Authorities", the "Personnel Management Procedure" and the "Staff Monitoring" document describe the measures implemented.

#### 5.3 Personnel Controls

#### 5.3.1 Qualifications, Experiences, and Clearance Requirements

All staff must work within the PKI components must sign the internal security charter. This charter contains a confidentiality clause which applies both in respect of third parties and users. It lists the roles of each employee within the PKI. She is co-signed by the employee and the security officer.



Matching skills of personnel involved in the PKI is checked in compliance with its duties on the components. The management personnel, the security officer, system administrators, have the expertise necessary for the performance of their respective roles and are familiar with the security procedures applied to the operation of the PKI. AC informs any employee involved in the PKI trusted roles of its responsibilities for PKI services and procedures related to system security and monitoring staff.

Professional skills are determined during recruitment and each year by Security Officers.

The documents "Roles, Responsibilities and Authorities", "Personnel Management Procedure" and "Staff Monitoring" describe the measures implemented.

## 5.3.2 Background Check Procedures

The CA ensures that all employees involved on the PKI suffered no contradiction in justice conviction with their functions. The employees provide a copy of the bulletin Number 3 before their Assignment of his/her criminal record. This check is renewed periodically (at least every 3 years). In addition, the CA ensures that the employees do not suffer from conflict of interests detrimental to the impartiality of their tasks. The CA can decide in case of refusal of the personnel to communicate this copy or in case of presence of a court judgment incompatible with the attributions of the personnel, to withdraw these attributions to them.

The documents "Roles, Responsibilities and Authorities", "Personnel Management Procedure" and "Staff Monitoring" describe the measures implemented.

## 5.3.3 Training Requirements

Initial training to software, hardware and internal operating and safety procedures is provided to employees, in line with the role that the CA assigns. An awareness on the implications of the operations whose they are responsible, basic Public Key Infrastructure knowledge, authentication and vetting policies and procedures and common threats to the information verification process is also achieved.

The CA maintains records of such training and ensures that personnel entrusted with Validation Specialist duties maintain a skill level that enables them to perform such duties satisfactorily. The CA documents that each Validation Specialist possesses the skills required by a task before allowing the Validation Specialist to perform that task. The CA requires all Validation Specialists to pass an examination provided by the CA on the information verification requirements outlined in these Requirements.

The document "Roles, Responsibilities and Authorities", the "Personnel Management Procedure" and the "Staff Monitoring" document describe the measures implemented.



## 5.3.4 Retraining Frequency and Requirements

The staff concerned receives adequate information and training prior to any changes in systems, procedures in the organization.

The document "Roles, Responsibilities and Authorities", the "Personnel Management Procedure" and the "Staff Monitoring" document describe the measures implemented.

#### 5.3.5 Job Rotation Frequency and Sequence

No stipulation.

#### 5.3.6 Sanctions for Unauthorized Actions

Any member of the CA staff acting in contradiction with established policies and procedures of this CP and internal processes and procedures of the PKI, or negligently or maliciously, will see his/her privileges revoked and will be subject to administrative sanctions or judicial proceedings.

## 5.3.7 Independent Contractor Requirements

The staff of external providers involved in local and / or components of the PKI must also meet the requirements of this Section 5.3. This is translated into appropriate clauses in contracts with those providers. If so, whether the level of intervention requires, it may be asked to the provider to sign the IT charter and / or provide background check elements.

External staff are monitored through the "<u>Third Party Management Procedure</u>". An assessment of the IS risks related to the third parties is carried out and the security needs/requirements are mapped in order to be followed through the document "<u>Third party monitoring</u>" and the associated contractual agreements.

## 5.3.8 Documentation Supplied to Personnel

Each employee has the adequate documentation of operational procedures and specific tools that implements and general policies and practices of the component within which he/she works. The CA gives him/her the impacting security policies. Operators have the operator manuals corresponding to the components on which they are involved.

The document "Roles, Responsibilities and Authorities", the "Personnel Management Procedure" and the "Staff Monitoring" document describe the measures implemented for awareness and training, and the "Document Management Procedure" defined the management of these documents.



## 5.4 Audit Logging Procedures

Relevant events involved in the management and operation of the PKI are recorded in manuscript or electronically form (by seizure or by automatic generation) and, for purposes of audit.

## 5.4.1 Types of Events Recorded

The operating systems of the PKI servers will log the following events automatically on start-up and in electronic form (non-exhaustive list):

- Create / modify / delete user accounts (access rights) and corresponding authentication data,
- Start and stop IT systems and applications,
- Events related to logging: actions taken following a failure of the logging function,
- Connecting / disconnecting users with trusted roles, and corresponding unsuccessful attempts.

Other events are also collected. It is those concerning safety and not automatically generated by computer systems:

- Physical access,
- Logical access to PKI systems,
- PKI and security system actions performed,
- Actions of maintenance and configuration changes in systems,
- Installation, update and removal of software on a Certificate System,
- System crash, hardware failures, and other anomalies,
- Relevant router and firewall activities (as described in Section 5.4.1.1),
- Cryptographic device (used for CA keys) lifecyle management events,
- Changes in personnel,
- Operation of disposal and reset of media containing confidential information (keys, activation data, personal information on Subscribers, CMs and Subjects).

Specific events to different functions of the PKI are also logged:

- Events related to signing keys and CA certificates or activation data (generation, backup and recovery, revocation, destruction, disposal of media, ...),
- Introduction of a new Certificates Profiles and retirement of existing Certificate Profiles,
- Receiving a certificate request (initial and renewal),
- Events related to controls operated for certificate request validation,
- Validation / reject a certificate request,
- Certificate generation of services, servers and Subjects,
- Certificate transmission to CM or Subjects and, if appropriate, acceptances / explicit releases by
   CMs and Subjects,
- Publish and update information related to the CA (CP / CPS, CA certificates, Terms and Conditions, etc.),
- Receipt of requests for revocation,
- Validation / reject a request for revocation,
- CRL generation and publication,
- Signing OCSP Responses,



- Disposal of media containing personal information on Subscribers, CMs and Subjects.

The logging process allows real-time recording of the operations carried out.

Each record of an event in a journal contains at least the following fields:

- The type of event,
- The date and time of the event (the exact time of the significant CA events on the environment, key management and certificate management is recorded),
- The name of the executant or the reference of the system that triggered the event,
- The result of the event (success or failure).

Depending on the type of event, there are also the following fields:

- The recipient of the operation,
- the name of the applicant of the operation or the reference of the system which request
- The names of those present (for operations requiring several persons),
- The cause of the event,
- All the information characterizing the event (eg. Serial number of the certificate issued or revoked).

The logging process allows real-time recording of transactions. In case of manual input, writing is made exceptions the same business day as the event. The events and specific data to be logged are documented by the CA.

In case of manual entry, the writing is done, except exception, the same working day as the event.

The events and specific data to be logged are documented by the CA.

The measures implemented are described in the « Logging Procedure » and the « Archive Procedure ».

The CA makes these records available to its Qualified Auditor as proof of the CA's compliance with applicable requirements.

#### 5.4.1.1 Router and firewall activities logs

Logging of router and firewall activities at a minimum includes:

- Successful and unsuccessful login attempts to routers and firewalls; and
- Logging of all administrative actions performed on routers and firewalls, including configuration changes, firmware updates, and access control modifications; and
- Logging of all changes made to firewall rules, including additions, modifications, and deletions; and
- Logging of all system events and errors, including hardware failures, software crashes, and system restarts



## 5.4.2 Frequency of Processing Log

Cf. chapter 5.4.8

## 5.4.3 Retention Period for Audit Log

The retention period for event logs on site is 1 month. Archiving of event logs is made no later than 1 month after their generation. Event logs specified in Chapter 5.5.2.3 are archived for seven years after their generation.

## 5.4.4 Protection of Audit Log

Only members dedicated CA can process these files. The systems generate event logs (except for physical access control systems) are synchronized to a reliable source of UTC time (cf. 6.8. Timestamp / dating system).

Write access to the logs is protected through the logical and physical access controls described in the "Logging Procedure", the "Logical Access Control Policy" and the "Safety Policy".

The systems generate event logs (except for physical access control systems) are synchronized to a reliable source of UTC time (cf. 6.8. Timestamp / dating system).

The "Clocks Synchronization Procedure" describes the measures implemented.

## 5.4.5 Audit Log Backup Procedures

Security measures are implemented by any entity operating a PKI component to ensure the integrity and availability of event logs for the component considered, in accordance with the requirements of this CP/CPS. A backup is performed at high frequency to ensure the availability of such information.

# 5.4.6 Audit collection System (Internal or external)

Event logs are centralized in a hub. The consolidation obtained is accessible by CERTIGNA staff. The protection of the confidentiality and integrity of event logs is ensured by logical access control and the use of file sealing tools.

## 5.4.7 Notification to Event-causing Subject

No stipulation.

#### 5.4.8 Vulnerability Assessments

An annual risk assessment is performed to:



- Identify foreseeable internal and external threats that could result in unauthorized access, disclosure, misuse, alteration, or destruction of any Certificate Data or Certificate Management Processes.
- Assess the likelihood and potential damage of these threats, taking into consideration the sensitivity of the Certificate Data and Certificate Management Processes; and
- Assess the sufficiency of the policies, procedures, information systems, technology, and other arrangements that the CA has in place to counter such threats.

The event logs are monitored once per workday to identify abnormalities related to failed attempts (access or instruction).

Event logs are analysed in their entirety to the frequency of at least once every workday and upon detection of an abnormality. A summary analysis is produced for the occasion. A reconciliation between the various logs of functions that interact with each other is made at the rate of at least 1 time per week to verify the correlation between dependent events and to reveal any abnormality. The auditor is assisted by a person with skills related to the different environments used. The measures implemented are described in the « Logging Procedure ».

#### 5.5 Records Archival

## 5.5.1 Types of Records Archived

#### CA is archiving:

- Documentation related to the security of their Certificate Systems, Certificate Management Systems, Root CA Systems, and Delegated Third Party Systems,
- Documentation related to their verification, issuance, and revocation of certificate requests and Certificates,
- The software (executable) constituent of the PKI,
- IT equipment configuration files,
- Event Logs of various components of the PKI,
- The CP/CPS,
- The digital Certificate requests,
- The records of Certification Agent registration,
- The records of DRA operator registration,
- The certificate request files with credentials,
- The certificates issued,
- The requests for revocation,
- The CRL issued,
- The OCSP responses.



#### 5.5.2 Retention Period for Archive

#### 5.5.2.1 Certificates Application Files

All accepted certificate registration files are archived seven years minimum and as long as necessary for supply needs of the proof of certification in legal proceedings in accordance with applicable law, in particular Article 6-II of the implementing decree n ° 2001-272 of 30 March 2001. In this context, it is archived for at least seven years from the generation of the certificate by the Subject. During this period of enforceability of documents, the certificate request files can be submitted by the CA in any solicitation by the competent authorities. The files, completed by the words recorded by the RA or Certification Agents, is traceable to find at an instant "t" the real identity of Subject of the certificate issued by the CA in the certificate.

## 5.5.2.2 Certificates, CRL / ARL and OCSP responses issued by the CA

Certificates of Subjects and of CA and the CRL / ARL produced (respectively by the CA and Certigna Root CA), are archived for at least seven years after their generation. OCSP responses produced are archived for at least two years after their expiration.

OCSP responses are automatically destroyed after this delay.

#### 5.5.2.3 Event logs

Event logs specified in Chapter 5.4 are archived for seven years after the associated certificates expiration. The archives are kept in multiple copies through the process of replication between production centers, which ensures the protection and availability of information. Electronic records are deleted (Periodic Process) after their retention period has passed.

The paper application files are physically destroyed. Beyond the first 11 years of operation of the CA, a manual clear archive procedure is performed on the different production centers.

#### 5.5.3 Protection of Archive

During the time of their conservation, the archives are protected in integrity. They can be played back and used by the dedicated members of the CA. Write access to these files is protected (rights management). Access to read the logs (stored on NetApp servers) is only possible from a machine identified and authorized in the internal networks.

#### 5.5.4 Archive Backup Procedures

The mirroring process (automatic or manual in case of recovery) guarantees the existence of a backup of the entire archive.

To compensate for the impossibility of replication between the production sites, daily backups are carried out in order to guarantee the existence of a copy of the recorded data.



## 5.5.5 Requirements for Time-stamping of Records

The data are dated according to Chapter 6.8.

# 5.5.6 Archive Collection System (Internal or external)

Archiving is achieved with archiving servers which ensure the availability, integrity and confidentiality of archives.

The "Backup Procedure" and the "Archive Procedure" describe the measures implemented.

## 5.5.7 Procedures to Obtain and Verify Archive Information

Archives can be recovered only by the dedicated members of the CA authorized to process these files within a maximum of two workdays. Data about contractors can be retrieved on their request.

## 5.6 Key Changeover

#### 5.6.1 CA Key

The CA cannot generate a certificate for which the end date is later than the expiration date of the certificate corresponding to the CA. For this, the validity period of the CA certificate must be higher than the certificate that it signs. Knowing the date of expiry of the certificate, renewal must be requested within a delay at least equal to the lifespan of the certificates signed by the corresponding private key.

When a new CA key pair is generated, only the new private key is used to sign certificates. The previous certificate can still be used to validate certificates issued under this key until that all certificates signed with the corresponding private key have expired.

The CERTIGNA PKI communicate on its website in case of generation of a new certificate for the CA or CERTIGNA Root CA, inviting users to download the new certificate chain.

The "<u>Cryptographic Key Management Procedure</u>" and the "<u>Key monitoring</u>" document describe the measures implemented.

## 5.6.2 Keys of the Other Components

The associated key pairs and certificates of the PKI components are renewed in the three months before their expiry or after revocation of the certificate valid.



## 5.7 Compromise and Disaster Recovery

The CA establishes procedures to maintain activities, wherever possible, and described in these procedures, the steps provided in case of corruption or loss of computing resources, software and data. These procedures are formalized as part of the implementation of Business Continuity Plans. In particular for the major risks identified, these plans address the immediate treatment in the case of strong constraints of service availability required by the CP/CPS. The operation of a supervisory monitor ensures that incidents are detected and taken into account in real time at both production sites.

## 5.7.1 Incident and Compromise Handling Procedures

In the event of a major incident, such as loss, suspicion of compromise, compromise, theft of the private key of the CA, the triggering event is the finding of this incident in the component concerned, which must inform the CA immediately.

The case of major incidents is imperative treated when detected, and the publication of the certificate revocation information, if any, will be made in the most urgent, if not immediately, by all appropriate and available means (press, website, receipt, etc.).

Similarly, if one of the algorithms, or associated parameters, used by the CA or its promoters / servers becomes insufficient for its intended use remaining, then the CA:

- Inform all CMs and Subjects and third certificate users with whom the CA has agreements or other forms of established relationships. In addition, this information must be made available to other users of certificates,
- Revoke any certificate concerned.

The "Incident Management Procedure" and the "Business Continuity Plans" describe the measures implemented.

Business continuity plan is reviewed, updated, and tested annually through one or more simulated disaster scenarios. The business continuity plan includes:

- The conditions for activating the plan,
- Emergency procedures,
- Fallback procedures,
- Resumption procedures,
- A maintenance schedule for the plan,
- Awareness and education requirements,
- The responsibilities of the individuals,
- Recovery time objective (RTO),
- Regular testing of contingency plans.
- The CA's plan to maintain or restore the CA's business operations in a timely manner following interruption to or failure of critical business processes,
- A requirement to store critical cryptographic materials (i.e., secure cryptographic device and activation materials) at an alternate location,



- What constitutes an acceptable system outage and recovery time,
- How frequently backup copies of essential business information and software are taken,
- The distance of recovery facilities to the CA's main site; and
- Procedures for securing its facility to the extent possible during the period of time following a disaster and prior to restoring a secure environment either at the original or a remote site.

# 5.7.2 Computing Resources, Software, and/or Data Are Corrupted

Each component of the PKI is integrated into the business continuity plan (BCP) of the company to meet the availability requirements of the various functions of the PKI under the CA commitments and results of the analysis risk of PKI, especially regarding the functions related to the publication and / or related to the revocation. This plan is tested at least once every two years. The "Incident Management Procedure" and the "Business Continuity Plans" describe the measures implemented.

## 5.7.3 Entity Private Key Compromise Procedures

The case of compromise of a key infrastructure or control of a component is treated in the business continuity plan of the component as a disaster (see Section 5.7.2).

In the case of compromise of a CA key, the corresponding certificate will be immediately revoked (see section 4.9).

Similarly, all valid Subject certificates issued by this CA will be revoked. In addition, the CA meets at least the following commitments:

- It shall inform the following entities of the compromise: all CMs, Subjects, Certification Agent and
  other entities with which the CA has agreements or other forms of established relationships,
  including third-party users and others CA. In addition, this information is made available to other
  third-party users,
- It shall inform especially that certificates and revocation status information issued using this CA key may no longer be valid.

Note: In the case of Certigna Root CA, the signing certificate is not revoked, it is the intermediate CA certificates that are revoked in case of compromise of the private key of the Certigna Root CA.

The "<u>Cryptographic Key Management Procedure</u>", the "<u>Incident Management Procedure</u>" and the "Business Continuity Plans" describe the measures implemented.

## 5.7.4 Business Continuity Capabilities after a Disaster

The various components of the PKI have the necessary means to ensure the continuity of their activities in accordance with the requirements of the CA Certification Policy. CA uses the redundancy of its information systems into several sites and its business continuity plans to ensure the services continuity. The measures are described in the "Business Continuity Plans".



#### 5.8 CA or RA Termination

One or more components of the PKI may have to stop working or to transfer it to another entity. The transfer of activity is defined as:

- The End of the activity of a PKI component having no effect on the validity of certificates issued prior to the transfer in question;
- The resumption of this activity organized by the CA in collaboration with the new entity.

The cessation of activity is defined as the end of the activity of a PKI component influencing the validity of certificates issued prior to the relevant termination.

# 5.8.1 Transfer of Activity or Cessation of Activity Affecting a Component of the PKI

One or more components of the PKI may have to stop working or to transfer it to another entity. To ensure a constant level of confidence during and after such events, the CA takes the following actions:

- It ensures the continuity of the archive service, especially certificates and registration records;
- It ensures the continuity of the revocation service, in accordance with the availability requirements for its functions under this CP/CPS;
- It informs CMs and Subjects if the proposed changes may affect the commitments and that, at least in the period of 1 month;
- It informs application managers listed in Chapter 1.4.1 the principles of the action plan for dealing with the cessation of business or to organize the transfer of activities;
- It carries information to the administrative authorities. In particular, contact of the ANSSI is warned (https://www.ssi.gouv.fr). The CA will inform him including any obstacles or additional delay encountered during the process of transfer or retirement.

La « <u>Procédure de gestion des incidents</u> » et les « <u>Plans de continuité d'activité</u> » décrivent en détails les dispositions mises en œuvre.

## 5.8.2 Cessation of Activity Affecting the CA

In the event of termination of total activity, before the CA stops its services, it does the following:

- It informs all the CMs, the Subjects, the other components of the PKI and third parties by email of the cessation of activity. This information will also be relayed directly to the entities and if appropriate their Certification Agent;
- It revokes all certificates it has signed and which are still valid;
- It revokes its certificate;
- It destroys the private key stored in the cryptographic module and the context of the module. Holders of secret (private key and context) are summoned and destroy their secrets. It also prohibits transmitting the key to third parties.



If the CA is bankrupt, it is the commercial court which decides on the follow-up to the company's operations. Nevertheless, if any, CA is committed to supporting the commercial court under the following conditions: before bankruptcy, there is a prior period, generated most of time by several alert procedures or by a legal redress; during this period, CA is committed to preparing for the commercial court, if appropriate, a proposal to transfer digital certificates to another authority with the same level of certification. The contact identified on the website of the ANSSI (https://www.ssi.gouv.fr) is immediately informed in case of cessation of trading of the CA. The "Incident Management Procedure", the "Business Continuity Plans", and the "Transfer and Cessation Procedure" describe the measures implemented.



## 6 TECHNICAL SECURITY CONTROLS

# 6.1 Key Pair Generation and Installation

## 6.1.1 Key Pair Generation

#### 6.1.1.1 CA Key Pair Generation

This chapter describes the key pair generation context of the CA.

The generation of CA signing key is performed in a secure environment (see Chapter 5). The CA signing keys are generated and implemented in a cryptographic module complies with the requirements of Chapter 10.

The generation of CA signing key is performed under perfectly controlled circumstances by people in trusted roles (see Section 5.2.1), as part of "key ceremony".

The ceremony took place following a predefined script:

- It takes place under the control of at least two persons with a trusted role within the PKI and in the presence of several witnesses whom at least two are externed of the CA and are impartial;
- Witnesses testify in an objective and factual manner, the order of the key ceremony in relation to previously defined script.

For CA Key Pairs that are either used as a CA Key Pair for a Root Certificate or used as a CA Key Pair for a Subordinate CA Certificate, where the Subordinate CA is not the operator of the Root CA or an Affiliate of the Root CA, the CA:

- prepare and follow a Key Generation Script,
- have a Qualified Auditor witness the CA Key Pair generation process or record a video of the entire CA Key Pair generation process, and
- have a Qualified Auditor issue a report opining that the CA followed its key ceremony during its Key and Certificate generation process and the controls used to ensure the integrity and confidentiality of the Key Pair.

The generation of CA signing key is accompanied by the generation of secret share. PKI's secrets are data to manage and manipulate, subsequently to the key ceremony, the private signing keys of the CA to later initiate new cryptographic modules with the signing key of the CA. These secrets are parts of the private key of the CA decomposed per a Shamir's threshold scheme.

After their generation, the secrets are issued to their holders designated in advance and skills to this trusted role by CA. One carrier can hold only one secret of the same CA. Secrets are placed in sealed envelopes, placed in vaults. Key ceremony scripts and the distribution of secret shares are monitored and documented. The "Cryptographic Key Management Procedure" and the "HSM Management Procedure" describe the measures implemented.



## 6.1.1.2 RA Key Pair Generation

No stipulation.

Note: The RA uses as much as possible the final certificates issued by the Cas covered by this CP/CPS to authenticate its personnel and secure its services.

#### 6.1.1.3 Legal or Natural Person Key Pair Generation

The CA SHALL reject a certificate request if the requested Public Key does not meet the requirements set forth in Sections 6.1.5 and 6.1.6 or if it has a known weak Private Key

The CM or the Subject is committed by contract, accepting the TCSU, to:

- generate the private key in a device which meets the requirements of Section 11.
- comply with requirements for the device he uses to generate and store the private key, if it is not provided by the CA.

The CA will take any necessary measures to obtain technical information about the device of the Subjects and reserves the right to reject the certificate request if it is found that this device does not meet these requirements.

The CA SHALL reject a certificate request if:

- The Key Pair does not meet the requirements set forth in Section 6.1.5 and/or Section 6.1.6;
- There is clear evidence that the specific method used to generate the Private Key was flawed;
- The CA is aware of a demonstrated or proven method that exposes the Applicant's Private Key to compromise;
- The CA has previously been made aware that the Applicant's Private Key has suffered a Key Compromise, such as through the provisions of Section 4.9.1.1;
- The CA is aware of a demonstrated or proven method to easily compute the Applicant's Private Key based on the Public Key (such as a Debian weak key, see https://wiki.debian.org/SSLkeys).

In the case where the CA generates the key pair, the generation is carried out in a device that complies with the requirements of Section 11.

## 6.1.2 Private Key Delivery to Subscriber

When the CA generates the private key on behalf of the service, server or Subject, the CA, the authentication of the CM or the Subject by the AE is carried out prior to the delivery of the key pair in encrypted format.

The private key is transmitted either in the form of a download protected by an activation data defined by the CM or the Subject (PKCS#12 file with at least 112 bits of encryption strength), or in a device conforming to Section 11 (with an activation method that is equivalent to 128 bits of encryption) and sent by secure mail to the CM or the Subject, or delivered via a face-to-face with a RA operator, a DRA operator, or a Certification Agent.



If the CA or any of its designated RAs become aware that a CM or Subject Private Key has been communicated to an unauthorized person or an organization not affiliated with the Subject of the Certificate, then the CA SHALL revoke all certificates that include the Public Key corresponding to the communicated Private Key.

## 6.1.3 Public Key Delivery to Certificate Issuer

If the key pair is not generated by the CA, the certificate request (PKCS # 10 format) containing the service, the server or the Subject's key, is sent to the CA by the CM or the Subject. This request is signed with the private key, which enables the RA to verify its integrity and ensure that the CM or the Subject has the private key associated with the public key transmitted in this request. Once these checks are complete, the RA signs the request and sends it to the CA.

## 6.1.4 CA public Key Delivery to Relying Parties

The issuance of public key of the CA, which allows all those who need to validate a certificate issued by the CA under the CP/CPS, is made by means ensuring integrity and authentication of the public key.

The public key of an intermediate CA is broadcast in a certificate signed by the Certigna Root CA. The public key of the Certigna Root CA is distributed in a self-signed certificate. These public CA keys and their control values are disseminated and retrieved by the information systems of all certificates acceptors through the Certigna website at <a href="https://www.certigna.com">https://www.certigna.com</a>. See Section 2.2.1.2.

## 6.1.5 Key Sizes

#### 6.1.5.1 Root CA Certificate

- Digest algorithm: SHA-256,

- RSA modulus size (bits): 4096

#### 6.1.5.2 Subordinate CA Certificate

Digest algorithm: SHA-256, or SHA-384

- RSA modulus size (bits): 4096

#### 6.1.5.3 Legal or Natural Person Certificate

CERTIGNA IDENTITY PLUS CA	Authentication/signature				
CERTIGNA EMAIL PROTECTION NATURAL PERSON	Authentication/signature				
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails				
CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails				

- Digest algorithm: SHA-256 or superior (SHA-256, SHA-384, SHA-512)
- RSA modulus size (bits): 2048, 3072 or 4096 (see Certificate profiles in section 7)



## 6.1.6 Public Key Parameters Generation and Quality Checking

The parameters and signature algorithms implemented in cryptographic boxes, physical media and software are documented by CA. The CA confirms that the value of the public exponent is an odd number is superior to 3 and is in the range between 2<sup>16</sup>+1 and 2<sup>256</sup>-1.

#### 6.1.6.1 CA Key

The key pair generation equipment uses parameters respecting the safety standards corresponding to the key pair.

#### 6.1.6.2 Legal or Natural Person Key

The key pair generation equipment used by the Subject uses parameters respecting the safety standards corresponding to the key pair.

## 6.1.7 Key Usage Purposes (as per X.509 v3 Key usage field)

## 6.1.7.1 CA Key

The use of the private key of the root CA and associated certificate is exclusively limited to signing the root CA certificate, intermediate CA certificates and ARLs. The use of the private key of the CA and associated certificate is exclusively limited to signing legal and natural person certificates, CRLs, and OCSP responder certificate.

#### 6.1.7.2 Legal or Natural Person Key

The use of the CM or Subject's private key and the associated certificate is exclusively limited to the usages defined at chapter 1.5.1. Otherwise, their responsibility could be engaged.

# 6.2 Private Key Protection and Cryptographic Module Engineering Controls

## 6.2.1 Cryptographic Modules Standards and Controls

#### 6.2.1.1 Cryptographic Modules

The cryptographic module used by the Root CA and CA for the generation and the implementation of their signing keys are compliant with the requirements of the Section 10. These devices are resources exclusively available for CA's servers through a dedicated VLAN. The cryptographic modules used are BULL Trustway Proteccio. The "HSM Management Procedure" describes the measures implemented. The CA implements physical and logical safeguards to prevent unauthorized certificate issuance.



#### 6.2.1.2 Device to protect Legal or Natural Person private key

The device used by the CA, the CM or the Subject to protect the private key is compliant with the requirements of the Section 11. In the case where the CA provides the device to the CM or the Subject, directly or indirectly, CA ensure that:

- The device preparation is controlled securely;
- The device is stored and provided securely;
- The deactivation and reactivation of the device is controlled securely.

# 6.2.2 Private Key (n out of m) Multi-Person Control

Control of CA signature private key is provided by trusted personnel and with a tool implementing sharing secrets (systems where n operators of m must authenticate, with n at least equal to 2). The "HSM Management Procedure" and the "Cryptographic Key Management Procedure" describe the measures implemented.

## 6.2.3 Private Key Escrow

#### 6.2.3.1 CA Key

The CA private keys are never escrowed.

#### 6.2.3.2 Legal or Natural Person Key

The escrow of private keys is prohibited.

## 6.2.4 Private Key Backup

## 6.2.4.1 CA Key

The private key of the CA is saved:

- Inside one or several cryptographic modules compliant with the requirements of the Section 10.
- Outside the cryptographic module enciphered by the module and dispatched to several persons in trusted roles.

#### 6.2.4.2 Legal or Natural Person Key

Private keys of the services, servers and Subjects are not the subject of any backup copy of the CA.

## 6.2.5 Private key archival

#### 6.2.5.1 CA Key

The private key of the CA is never archived.



#### 6.2.5.2 Legal or Natural Person Key

Private keys of services, servers or Subjects are not archived. For private keys generated on cryptographic module, it is technically impossible to make a copy of these keys outside the HSM.

#### 6.2.6 Private Key Transfer into or from a Cryptographic Module

## 6.2.6.1 CA Key

The CA private keys are generated in the cryptographic module. As described in Section 6.2.4, the CA private keys are exportable / importable from the cryptographic module in encrypted form. If the CA becomes aware that a Subordinate CA's Private Key has been communicated to an unauthorized person or an organization not affiliated with the Subordinate CA, then the CA revokes all certificates that include the Public Key corresponding to the communicated Private Key.

#### 6.2.6.2 Legal or Natural Person Key

The services, servers and Subjects private keys are generated under the responsibility of the operator of RA, DRA, Certification Agent or Subject.

## 6.2.7 Private Key Storage on Cryptographic Module

## 6.2.7.1 CA Key

The root CA private key is generated in a cryptographic module described in chapter 6.2.1 and is exported in accordance with the requirements of chapter 6.2.4 in order to be continuously taken offline. The key is reconstituted in the cryptographic module to allow the annual generation of ARLs or the creation of a new intermediate authority, then deleted from the module once the operation is complete. The "HSM Management Procedure" and the "Cryptographic Key Management Procedure" describe the measures implemented.

#### 6.2.7.2 Legal or Natural Person Key

The services, servers and Subjects private keys are generated and stored in a device compliant with the requirements from the Section 11, if applicable.

#### 6.2.8 Method of Activating Private Key

## 6.2.8.1 CA Key

Activation of CA private key in the cryptographic module is controlled via activation data (see Section 6.4) and involves two people with a trusted role within PKI. The "HSM Management Procedure" and the "Cryptographic Key Management Procedure" describe the measures implemented.



#### 6.2.8.2 Legal or Natural Person Key

Activation of key pairs is controlled by activation data (cf. chapter 6.4) which are used by the key pair hardware or software container.

## 6.2.9 Method of Deactivating Private Key

#### 6.2.9.1 CA Key

The cryptographic module resists physical attacks by erasing the CA private keys. The module can detect the following physical attacks: Opening the device, removing or forcing.

#### 6.2.9.2 Legal or Natural Person Key

The method of disabling the private key depends on the cryptographic module used by the CM or the Subject.

## 6.2.10 Method of Destroying Private Key

#### 6.2.10.1 CA Key

End of life of a CA private key, normal or anticipate (revocation), the key and the secrets of shares to reconstruct are systematically destroyed. A record of key and secret destruction is established at the end of this procedure. The measures implemented are described in the "Procedure for managing cryptographic keys".

#### 6.2.10.2 Legal or Natural Person Key

The CM or the Subject is the sole owner of the private key and is the only one who can destroy it (deletion of the key or physical destruction of the device).

## 6.2.11 Cryptographic Module Rating

#### 6.2.11.1 CA Key

The assessment level of the CA cryptographic module is specified in Section 10.

#### 6.2.11.2 Legal or Natural Person Key

The assessment level of the device used, if applicable, by the CM or the Subject, is specified in Section 10.



# 6.3 Other Aspects of Key Pair Management

## 6.3.1 Public Key Archival

The public keys of the CA and of the legal or natural persons are stored within the archival of relevant certificates.

# 6.3.2 Certificate Operational Periods and Key Pair Usage Periods

#### 6.3.2.1 CA Key Pair and Certificate

For CERTIGNA PKI, the validity period of Root CA certificate is:

- For old CA certificates: 20 years for root CAs, and 18 years for intermediate CAs;
- For new CA certificates: 15 years for root CAs, and less than 15 years for intermediate certificates

The end of validity of a CA certificate is later than the end of life of the certificates it issues.

## 6.3.2.2 Legal or Natural Person Key Pair and Certificate

Certificate	Lifetime				
CERTIGNA EMAIL PROTECTION LEGAL PERSON CA					
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU	CA				
Seal for mails	825 days maximum				
CERTIGNA EMAIL PROTECTION NATURAL PERSON	CA				
CERTIGNA EMAIL PROTECTION NATURAL PERSON	EU CA				
Seal for mails	825 days maximum				
CERTIGNA IDENTITY PLUS CA					
Authentication & signature	3 years maximum until the 14 July 2025				
	825 days maximum after the 14 July 2025				
Signature	3 years maximum until the 14 July 2025				
	825 days maximum after the 14 July 2025				



#### 6.4 Activation Data

#### 6.4.1 Activation Data Generation and Installation

# 6.4.1.1 Generation and Installation of Activation Data Corresponding to the Private Key of the CA

Generation and installation of activation data of the cryptographic module of the CA are performed during the initialization and customization phase of the module (see chapter 6.1.1).

The "HSM Management Procedure" and the "Cryptographic Key Management Procedure" describe the measures implemented.

# 6.4.1.2 Generation and installation of activation data corresponding to the private key of the subject

In the case where the key pair is generated by the CA, activation data are transmitted:

- If the device is a token, through the client space after authentication of the Subject;
- If the device is a cryptographic module with different form of activation data (cards, secrets, etc.) through different communication channels (email, mail, phone/SMS) and at different periods of time.

## EN 319 411-2 QCP-n EN 319 411-2 QCP-I

- In the case of another type of hardware or software equipment, via a communication channel different from the platform on which the certificate is proposed (mail, mail, telephone / SMS).

#### 6.4.2 Activation Data Protection

#### 6.4.2.1 Protection of Activation Data Corresponding to the CA Private Key

Activation data are directly provided to secret holders during the key ceremonies. Their storage conditions ensure their availability, integrity and confidentiality. The secrets are stored in devices with limited access, in secure envelopes to detect any unauthorized opening and traced. The "HSM Management Procedure" and the "Materiel Management Procedure" describe the measures implemented.

# 6.4.2.2 Protection of Activation Data Corresponding to Private Key of Legal or Natural Person

If the key pair is generated by the RA, it also generates the activation data that are sent as described at chapter 6.4.1. These activation data are not backed up by RA and are modified by the Subject when accepting the certificate or in case of a cryptographic module, after hardware reception.



## 6.4.3 Other Aspects of Activation Data

No stipulation.

## 6.5 Computer Security Controls

#### 6.5.1 Specific Computer Security Technical Requirements

A minimum level of safety assurance on the computer systems of persons in trusted role is ensured by:

- Strong and multi-factor identification and authentication of user for system access (E.g., physical
  access control to enter in the room + logic control by id / password or certificate to access the
  system);
- Management of user sessions (logoff after idle time, file access controlled by role and user name);
- User rights management (to implement the access control policy defined by the CA, to implement the principles of least privilege, multiple controls and separation of roles);
- Protection against computer viruses and other forms of compromise or unauthorized software and software updates using the firewall;
- Manage user accounts, including changes and the rapid removal of access rights;
- Network protection against intrusion of an unauthorized person using the firewall;
- Secure inter-sites communication (tunnel IPSec VPN);
- Audit Functions (non-repudiation and nature of the actions performed).

Monitoring devices and audit procedures of the system settings, including routing elements, are in place. The "Safety Policy", the "Logical Access Control Policy", the "Security Charter", the "Firewall Management Procedure" describe the measures implemented.

#### 6.5.2 Computer Security Rating

No stipulation.

# 6.6 Life Cycle Technical Controls

#### 6.6.1 System Development Controls

According to the risk analysis conducted, during the design of any new development project, an analysis of security is achieved and approved by the CA Security Committee. The configuration of CA systems and any changes and upgrades are documented. The development is done in a controlled and secured environment requiring a high level of authorization.

To enable its prospects or future customers to test some of their dematerialized trading applications, CA has set up a test CA issuing certificates identical in all respects to the production certificates (only



the certificate issuer is different). This test CA has its own private key. The public key certificate is self-signed. These certificates are used for testing purposes only.

The CERTIGNA solutions are tested in a development/test environment before being used in the production environment. Production and development environments are separated.

The description of the evolution context of the PKI is defined in the "Procedure for updating the technical platform". Developments of the modules related to the exploitation of the components of the PKI are carried out in accordance with the rules and instructions enacted in the "Development Guide".

When the CA uses Linting software developed by third parties (i.e. pkimetal linter), the CA monitors for updated versions of that software and plan for updates no later than three (3) months from the release of the update. The CA can perform Linting on the corpus of its unexpired, un-revoked Subscriber Certificates whenever it updates the Linting software.

#### 6.6.2 Security Management Controls

Any significant change to a system of a component of the PKI is documented and reported to the CA for validation.

## 6.6.3 Life Cycle Security Controls

No stipulation.

#### 6.7 Network Security Controls

This CP/CPS also aims to comply with the current version of the « Network and Certificate System Security Requirements » from the CA/Browser Forum.

Interconnection to public networks is protected by security gateways configured to accept only the necessary protocols to the desired operation by CA.

The CA guarantees that the components of the local network are kept in a physically secure environment and their configurations are periodically audited for compliance with the requirements specified by the CA.

The "<u>Firewall Management Procedure</u>", the "<u>Monitoring Management Procedure</u>" and the "<u>Logical Access Control Policy</u>" describe the measures implemented.

# 6.8 Time-stamping

To ensure synchronization between different dating of events, the various components of the PKI synchronize their clocks with respect to a reliable source of UTC time.

The "Clocks Synchronization Procedure" describes the measures implemented.



## 7 CERTIFICATE AND CRL PROFILES

# 7.1 Certificate profile

The CA meets the technical requirements set forth in:

- Section 6.1.5 Key Sizes, and
- Section 6.1.6 Public Key Parameters Generation and Quality Checking.

The CA generates non-sequential Certificate serial numbers greater than zero (0) containing at least 64 bits of output from a CSPRNG. The certificates and CRLs generated by the CA comply with ITU-T Recommendation X.509 v3 standard, RFC 5280 and applicable requirements from EN 319 412 ETSI specifications.

**CERTIGNA** has three root CAs:


- The historical "Certigna";
- The current "Certigna Root CA";
- The new dedicated "Certigna Email Protection Root CA";
- The new dedicated "Certigna Email Protection EU Root CA".

The intermediate CA certificates covered by this CP have been signed by the two root CAs in order to ensure the transition of certificates from the old root to the new one.

Effective July 1, 2023, the CA shall not sign SHA-1 hashes over:

- certificates with an EKU extension containing the id-kp-ocspSigning key purpose;
- intermediate certificates;
- OCSP responses;
- or CRLs.

The trusted hierarchy is composed with following certificates and authorities:





## 7.1.1 Version number(s)

Certificates are of type X.509 v3.

#### 7.1.2 Certificates extensions

See requirements for all profiles in section 7.10.

#### 7.1.2.1 Processing certificates extensions by applications

Extensions defined for X509 V3 certificates are used to associate additional information with a public key, relating to the subject or the CA.

#### 7.1.2.2 Criticality

The criticality character must be treated as follows depending on whether the extension is critical or not:

- If the extension is uncritical, then:
  - If the application does not recognise the OID, the extension is abandoned but the certificate is accepted;
  - o If the application recognizes the OID, then:
    - If the extension is compliant with what the application wants to do, the extension is processed.
    - If the extension is not compliant with what the application wants to do, the extension is abandoned but the certificate is accepted.
  - o If the extension is critical, then:
    - If the application does not recognise the OID, the certificate is rejected.
    - If the application recognizes the OID, then:
      - If the extension is compliant with what the application wants to do, the extension is processed.
      - If the extension is not compliant with what the application wants to do, the certificate is rejected.

## 7.1.2.3 Extension description

**Authority Key Identifier**: This extension identifies the public key used to verify the signature on a certificate. It differentiates the different keys used by the CA when it has multiple signing keys. The authorityKeyIdentifier field is necessarily informed. It contains a unique identifier (keyIdentifier). This CA key identifier has the same value as the subject-field KeyIdentifier of the CA certificate. The authorityCertIssuer authorityCertSerialNumber fields are blank.

**Subject Key Identifier**: This extension identifies the public key of the subject associated with the certificate. It allows to distinguish the different keys used by the subject. Its value is the value in the field keyldentifier.

KeyUsage: This extension defines the intended use of the key contained in the certificate. CA Indicates



the intended use of the key and manages the criticality as defined in section 7.2.

Extended Key Usage: This extension defines the advanced use of the key.

**CertificatePolicies**: This extension defines the certification policy following which the certificate was created. This field is processed during the validation of the certification chain. The CA includes the policyInformation field by filling the policyIdentifier field with the OID of the CP/CPS.

**CRL Distribution Points**: This extension identifies the location where the user can find the CRL indicating that the certificate has been revoked. The CA includes as many distributionPoint fields than it offers access mode to CRL. Each of these fields includes the uniformRessourceIdentifier of the CRL.

**Authority Information Access**: This extension identifies (with Method = OCSP) the location of OCSP server(s) providing information on the status of certificates, and the CA with providing a link to the its certificate.

**Basic Constraints**: This extension indicates whether the certificate is an end entity certificate or an authority certificate.

**Certificate Transparency**: This extension allows to control the registration of the certificate in the logs used for the "Certificate Transparency".

## 7.1.3 Algorithm object identifiers

#### 7.1.3.1 SubjectPublicKeyInfo

#### 7.1.3.2 RSA

The CA indicates an RSA key using the rsaEncryption (OID: 1.2.840.113549.1.1.1) algorithm identifier. The parameter is present and is an explicit NULL. The CA do not use a different algorithm, such as the id-RSASSA-PSS (OID: 1.2.840.113549.1.1.10) algorithm identifier, to indicate an RSA key. When encoded, the AlgorithmIdentifier for RSA keys is byte-for-byte identical with the following hex-encoded bytes: 300d06092a864886f70d0101010500

## 7.1.3.3 Signature AlgorithmIdentifier

#### 7134 RSA

For TLS, S/MIME and Code Signing certificates, the CA uses one of the following signature algorithms and encodings:

- RSASSA-PKCS1-v1\_5 with SHA-256: Encoding: 300d06092a864886f70d01010b0500.
- RSASSA-PKCS1-v1\_5 with SHA-384: Encoding: 300d06092a864886f70d01010c0500.

#### 7.1.4 Name forms

Attribute values are encoded according to RFC 5280.



#### 7.1.4.1 Name encoding

For every valid Certification Path (as defined by RFC 5280, Section 6):

- For each Certificate in the Certification Path, the encoded content of the Issuer Distinguished Name field of a Certificate is byte-for-byte identical with the encoded form of the Subject Distinguished Name field of the Issuing CA Certificate.
- For each CA Certificate in the Certification Path, the encoded content of the Subject Distinguished Name field of a Certificate is byte-for-byte identical among all Certificates whose Subject Distinguished Names can be compared as equal according to RFC 5280, Section 7.1, and including expired and revoked Certificates.

## 7.1.4.2 Subject information - subscriber certificates

For S/MIME certificates, the CA do not include a Mailbox Address in a Mailbox Field except as verified in accordance with Section 3.2.2. Subject attributes do not contain only metadata such as '.', '-', and ' ' (i.e., space) characters, and/or any other indication that the value is absent, incomplete, or not applicable. See requirements for all profiles in section 7.10.

#### 7.1.5 Name Constraints

No stipulation. See requirements for all profiles in section 7.10.

## 7.1.6 Certificate Policy Object Identifier

#### 7.1.6.1 Reserved Certificate Policy Identifiers

The following Certificate Policy identifiers are reserved to assert that a Certificate complies with CA\Browsers Requirements.

Certificate Type	Generation	Policy Identifier
Organization-validated	Legacy	2.23.140.1.5.2.1
Organization-validated	Multipurpose	2.23.140.1.5.2.2
Organization-validated	Strict	2.23.140.1.5.2.3
Sponsor-validated	Legacy	2.23.140.1.5.3.1
Sponsor-validated	Multipurpose	2.23.140.1.5.3.2
Sponsor-validated	Strict	2.23.140.1.5.3.3

## 7.1.7 Usage of Policy Constraints Extension

No stipulation.

## 7.1.8 Policy Qualifiers Syntax and Semantics

No stipulation.



# 7.1.9 Processing Semantics for the critical Certificates Policies Extension

No stipulation.

# 7.1.10 Profile of Root CA Certificates

## 7.1.10.1 Basic fields

Fields	Certigna Email Protection Root CA	Certigna Email Protection EU Root CA	Certigna Root CA	Certigna
Version	V3			
Serial Number	68 B4 31 84 C4 63 A9 6B C5 36 10 6B B3 C3 07 41 C1 11 98 D7	7A CE F9 38 FD FC 0F 6C 2C BF 5B 97 27 AC 2A IC 7C FA I7 7B	00 CA E9 IB 89 FI 55 03 0D A3 E6 4I 6D C4 E3 A6 EI	00 FE DC E3 01 0F C9 48 FF
Signature	SHA-256 RSA 4096	SHA-256 RSA 4096	SHA-256 RSA 4096	SHA-128 RSA 2048
SPKI	RSA 4096 bits	RSA 4096 bits	RSA 4096 bits	RSA 2048 bits
Validity	Certificate activation	and expiration dates and	l times	
Issuer DN	CN = Certigna Email Protection Root CA O = Certigna C = FR	CN = Certigna Email Protection EU Root CA O = Certigna C = FR	CN = Certigna Root CA OU = 0002 48146308100036 O = DHIMYOTIS C = FR	CN = Certigna O = DHIMYOTIS C = FR
Subject DN	CN = Certigna Email Protection Root CA O = Certigna C = FR	CN = Certigna Email Protection EU Root CA O = Certigna C = FR	CN = Certigna Root CA OU = 0002 48146308100036 O = DHIMYOTIS C = FR	CN = Certigna O = DHIMYOTIS C = FR

## 7.1.10.2 Extensions

Extensions	Crit	Certigna Email Protection Root CA	Certigna Email Protection EU Root CA	Certigna Root CA	Certigna
SKI	No	CA public key iden	tifier		
AKI	No	Root CA public key	identifier		
Certificate Policies	No				CPS=https://www.c ertigna.fr/autorites/
CRL Distribution Points	No			URL=http://crl.certigna.fr/certign arootca.crl URL=http://crl.dhimyotis.com/ce rtignarootca.crl	
Netscape Cert type	No				SSL CA SMIME CA Signature CA
Basic Const.	Yes	cA = TRUE			
Key Usage	Yes	Certificate signing		CRL signing	



# 7.1.11 Profile of Intermediate CA certificates

Au	uthority	CERTIGNA EMAIL PROTECTION	CERTIGNA EMAIL PROTECTION	IDENTITY PLUS CA		
		LEGAL PERSON CA	NATURAL PERSON CA			
Fields		Description				
Version		V3				
Serial Number		Unique serial number				
Signature		CA signing algorithm identifier / SHA-384 RSA 40	996	SHA-256 RSA 4096		
Subject Public	Key Info	RSA 4096				
Validity		15 years maximum		18 years		
	CN =	Certigna Email Protection Root CA		Certigna Root CA		
Issuer DN	OU =			0002 48146308100036		
100dCl DIV	0 =	Certigna		DHIMYOTIS		
	C =	FR		FR		
	CN =	Certigna Email Protection Legal Person CA	Certigna Email Protection Natural Person CA	Certigna Identity Plus CA		
	OI =	NTRFR-48146308100036				
Subject DN	OU =			0002 48146308100036		
	0 =	Certigna		Dhimyotis		
	C =	FR				
SKI	No	CA public key identifier				
AKI	No	Root CA Public key identifier				
Certificate		OID=2.23.140.1.5.1.3 (Mailbox-validated Strict) OI	D=2.23.140.1.5.2.3 (Organization-validated Strict)	OID=1.2.250.1.177.2.0.1.1		
Policies	No	OID=2.23.140.1.5.3.3 (Sponsor-validated Strict) OI	D=2.23.140.1.5.4.3 (Individual-validated Strict)	CPS=https://www.certigna.fr/autorites/		
rolicies		OID=1.2.250.1.177.8.0.1.1 id	-qt-cps = http://cps.certigna.com			
Authority	No	URL=http://ocsp.certigna.com		http://autorite.certigna.fr/certignarootca.der		
Info. Access	NO	calssuers= http://cert.certigna.com/CertignaEm	http://autorite.dhimyotis.com/certignarootca.der			
CRL Dist.	No	URL=http://crl.certigna.com/CertignaEmailProte	URL=http://crl.certigna.fr/certignarootca.crl			
Points	NO			URL=http://crl.dhimyotis.com/certignarootca.crl		
Basic	Yes	cA = TRUE	CA = TRUE			
Constraints	165	PathLengthConstraint = 0				
Key Usage	Yes	Certificate signature				
key usage	162	CRL signature				



Au	uthority	CERTIGNA EMAIL PROTECTION	CERTIGNA EMAIL PROTECTION			
		LEGAL PERSON EU CA	NATURAL PERSON EU CA			
Fields		Description				
Version		V3				
Serial Number		Unique serial number				
Signature		CA signing algorithm identifier / SHA-384 RSA 4096				
Subject Public	Key Info	RSA 4096				
Validity		15 years maximum				
	CN =	Certigna Email Protection EU Root CA				
Issuer DN	0 =	Certigna				
	C =	FR				
	CN =	Certigna Email Protection Legal Person EU CA	Certigna Email Protection Natural Person EU CA			
Subject DN	OI =	NTRFR-48146308100036				
oubject bit	0 =	Certigna				
	C =	FR				
SKI	No	CA public key identifier				
AKI	No	Root CA Public key identifier				
Certificate		OID=2.23.140.1.5.1.3 (Mailbox-validated Strict) OID=2.23.140.1.5.2.3 (C				
Policies	No	OID=2.23.140.1.5.3.3 (Sponsor-validated Strict) OID=2.23.140.1.5.4.3 (Ir				
		OID=1.2.250.1.177.17.0.1.1 id-qt-cps = http://cp	•			
Authority Info. Access	No	calssuers= http://cert.certigna.com/CertignaEmailProtectionEURootCA.cer				
CRL Dist. Points	No	URL=http://crl.certigna.com/CertignaEmailProtectionEURootCa.crl				
Basic	.,	cA = TRUE				
Constraints	Yes	PathLengthConstraint = 0				
I/ I I	W	Certificate signature				
Key Usage	Yes	CRL signature				



# 7.1.12 Profiles of end-entity certificates

## 7.1.12.1 Profile of Certificates issued by Certigna Email Protection Legal Person CA

#### 7.1.12.1.1 Basic Fields

CERTIGNA E	MAIL PROT	TECTION LEGAL PERSON							
Usage		Seal for mails							
OID 1.2.250.1.1	77.	8.1.1.1 8.1.1.2 8.1.1.2.1 8.1.1.2.2 8.1.1.3.1							
ETSI 319 411		LCP	<del>LCP</del>	<del>LCP</del>	<del>LCP</del>	QCP-I	<del>QCP-l</del>		
RGS v2				<del>RGS *</del>	<del>RGS *</del>				
Fields		Description							
Version		V3							
Serial Numbe	er	Unique serial number ou	tput from a CSPRNG. (Cry	ptographically secure p	seudorandom number g	enerator) / Between 128 a	nd 160 bits		
Signature		CA signing algorithm ide	entifier / SHA-256 minimu	m					
Subject Public Key Info >=3072 4096 3072 4096 >=3072					>=3072	<del>4096</del>			
Validity 825 days maximum									
	CN =	Certigna Email Protection Legal Person CA							
Issuer DN	OI =	NTRFR-48146308100036							
ISSUCI DIV	0 =	Certigna							
	C =	FR							
	SN =	A series of characters co	nsisting in part of a rand	om value for uniquenes	3				
	CN =	Name of the entity linked	to the seal service						
Subject DN	OU =	ICD + identifier of the entity that owns the service registered in accordance with the laws and regulations							
Jubject DN	OI =	Information on the proof	of identity of the entity						
	0 =	Name of the entity linked	to the seal service						
	C =	Country of the compete	nt authority to which the e	buntry of the competent authority to which the entity is officially registered					

¹The OrganizationIdentifier (OI) field is used to provide the registration number of the entity attached to the certificate. In the case where this number is issued by the NCA, this field will be composed as follows: ["PSD" as 3 characters legal person identity type reference] + [2 characters country code representing the NCA country] + [hyphen-minus "-"] + [2-8 characters NCA identifier without country code] + [hyphen-minus "-"] + [PSP identifier (authorization number as specified by the NCA. There are no restrictions on the characters used)]



## 7.1.12.1.2 Extensions

		016					
Usage		Seal for mails	al for mails				
OID 1.2.250.1.177		8.1.1.1.1	<del>8.1.1.1.2</del>	<del>8.1.1.2.1</del>	<del>8.1.1.2.2</del>	8.1.1.3.1	<del>8.1.1.3.2</del>
ETSI 319 411		LCP	<del>LCP</del>	<del>LCP</del>	<del>LCP</del>	QCP-I	<del>QCP-I</del>
RGS v2				<del>RGS *</del>	<del>RGS *</del>		
Extension	Crit	Description					
Authority Key Identifier	No	CA public key identifier					
Subject Key Identifier	No	Public key identifier of	seal service				
Subject Alt. Name	No	Nom RFC822= seal ser	Nom RFC822= seal service email address				
Key Usage	Yes	Digital signature / Non repudiation					
Extended Key Usage	No	Email Protection					
		.8.1.1.1.1	<del>.8.1.1.1.2</del>	<del>.8.1.1.2.1</del>	<del>.8.1.1.2.2</del>	.8.1.1.3.1	<del>.8.1.1.3.2</del>
Certificate Policies	No	2.23.140.1.5.2.3 (CAB FOR	RUM – Organization-valid	dated Strict)	'	'	
		CPS= http://cps.certigna.com					
CRL Distribut. Points	No	URL=http://crl.certigna	.com/CertignaEmailProt	ectionLegalPersonCA.cı	rl		
A		URL=http://ocsp.certig	na.com				
Authority Info. Access	No	calssuers= http://cert.o	certigna.com/CertignaEi	mailProtectionLegalPers	sonCA.cer		
Basic Constraints	No	cA = FALSE					
						QcCompliance	
QC Statement	No					QcEuPDS	
						QcТуре 2	



## 7.1.12.2 Profile of Certificates issued by Certigna Email Protection Legal Person EU CA

#### 7.1.12.2.1 Basic Fields

CERTIGNA EN	MAIL PRO	FECTION LEGAL PERSON EU CA				
Usage		Seal for mails				
OID 1.2.250.1.17	7	17.1.1.1	17.1.1.2.1	17.1.1.3.1		
ETSI 319 411		LCP	QCP-I	QCP-I-qscd		
RGS v2		*	**	**		
Fields		Description				
Version		V3				
Serial Numbe	r	Unique serial number output from a CSPRNG. (Crypto	graphically secure pseudorandom number ger	nerator) / Between 128 and 160 bits		
Signature		CA signing algorithm identifier / SHA-256 minimum				
Subject Public	Key Info	RSA 3072 minimum				
Validity		825 days maximum				
	CN =	Certigna Email Protection Legal Person EU CA				
Issuer DN	OI =	NTRFR-48146308100036				
issuel Div	0 =	Certigna				
	C =	FR				
	SN =	A series of characters consisting in part of a random	value for uniqueness			
	CN =	Name of the entity linked to the seal service				
OI = Information on the proof of identity of the entity						
Subject DN	OU = ICD + identifier of the entity that owns the service registered in accordance with the laws and regulations					
	O = Name of the entity linked to the seal service					
	C =	Country of the competent authority to which the enti	ty is officially registered			

¹The OrganizationIdentifier (OI) field is used to provide the registration number of the entity attached to the certificate. In the case where this number is issued by the NCA, this field will be composed as follows: ["PSD" as 3 characters legal person identity type reference] + [2 characters country code representing the NCA country] + [hyphen-minus "-"] + [2-8 characters NCA identifier without country code] + [hyphen-minus "-"] + [PSP identifier (authorization number as specified by the NCA. There are no restrictions on the characters used)]



## 7.1.12.2.2 Extensions

Usage		Seal for mails					
OID 1.2.250.1.177		17.1.1.1	17.1.1.1 17.1.1.2.1 17.1.1.3.1				
ETSI 319 411		LCP QCP-I QCP-I-qscd					
RGS v2	9S v2 * ** **			**			
Extension	Crit	Description					
Authority Key Identifier	No	CA public key identifier					
Subject Key Identifier	No	Public key identifier of seal service					
Subject Alt. Name	No	Nom RFC822= seal service email address	Nom RFC822= seal service email address				
Key Usage	Yes	Digital signature / Non repudiation					
Extended Key Usage	No	Email Protection					
		17.1.1.1	17.1.1.2.1	17.1.1.3.1			
Certificate Policies	No	2.23.140.1.5.2.3 (CAB FORUM - Organization-validated Strict)					
		CPS= http://cps.certigna.com					
CRL Distribut. Points	No	URL=http://crl.certigna.com/CertignaEmailPro	tectionLegalPersonEUCA.crl				
Authority Info Access	No	URL=http://ocsp.certigna.com					
Authority Info. Access	No	calssuers= http://cert.certigna.com/Certignal	EmailProtectionLegalPersonEUCA.cer				
Basic Constraints	No	ca = false					
QcCompliance							
QC Statement	No			QcSSCD			
QC statement	NO		QcEuPDS	1			
			QcТуре 2				



# 7.1.12.3 Profile of Certificates issued by Certigna Email Protection Natural Person CA

# 7.1.12.3.1 Basic Fields

Usage		Signature for mails			Signature for mails								
OID 1.2.250.1.1	77	.8.2.1.1.1	<del>.8.2.1.2.1</del>	.8.2.1.3.1	.8.2.1.4.1	<del>.8.2.1.5.1</del>							
ETSI 319 411		LCP	<del>LCP</del>	QCP-n	QCP-n-qscd	QCP-n-qscd							
RGS v2			<del>RGS *</del>			<del>RGS **</del>							
Fields		Description											
Version		V3											
Serial Numbe	er	Unique serial number output from a CSPRNG  (Cryptographically secure pseudorandom number generator) / Between 128 and 160 bits											
Signature		CA signing algorithm identifie	er / SHA-256 minimum										
Subject Publ	c Key Info	Info RSA 3072											
Validity		825 days maximum											
	CN =	Certigna Email Protection Na	tural Person CA										
Issuer DN	OI =	NTRFR-48146308100036											
issuel Div	0 =	Certigna											
	C =	FR											
	SN1 =	A series of characters consis	ting in part of a random valu	e for DN uniqueness									
	CN =	Firstname SURNAME ID											
	GN =	< Firstname >											
Subject DN	SN <sup>2</sup> =	< SURNAME >											
oabjoot biv	OI =	Entity identifier <sup>3</sup>											
	OU =	ICD + identifier <sup>4</sup>											
	O =	Name of the entity linked to t	he Subject										
	C =	Country to which the entity is	Country to which the entity is officially registered										

<sup>&</sup>lt;sup>1</sup> Serial Number field



<sup>&</sup>lt;sup>3</sup> OrganizationIdentifier field

<sup>&</sup>lt;sup>2</sup> Surname field

<sup>&</sup>lt;sup>4</sup> identifier of the entity that owns the service registered in accordance with the laws and regulations

# 7.1.12.3.2 Extensions

Heado		Signature for mails						
Usage								
OID 1.2.250.1.177		.8.2.1.1.1	<del>.8.2.1.2.1</del>	.8.2.1.3.1	.8.2.1.4.1	<del>.8.2.1.5.1</del>		
ETSI 319 411		LCP	<del>LCP</del>	QCP-n	QCP-n-qscd	<del>QCP-n-qscd</del>		
RGS v2			<del>RGS *</del>			<del>RGS **</del>		
Extension	Crit.	Description						
Authority Key Identifier	No	CA public key identifier	CA public key identifier					
Subject Key Identifier	No	Public key identifier of the S	ubject					
Subject Alt. Name	No	RFC822 Name=Subject em	ail address					
Key Usage	Yes	Digital signature / Non repu	ıdiation					
Extended Key Usage	No	Email Protection						
		.8.2.1.1.1	<del>.8.2.1.2.1</del>	.8.2.1.3.1	.8.2.1.4.1	<del>.8.2.1.5.1</del>		
Certificate Policies	No	2.23.140.1.5.3.3 (CAB FORUM - Sponsor-validated Strict)						
		CPS= http://cps.certigna.com						
CRL Distrib. Points	No	URL=http://crl.certigna.com	n/CertignaEmailProtectionNo	aturalPersonCA.crl				
Authority Info.		URL=http://ocsp.certigna.c	om					
Access	No	calssuers= http://cert.certi	gna.com/CertignaEmailProte	ectionNaturalPersonCA.cer				
Basic Constraints	No	cA = FALSE	-					
				QcCompliance				
OO Statement					QcSSCD			
QC Statement	No			QcEuPDS				
				QcType 1				



# 7.1.12.4 Profile of Certificates issued by Certigna Email Protection Natural Person EU CA

# 7.1.12.4.1 Basic Fields

Usage		Signature for mails							
OID 1.2.250.1.1	77	.17.2.1.1.1	.17.2.1.2.1	.17.2.1.3.1					
ETSI 319 411		LCP	QCP-n	QCP-n-qscd					
RGS v2		RGS *	RGS **	RGS **					
Fields		Description							
Version		V3							
Serial Numbe		Unique serial number output from a CSPRNG							
Serial Number	<del>2</del> 1	(Cryptographically secure pseudorandom num	nber generator) / Between 128 and 160 bits						
Signature		CA signing algorithm identifier / SHA-256 minim	num						
Subject Publi	c Key Info	Key Info RSA 3072							
Validity		825 days maximum							
	CN =	Certigna Email Protection Natural Person EU CA							
Issuer DN	OI =	NTRFR-48146308100036							
issuei Div	0 =	Certigna							
	C =	FR							
	SN1 =	A series of characters consisting in part of a rar	ndom value for DN uniqueness						
	CN =	Firstname SURNAME ID							
	GN =	< Firstname >							
Subject DN	$SN^2 =$	< SURNAME >							
Casjoot biv	OI =	Entity identifier <sup>3</sup>							
	OU =	ICD + identifier <sup>4</sup>	ICD + identifier <sup>4</sup>						
	O =	Name of the entity linked to the Subject							
	C =	Country to which the entity is officially registere	d						

<sup>&</sup>lt;sup>1</sup> Serial Number field



<sup>&</sup>lt;sup>3</sup> OrganizationIdentifier field

<sup>&</sup>lt;sup>2</sup> Surname field

<sup>&</sup>lt;sup>4</sup> identifier of the entity that owns the service registered in accordance with the laws and regulations

# 7.1.12.4.2 Extensions

Usage		Signature for mails					
OID 1.2.250.1.177		.17.2.1.1.1	.17.2.1.2.1		.17.2.1.3.1		
ETSI 319 411		LCP	QCP-n		QCP-n-qscd		
RGS v2		RGS *	RGS **		RGS **		
Extension	Crit.	Description					
Authority Key Identifier	No	CA public key identifier	CA public key identifier				
Subject Key Identifier	No	Public key identifier of the Subject					
Subject Alt. Name	No	RFC822 Name=Subject email address					
Key Usage	Yes	Digital signature / Non repudiation					
Extended Key Usage	No	Email Protection					
		.17.2.1.1.1	.17.2.1.2.1	.17.2.1.3	3.1		
Certificate Policies	No	2.23.140.1.5.3.3 (CAB FORUM – Sponsor-validated Strict)					
		CPS= http://cps.certigna.com					
CRL Distrib. Points	No	URL=http://crl.certigna.com/CertignaEmailPro	tectionNaturalPersonEUCA.crl				
Authority Info. Access	No	calssuers= http://cert.certigna.com/Certignal	EmailProtectionNaturalPersonEUCA.cer				
Basic Constraints	No	cA = FALSE					
			QcCompliance				
00.044				QcSSCD			
QC Statement	No		QcEuPDS				
			QcType 1				



# 7.1.12.5 Profile of Certificates issued by Certigna Identity Plus CA

# 7.1.12.5.1 Champs de base

CERTIGNA II	JENTTI Y PL	US CA											
OID 1.2.250.1.17	77.2	.4.1.1.1	.4.1.1.2	.4.1.7.1	.4.1.7.2	.4.1.8.1	.4.1.8.2	<del>.4.1.4.1</del>	<del>.4.1.4.2</del>	<del>.4.1.3.1</del>	<del>.4.1.3.2</del>	<del>.4.1.6.1</del>	<del>.4.1.6.2</del>
Usage Auth + Sign				Auth + Sigi	Auth + Sign Auth + Sign		า	Auth + Sign		<del>Signature</del>		<del>Signature</del>	
ETSI 319 411		QCP-n-qs	cd	QCP-n		QCP-n-qso	cd	QCP-n-qs	ed	QCP-n-qs	n-qscd QCP-n-qscd		ed
RGS v2		RGS **						RGS **		RGS ***		RGS ***	
Fields		Description											
Version		V3											
Serial Numbe	er	Unique ser	ial number o	output from (	a CSPRNG. (0	Cryptograph	ically secure	e pseudoran	dom numbe	er generator)	/ Between 1	28 and 160 b	its
Signature		CA signing	g algorithm i	dentifier / SH	A-256 minir	num							
Subject Publi Key Info	С	RSA 2048	RSA 3072	RSA 2048	RSA 3072	RSA 2048	RSA 3072	RSA 2048	RSA 3072	RSA 2048	RSA 3072	RSA 2048	RSA 3072
Validity		3 years mo	aximum <mark>unti</mark>	l 14 July 2025	/ 825 days	maximum at	fter 14 July 2	025	1				1
	CN =	Certigna Identity Plus CA											
	OU =	0002 48146308100036											
Issuer DN	OI =	NTRFR-481	46308100036	3									
	0 =	DHIMYOTIS	;										
	C =	FR											
	SN1 =	A series of	characters (	consisting in	part of a rai	ndom value 1	for uniquene	ess					
	CN =	Firstname	SURNAME ID					Firstname :	SURNAME SI	ЭN			
	GN =	<firstname< td=""><td><b>9</b>&gt;</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></firstname<>	<b>9</b> >										
Subject DN	$SN^2 =$	<surname< td=""><td>&gt;</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></surname<>	>										
Subject DN	OI =	Entity iden	tifier <sup>3</sup>					Entity ident	ifier <sup>3</sup>				
	OU =	ICD + iden	tifier <sup>4</sup>					ICD + ident	.4				
	0 =	Entity nam	ie					Entity name	е				
	C =	Country to	which the e	ntity or the S	subject is off	icially registe	red						

<sup>&</sup>lt;sup>1</sup> Serial Number field



www.certigna.com

113

<sup>&</sup>lt;sup>3</sup> OrganizationIdentifier field

<sup>&</sup>lt;sup>2</sup> Surname field

<sup>&</sup>lt;sup>4</sup> identifier of the entity that owns the service registered in accordance with the laws and regulations

# 7.1.12.5.2 Extensions

OID 1.2.250.1.177.2		4111	4110	.4.1.7.1	4170	4101	.4.1.8.2	<del>.4.1.4.1</del>	<del>.4.1.4.2</del>	<del>.4.1.3.1</del>	<del>.4.1.3.2</del>	<del>.4.1.6.1</del>	.4.1.6.2	
010 1.2.200.11.77.2		.4.1.1.1	.4.1.1.2		.4.1.7.2	.4.1.8.1					<del>.4.1.3.2</del>			
Usage Auth + Sign			n	Auth + Sig	jn	Auth + Sig		Auth + Sig	Auth + Sign		Signature		<del>Signature</del>	
ETSI 319 411		QCP-n-qs	scd	QCP-n		QCP-n-qs	scd	<del>QCP-n-qs</del>	<del>sed</del>	QCP-n-qs	<del>ed</del>	<del>QCP-n-qscd</del>		
RGS v2		RGS **						RGS **		<del>RGS ***</del>		RGS ***		
Extension	Critical		Descripti											
Authority Key Identifier	No	CA public	key identifi	er										
Subject Key Identifier	No	Public key	identifier o	f the Subjec	t									
Subject Alt. Name	No	RFC822 No	ame=Subje	ct email add	dress									
Key Usage	Yes	Digital sig	nature / No	n repudiatio	n					Non repud	liation			
Extended Key Usage	No	Client Aut	h / Email Pr	otection						Email Prote	ection			
	No	.4.1.1.1	.4.1.1.2	.4.1.7.1	.4.1.7.2	.4.1.8.1	.4.1.8.2	.4.1.4.1	<del>.4.1.4.2</del>	.4.1.3.1	<del>.4.1.3.2</del>	.4.1.6.1	<del>.4.1.6.2</del>	
O		2.23.140.1.	2.23.140.1.5.3.1 (CAB FORUM Sponsor-validated / Legacy profile) until 14 July 2025											
Certificate Policies		2.23.140.1.5.3.2 (CAB FORUM Sponsor-validated / Multipurpose profile) after 14 July 2025												
		CPS= http	s://www.ce	rtigna.fr/aut	torites/									
CRL Distribut. Points	N-	URL=http:/	//crl.certign	a.fr/identity	plusca.crl									
CRL DISTIBUT. POINTS	No	URL=http:/	//crl.dhimyd	otis.com/ide	entityplusca	.crl								
		calssuers	=http://auto	orite.certign	a.fr/ < i	identityplus	ca.der > ou	< identityplu	sca_rootco	a.der >				
Authority Info. Access	No		calssuers=http://autorite.dhimyotis.com/ < identityplusca.der > ou < identityplusca_rootca.der >											
Additionty inio. Access	110		URL=http://identityplusca.ocsp.certigna.fr											
		URL=http:/	//identityplu	usca.ocsp.dl	himyotis.co	m								
Basic Constraints	No	cA = FALSE												
		QcCompli	ance											
	N	QcSSCD						QcSSCD						
QC Statement	No			QcEuPDS										
				QcType 1										



# 7.2 Profile of CRL

# 7.2.1 Version number(s)

Certificate Revocation Lists are of type X.509 v2.

# 7.2.2 CRL and CRL entry extensions

		CERTIGNA EMAIL	CERTIGNA EMAIL	CERTIGNA EMAIL	CERTIGNA EMAIL	CERTIGNA IDENTITY PLUS				
		PROTECTION LEGAL	PROTECTION LEGAL	PROTECTION NATURAL	PROTECTION NATURAL	CA				
		PERSON CA	PERSON EU CA	PERSON CA	PERSON EU CA					
Fields		Description								
Version		V2								
Signature		CA signing algorithm identi	SHA-256 RSA 4096							
	CN =	Certigna Email Protection	Certigna Email Protection	Certigna Email Protection	Certigna Email Protection	Certigna Identity Plus CA				
		Legal Person CA	Legal Person EU CA	Natural Person CA	Natural Person EU CA					
Issuer DN	OI/OU =	NTRFR-48146308100036	NTRFR-48146308100036							
	O = Certigna					Dhimyotis				
	C =	FR								
This Update		CRL generation date								
Next Update		Next date of CRL update [7	days maximum]							
Revoked cert	tificates	List of revoked certificate serial number								
		ReasonCode <sup>1</sup>								
Extensions	Crit.	Description	Description							
AKI	No	CA public key identifier	CA public key identifier							
CRL Nb	No	CRL serial number								
Expired CertsOnCRL	No	Date from which revoked and expired certificates are maintained in the CRL.								

<sup>&</sup>lt;sup>1</sup> An extension specifying the reason for revocation may be present in accordance with the commitments of chapters 4.9.1 and 4.9.3.2.



# 7.2.3 Profile of ARL for root CAs

		Certigna Email Protection Root CA	Certigna Email Protection EU Root CA	Certigna Root CA	Certigna			
Fields		Description						
Version V2								
Signature		SHA-384 RSA 4096		SHA-256 RSA 4096				
		Certigna Email	Certigna Email	CN = Certigna Root CA	CN = Certigna			
		Protection Root CA	Protection EU Root CA	OU = 0002				
Issuer DN				48146308100036				
		O = Certigna	O = Certigna	O = Dhimyotis	O = Dhimyotis			
		C = FR	C = FR	C = FR	C = FR			
This Update		ARL generation date						
Next Update		Next date of ARL update	[1 year maximum]					
Revoked		List of revoked CA certificate serial number:						
certificates		- Serial number						
		- Revocation date						
		- Revocation reason (since 09-30-2020)						
Extensions	Crit.		Description					
AKI	No	CA public key identifier						
CRL Nb	No	ARL serial number						
Expired CertsOnCRL	No	Date from which revoked and expired certificates are maintained in the ARL.						



# 7.3 OCSP Profile

# 7.3.1 Version number(s)

No stipulation.

# 7.3.2 OCSP extension

The singleExtensions of an OCSP response MUST NOT contain the reasonCode (OID 2.5.29.21) CRL entry extension.

# 7.3.3 OCSP Profile for root CAs

		Certigna Email Protection Root CA			
Fields		Description			
Version		V3			
Signature		SHA-384 RSA 4096			
Validity		15 ans			
		CN = Certigna Email Protection Root CA			
Issuer DN		O = Certigna			
		C = FR			
		CN = Certigna Email Protection Root OCSP			
Subject DN		OI = NTRFR-48146308100036			
Subject Div		O = Certigna			
		C = FR			
Extensions	Crit.	Description			
SKI	No	CA public key identifier			
AKI	No	OSCP responder public key identifier			
Key Usage Yes		Digital signature			
Extended Key Usage No		Signature OCSP (1.3.6.1.5.5.7.3.9)			
Ocsp No Check No					
Basic Constraints	Yes	ca = False			



# 7.3.4 Profile of OCSP certificates from intermediate CA

	Authority	CERTIGNA EMAIL PROTECTION	CERTIGNA EMAIL PROTECTION	CERTIGNA IDENTITY PLUS CA				
		LEGAL PERSON CA	NATURAL PERSON CA					
Fields		Description						
Version		V3						
Serial Number		Unique serial number output from a CSPRNG. Between 128 and 160 bits						
Signature		CA signing algorithm identifier / SHA-256 min	nimum	SHA-256 RSA 4096				
Subject Public Key I	nfo	RSA 4096		RSA 2048				
Validity		3 years						
	CN =	Certigna Email Protection Legal Person CA	Certigna Email Protection Natural Person CA	Certigna Identity Plus CA				
Issuer DN	OU / OI =	OI = NTRFR-48146308100036	OI = NTRFR-48146308100036	0002 48146308100036				
issuel Div	0 =	Certigna	Certigna	Dhimyotis				
	C =	FR	FR	FR				
	CN =	Certigna Email Protection Legal Person CA OCSP	Certigna Email Protection Natural Person CA OCSP	OCSP Identity Plus CA				
	OU =			0002 48146308100036				
Subject DN	OI =	NTRFR-48146308100036						
	0 =	Certigna		Dhimyotis				
	C =	FR						
Extensions	Crit.	Description						
SKI	No	CA public key identifier						
AKI	No	OSCP responder public key identifier						
Key Usage	Yes	Digital signature	Digital signature					
Extended Key U.	No	Signature OCSP (1.3.6.1.5.5.7.3.9)						
Ocsp No Check	No							
Basic Constraints	Yes	cA = FALSE						



#### 8 COMPLIANCE AUDIT AND OTHER ASSESSMENT

Audits and assessments concern, firstly, those made for the issuance of a qualification attestation based on the Ordinance No. 2005-1516 of 8 December 2005 and eIDAS European Regulation and, secondly, those that are carried by the CA or outsourced to ensure that all its PKI is compliant with its commitments stated in its CP and practices identified in this CP/CPS.

The following chapters are for audits and evaluations of the responsibility of the CA to ensure the efficiency of its PKI.

The CA aims to comply with the current version of the "Baseline Requirements for the Issuance and Management of Publicly-Trusted S/MIME Certificates" from the CA/Browser Forum (http://www.cabforum.org).

The CA may carry out audits of its DRAs' operators as well as the staff of its PKI. It ensures among others that DRA operators respect the requirements and the practices identified in its CP/CPS. To this end, the CP/CPS is given to them.

# 8.1 Frequency or Circumstances of Assessment

A CA compliance check was performed before the deployment of certification services relative to means and rules mentioned in this CP/CPS.

This control is conducted once a year by the CA. A qualification audit is performed every year, with an audit period which does not exceed one year in duration, so that the period during which the CA issues Certificates is divided into an unbroken sequence of audit periods. The CA maintains a complete certification and qualification audit history from cradle to grave with no gaps.

Certificates that are capable of being used to issue new certificates are either Technically Constrained and audited in line with Section 8.7 only, or Unconstrained and fully audited in line with all remaining requirements from this section. A Certificate is deemed as capable of being used to issue new certificates if it contains an X.509v3 basicConstraints extension, with the cA boolean set to true and is therefore by definition a Root CA Certificate or a Subordinate CA Certificate.

# 8.2 Identity/Qualifications of Assessor

Control is assigned by the CA to a team of competent auditors in computer security and in activity of the controlled component. Annual certification and qualification audits are carried out by qualified auditors. A Qualified Auditor means a natural person, Legal Entity, or group of natural persons or Legal Entities that collectively possess the following qualifications and skills:

- Independence from the subject of the audit;
- The ability to conduct an audit that addresses the criteria specified in an Eligible Audit Scheme (see Section 8.4);



- Employs individuals who have proficiency in examining Public Key Infrastructure technology, information security tools and techniques, information technology and security auditing, and the third-party attestation function;
- For audits conducted in accordance with any one of the ETSI standards accredited in accordance with ISO 17065 applying the requirements specified in ETSI EN 319 403;
- Bound by law, government regulation, or professional code of ethics; and
- Except in the case of an Internal Government Auditing Agency, maintains Professional Liability/Errors & Omissions insurance with policy limits of at least one million US dollars in coverage.

# 8.3 Assessor's Relationship to Assessed Entity

The audit team do not belong to the component of the controlled PKI, whatever that component, and must be duly authorized to practice the targeted controls.

# 8.4 Topics Covered by Assessment

The CA annually undergoes an ETSI EN 319 411-1 audit which includes normative references to ETSI EN 319 401.

For Delegated Third Parties which are not RA or DRA, then the CA obtains an audit report, issued under the auditing standards that provides an opinion whether the Delegated Third Party's performance complies with either the Delegated Third Party's practice statement or the CA's Certificate Policy and/or Certification Practice Statement. If the opinion is that the Delegated Third Party does not comply, then the CA does not allow the Delegated Third Party to continue performing delegated functions.

# 8.5 Actions Taken as a Result of Deficiency

Following a compliance check, the audit team provide to the CA, a notice from the following: "Improvement", "remark", "minor nonconformity", "major nonconformity".

According to the results, the consequences of control are:

- In case of 'improvement', and according to the importance of the improvement, the audit team makes recommendations to CA to improve its functioning. Improvements are left to the discretion of the CA that decides whether or not to implement them.
- In case of "remark" or "minor nonconformity", the CA sends to the component a notice specifying in what timeframe nonconformities shall be lifted. Then, a control for confirmation will verify that all critical points have been resolved.
- In case of a "major nonconformity", and according to the importance of non-conformities, the audit team makes recommendations to the CA that can be business termination (temporary or permanent), revocation of certificate of component, revocation of all certificates issued since the last positive control, etc. The choice of measurement to be used is made by the CA and must respect the internal security policies.



Each session of audit permits to consult the opinion of the audit team. A control for confirmation will verify that all critical points have been resolved on time.

#### 8.6 Communication of Results

An "Audit attestation" is publicly available on the assessment body website. This attestation is published no later three (3) months after the end of the audit period. In the event of a delay grater than three (3) months, the CA provides an explanatory letter signed by the Qualified Auditor.

The Audit attestation contain at least the following clearly-labelled information:

- name of the organization being audited;
- name and address of the organization performing the audit;
- the SHA-256 fingerprint of all Roots and Subordinate CA Certificates, including Cross Certificates, that were in-scope of the audit;
- audit criteria, with version number(s), that were used to audit each of the certificates (and associated keys);
- a list of the CA policy documents, with version numbers, referenced during the audit;
- whether the audit assessed a period of time or a point in time;
- the start date and end date of the Audit Period, for those that cover a period of time;
- the point in time date, for those that are for a point in time;
- the date the report was issued, which will necessarily be after the end date or point in time date; and
- (for audits conducted in accordance with any of the ETSI standards) a statement to indicate if
  the audit was a full audit or a surveillance audit, and which portions of the criteria were applied
  and evaluated;
- statement to indicate that the auditor referenced the applicable CA/Browser Forum criteria, such as this document, and the version used.

#### 8.7 Self-Audits

Compliance checks aim to verify compliance with the commitments and practices defined in the CA's CP/CPS, as well as the resulting elements (operational procedures, resources implemented, etc.).

During the period during which the CA issues certificates, the CA monitors adherence to the requirements of this CP/CPS and strictly its service quality by performing self-audits on at least a quarterly basis against a randomly selected sample of the greater of one certificate or at least three percent of the Certificates issued by it during the period commencing immediately after the previous self-audit sample was taken.

Effective 2025-03-15, the CA can use a linting process to verify the technical accuracy of certificates within a selected sample.



Except for Delegated Third Parties that undergo an annual audit that meets the criteria specified in Section 8.4, the CA strictly control the service quality of Certificates issued or containing information verified by a Delegated Third Party by having a Validation Specialist employed by the CA perform ongoing quarterly audits against a randomly selected sample of at least the greater of one certificate or three percent of the Certificates verified by the Delegated Third Party in the period beginning immediately after the last sample was taken.

The CA reviews the practices and procedures of each delegated third party to ensure that the delegated third party is in compliance with the requirements of this CP/CPS. The CA internally audit each Delegated Third Party's compliance on an annual basis.

During the period in which a Technically Constrained Subordinate CA issues Certificates, the CA which signed the Subordinate CA monitors adherence to the CA's CP/CPS and the Subordinate CA's CP/CPS. On at least a quarterly basis, against a randomly selected sample of the greater of one certificate or at least three percent of the Certificates issued by the Subordinate CA, during the period commencing immediately after the previous audit sample was taken, the CA shall ensure all applicable CP are met.

The results of the compliance audits by the audit team are made available to the organization in charge of the qualification of the CA.



# 9 OTHER BUSINESS AND LEGAL MATTERS

#### 9.1 Fees

#### 9.1.1 Certificate Issuance or Renewal Fees

The issue of certificates to Subjects is charged according to the rates on the website or on the order form.

#### 9.1.2 Certificate Access Fees

No stipulation.

#### 9.1.3 Revocation or Status Information Access Fees

The access to certificate status information and revocation is free.

#### 9.1.4 Fees for Other Services

Other costs may be charged. In this case, charges will be brought to the attention of those to whom they apply and are available from CA.

#### 9.1.5 Refund Policy

The certificate order cannot be cancelled once the certificate request has been made. Then, Then, each certificate issued cannot be the subject of a request for reimbursement due to implementation difficulties related in particular to the technical operating environment of the certificate (e.g. non-compliance of software or hardware storing and using the certificate with the standards and norms in force). However, in the event that the certificate does not correspond to the certificate request, following an error exclusively attributable to the CA, the CA undertakes to provide a certificate compliant, or if it is unable to do so, to proceed with the reimbursement amounts already paid under the present CP/CPS and the TCSU associated.

# 9.2 Financial Responsibility

#### 9.2.1 Insurance Coverage

The CA holds an insurance policy in the field of professional civil liability, guaranteeing direct material or immaterial consequential damages caused in the exercise of his professional activity



#### 9.2.2 Other Assets

No stipulation.

# 9.2.3 Insurance or Warranty Coverage for End-Entities

Cf. chapter 9.9.

# 9.3 Confidentiality of Business Information

#### 9.3.1 Scope of Confidential Information

The information considered confidential are:

- The non-public part of the CP/CPS of the CA;
- The private keys of the CA, of components and of services, servers and subjects private key;
- Activation Data associated with CA private key and Subject private Key;
- All the PKI secrets;
- Event logs of components of the PKI;
- The subject registration records;
- The causes of revocation.

#### 9.3.2 Information not within the Scope of Confidential Information

No stipulation.

# 9.3.3 Responsibility to Protect Confidential Information

Generally, confidential information is accessible only to persons concerned by such information or who have the obligation to preserve and / or treat such information.

Once confidential information is subject to a special regime governed by a legislative and regulatory text, processing, access, modification of this information is made in accordance with the applicable legislation.

The CA implements security procedures to ensure confidentiality of the information identified in chapter 9.3.1, about the final erasure or destruction of media used for their storage. In addition, when data is exchanged, the CA guarantees their integrity.

The CA is particularly obliged to respect the laws and regulations in force on the French territory. It may need to provide the registration records of Subjects to third parties in connection with legal proceedings. It also provides access to this information at Subjects, certification agents and possibly DRA's operators in connection with the Subjects.



# 9.4 Privacy of Personal Information

# 9.4.1 Privacy Plan

By accepting these GCSU the Subscriber, the Subject or the CM acknowledges having read the CERTIGNA Personal Data Use Policy available on the Website <a href="https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/">https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/</a>.

The data provided by the Subscriber, the Subject or the CM, when registering on the Website <a href="https://www.certigna.com">https://www.certigna.com</a>, when ordering and when request for certificate are Personal Data, the collection and processing of which are governed by the Aforementioned Personal Data Policy.

Electronic certificate application files containing personal data are archived for at least seven years after certificate generation and as long as necessary for the purposes of providing proof of certification in legal proceedings, in accordance with applicable law. The personal identity information can be used as authentication data in the event of a request for revocation or information.

Application logs related to the life cycle of certificates and including personal data are archived at least seven years after their generation and as long as necessary for the purposes of providing proof of certification in legal procedures, in accordance with applicable law.

In addition, CERTIGNA retains the personal data for a period of three years from the end of the commercial relationship with the customer and 3 years from the last contact with the prospect. The delay starts from the last connection to the customer account or the last sending of an email to customer service, or from a click on a hypertext link of an email sent by CERTIGNA, a positive response to an email requesting if the client wishes to continue to receive commercial prospecting at the end of the three-year period.

In order to monitor the quality of our services, calls made to our customer service are likely to be registered and kept for a period of 30 days.

In accordance with the law n ° 78-17 of January 6, 1978 relating to data, files and freedoms, modified and the European regulation "2016/679 / EU of April 27, 2016" relating to the protection of natural persons to the processing of personal data and the free movement of such data, you have the right to access, oppose, rectify, delete and portability of your personal data. You can exercise your right by sending an email to: privacy@certigna.com, or by mail to the following address:

CERTIGNA, Service du DPO,

20 Allée de Râperie, 59 650 Villeneuve d'Ascq, France

Your request must indicate your surname and first name, e-mail or postal address, be signed and accompanied by a valid proof of identity.



#### 9.4.2 Information Treated as Private

The information considered as personal are:

- The causes of revocation of certificates;
- The registration files of RC, of DRA's operators and of certification agents.

#### 9.4.3 Information not Deemed Private

No stipulation.

#### 9.4.4 Responsibility to Protect Private Information

Cf. legislation and regulations on French territory.

#### 9.4.5 Notice and Consent to Use Private Information

Accordance with the laws and regulations on French territory, personal information submitted by Subject to CA must not be disclosed or transferred to third parties except in the following circumstances: prior consent of the Subject, court order or other legal authorization.

#### 9.4.6 Disclosure pursuant to Judicial or Administrative Process

The disclosure of confidential information is only made to the authorities empowered officially and exclusively on their specific request in accordance with French law.

#### 9.4.7 Other Information Disclosure Circumstances

No stipulation.

# 9.5 Intellectual Property Rights

The brand "CERTIGNA" is protected by the Code of Industrial Property. The use of this trademark by the entity is allowed only in the framework of the subscription contract.

# 9.6 Representations and Warranties

Obligations common to the PKI components are:

- To protect and ensure the integrity and confidentiality of their secret keys and / or private;
- Only use their cryptographic keys (public, private and / or secret) for the purposes specified when
  issued and with the equipment as specified in the conditions set by the CA's CP/CPS and
  documents arising therefrom;



- Respect and implement the part of the CP/CPS incumbent upon them (this part shall be communicated to the corresponding component);
- Submit to compliance checks by the audit team mandated by the CA (See Chapter 8) and the qualifying body;
- Respect the agreements or contracts between them or with the entity;
- To document their internal operating procedures;
- Implement the means (human and technical) necessary to achieve the benefits to which they are committed under conditions that ensure quality and safety.

# 9.6.1 CA Representations and Warranties

#### The CA will:

- can demonstrate to certificate users; it has issued a certificate to a service, a server or a Subject and the corresponding CM or Subject accepted the certificate in accordance with the requirements of Section 4.4;
- Ensure and maintain the consistency of its CPS with its CP/CPS;
- Take all reasonable steps to ensure that Subjects are aware of their rights and obligations regarding the use and management of keys, certificates or equipment and software used for PKI. The relationship between CM or Subject and the CA is formalized in a contractual relationship / regulation specifying the rights and obligations of the parties including the guarantees provided by the CA.
- At the time of issuance, implement and follow the requirements describes at sections 3.2 and 3.3 of this CP for verifying that the organization attached to the service, the server or the Subject authorized the issuance of the Certificate and that the Applicant Representative is authorized to request the Certificate on behalf of the Organization attached to the server.
- At the time of issuance, implement and follow the requirements describes at sections 3.2 and 3.3 of this CP/CPS for verifying the accuracy of all of the information contained in the Certificate.
- At the time of issuance, implement and follow the requirements describes at sections 3.2 and 3.3 of this CP/CPS for verifying the identity of the organization, the legal representative and the designated Certificate Manager or the Subject.
- If the CA and Subscriber are not Affiliated, the Subscriber and CA are parties to a legally valid and enforceable Subscriber Agreement that satisfies these Requirements,
- If the CA and Subscriber are the same entity or are Affiliated, the Applicant Representative acknowledged the Terms of Use;
- Maintain a 24 x 7 publicly accessible Repository with current information regarding the status (valid or revoked) of all unexpired Certificates;
- Revoke the Certificate for any of the reasons specified at section 4.9 of this CP/CPS.



CA assumes any harmful consequences resulting from non-compliance of its CP/CPS by itself or one of its components. CA planned to meet its responsibilities in its operations and / or activities and have the financial stability and resources required to operate in accordance with this policy. In addition, the CA recognizes its liability in case of fault or negligence of itself or one of its components, regardless of the nature and gravity, which would result in reading, alteration or misuse of personal data of Subjects for fraudulent purposes, these data are contained in transit or in the certificate management applications of the CA.

Furthermore, the CA recognizes having to bear a general duty of supervision for the safety and integrity of certificates issued by itself or one of its components. She is responsible for maintaining the security level of technical infrastructure on which it relies to provide its services. Any changes affecting the level of security provided shall be approved by the high-level bodies of the CA.

The Root CA is responsible for the performance and warranties of the Subordinate CA, for the Subordinate CA's compliance with these Requirements, and for all liabilities and indemnification obligations of the Subordinate CA under these Requirements, as if the Root CA were the Subordinate CA issuing the Certificates.

# 9.6.2 RA Representations and Warranties

The registration authority is committed to verify and validate the certificate requests and certificate revocation.

#### 9.6.3 Subscriber Representations and Warranties

#### The Subject or the CM has the following obligations:

- Make its certificate request by following all procedure steps provided on the Website https://www.certigna.fr;
- Respect the Terms and Conditions of Sale and Use (TCSU) of the requested certificate and use the certificate solely in compliance with applicable laws and solely in accordance with the TCSU;
- Know and accept that the CA is entitled to revoke the certificate immediately if the CM, the Subject or the Subscriber violate the TCSU or if revocation is required by the CA's CP/CPS or applicable requirements;
- Provide accurate, complete and up-to-date information during the certificate request or its renewal;
- Send to RA, if applicable to the DRA or to a Certification Agent of the entity, by hand or by post, the registration form generated at the time of the certificate request online on the Website: or on the DRA's website where appropriate, the payment, as well as the evidence documents.
- If necessary, generate and use the key pair with a RSA modulus size of 2048 bits minimum and in compliance with ESTI 119 312 specifications;
- Generate and use the key pair associated with the certificate in a device or cryptographic device meeting the requirements of Chapter II of the Associated CP/CPS.
  Evidence that the device compliance could be required by the CA durung the certificate request (in particular for a seal certificate. These evidences to provide will be at a minimum, the device's purchase invoice and the screen shots / prints of the hardware and software features of the device and the associated serial number. The CA reserves the right to refuse the certificate request if it is found that this device does not meet these requirements.



- In the case where the CA would be informed or would identified the loss of the compliance of the device, the CA will ask the Subject or the CM for proof that the key pair is stored in a device that meets the requirements of Chapter II of the CP associated to the certificate.
  - The Subject or the CM undertakes to provide these evidences (E.g. Invoice of purchase of a new device certified QSCD, Minutes of ceremony of the keys in case of key migration, Minutes of update of the device for the maintenance of the certification, etc.) within a deadline fifteen (15) days following the request. In the event that no evidence is provided or that the latter do not make it possible to determine if the storage conditions of the key pair, and transfer in another device if any, meet the requirements of the Certification Policy, the CA gives itself the right to revoke the certificate.
- Inform the RA in case of non-receipt of an e-mail confirming the certificate request or revocation request.
- Following receipt of an e-mail from the RA indicating the non-conformity of the certificate request or that the request is incomplete, make the modifications within seven (7) calendar days after receipt of this e-mail.
- Download the generated certificate, available on its customer area where appropriate, within thirty (30) days of the validation of the certificate request which is notified by e-mail to the CM. Beyond this period, the certificate is automatically revoked by the RA;
- Accept explicitly the certificate from its CERTIGNA customer area or form the DRA"s website where appropriate. This acceptation can also be done by sending a paper form signed by the Subject or the CM on the express request of the RA. In the event of explicit non-acceptance, the certificate is automatically revoked by the RA;
- Protect the private key associated with the certificate for which he is responsible by means appropriate to its environment and in compliance with the requirements from chapter 11;
- Protect its activation data and, if necessary, implement it;
- Protect access to the certificate database of the server for server and / or client authentication certificate:
- Respect the conditions of use of the certificate and of the associated private key mentioned in chapter 4.5 of this document;
- Inform the CA of any changes to the information contained in the certificate;
- Immediately make a certificate revocation request for which it is responsible to the RA, the DRA to which the certificate request has been made or, where appropriate, the Certification Agent of the entity, in the event of loss, theft, compromise or suspected compromise of the corresponding private key, or when one of the causes of revocation of Chapter 4.9.11 is encountered;
- Take all appropriate measures to ensure the security of the device(s) on which the certificate is installed. The Subject or the CM is solely responsible for the installation of the certificate;
- Install web authentication certificate only on servers that are accessible at the subjectAltName(s) listed in the Certificate;
- Respond to the CA's instructions concerning Key Compromise or Certificate misuse within 24 hours;
- Immediately and permanently discontinue the use of a certificate and its private key after the expiry or revocation of this certificate, and delete the associated key pair;
- no longer use a certificate if it has been revoked or if the CA that issued it has been compromised;
- Inform RA without delay of its departure from the entity or change of responsibilities and the need to register a new Subject or CM.
- Check the suitability of the certificate and its characteristics;
- Ensure that the hardware and / or software prerequisites recommended by the CA are met in view of the installation and use of the certificate;
- Have all the skills and means necessary to use the certificates;
- Implement measures to prevent any unauthorized person from physically accessing the device storing the keys and the certificate;



- Immediately notify the person in charge of the security of the information systems of his entity (example: CISO) in case of loss or theft of the device storing the keys and the certificate; and
- For applications deemed to be the most critical at the business level, implement measures to detect potentially fraudulent transactions (inconsistency of signed business data, etc.) and to provide, if necessary, an alternative procedure.
- For a server and / or client authentication certificate, and in the case where, for one or more domain names to be included in the certificate, the "DNS CAA" option is enabled, the RC must update the associated DNS records to include the CA, prior to the request for a certificate.

The relationship between the CM or the Subject and the CA or its components is formalized by a commitment from the CM or the Subject to certify the accuracy of the information and documents provided. This information also applies to DRA operators and Certification Agents.

#### The subscriber has the duty to:

- Apply for a certificate by following all the steps of the procedure appearing on the Website https://www.certigna.fr;
- Respect the Terms and Conditions of Sale and Use (TCSU) of the requested certificate and use the certificate solely in compliance with applicable laws and solely in accordance with the TCSU;
- Know and accept that the CA is entitled to revoke the certificate immediately if the CM, the Subject or the Subscriber violate the TCSU or if revocation is required by the CA's CP/CPS or applicable requirements;
- Communicate exact, complete and up-to-date information for the creation of his customer account, the request for certificate or its renewal;
- Confirm that the information to be placed in the certificate is correct;
- Send to the RA, if applicable to the DRA, or to a Certification Agent of the legal entity attached to the certificate, by hand or by post (at its expense), the registration form generated during the request for certificate online on the Website or on the DRA Website where applicable, payment, as well as supporting documents.
- Comply with the conditions of use of the certificate and the associated private key set out in chapter
   4.5 hereof and prohibit any unauthorized use of the certificate and the associated private key of the
   Subject, the seal service or the server;
- If necessary, generate and use the key pair with a 2048-bit RSA modulus minimum and in compliance with ESTI 119 312 specifications;
- If necessary, generate and use the key pair associated with the certificate in a cryptographic device which complies with the security requirements of chapter 11;
- Supporting documents attesting to the conformity of the crypographic device may be requested by the CA when requesting a certificate (in the case of a seal certificate). These supporting documents will be at a minimum the purchase invoice of the device and photos / screenshots of the hardware and software characteristics of the device and the associated serial number. The CA reserves the right to refuse the certificate request in the absence of supporting documents or if it has been proven that this device does not meet these requirements.
- Keep the Subject's private key under his sole control;
- Maintain the private key of the seal or server service under the control of the associated legal person;
- Immediately inform the CA of any loss, theft or compromise of the Subject's private key, seal or server service;
- Immediately inform the CA if control of the private key of the subject, service or server has been lost due to the compromise of activation data (for example, the PIN code) or other reasons;
- Immediately inform the CA of any modification concerning the information contained in the certificate;



- Inform the RA in the event of non-receipt of an email confirming that the request for certificate or revocation has been taken into account;
- Following receipt of an email from the RA indicating the non-compliance of the certificate application or that the file is incomplete, make the changes within seven (7) calendar days after receipt of said email;
- Make sure that the certificate of the Subject, the seal service or the server is no longer used following the expiration or revocation of this certificate (except for encipherment keys);
- check the suitability of the certificate and its characteristics to its needs;
- Respond to the CA's instructions concerning Key Compromise or Certificate misuse within 24 hours.

# 9.6.4 Relying Party Representations and Warranties

Third party users must:

- Check and maintain the use for which a certificate was issued;
- For each certificate of the certification chain, from the end-entities certificate to the Certigna Root
   CA, verify the digital signature of the issuing CA on the certificate and check the validity of the certificate (validity date, revocation status);
- Check and respect the obligations of certificate users expressed in this CP/CPS.

#### 9.6.5 Representations and Warranties of Other Participants

No stipulation.

#### 9.6.6 Termination

In the event of a breach by the CA or the Subject to one of its obligations hereunder, the other party shall be authorized thirty (30) days after formal notice sent by registered letter with acknowledgment of receipt, had no effect, to terminate these by operation of law by registered letter with acknowledgment of receipt without prejudice to any damages and interests to which it could claim due to the deficiencies invoked.

#### 9.7 Disclaimers of Warranties

Any certificate ordered must be accepted by the CM or the Subject on the customer space created from the CA website or from one of its DRA. Before generating the certificate, the CM or the Subject must verify that the information stated in his certificate request is accurate. Failing this, the CM or the Subject must contact a member of the staff of the CA either by telephone at 0 806 115 115 (free service cost of a local call), or by email at the following address: contact@certigna.fr. Telephone support is available from Monday to Friday, except holidays, from 9 AM to 6 PM without interruption. The CM or the Subject is aware that in case of error during the order in the nature of the certificate, no modification can be made by the CA and the CM or the Subject will have to make a new certificate request. If a payment had already been made, the CA would not be required to pay any refund.



Once the certificate request validated, the certificate is generated. The Subject is then brought to confirm the accuracy of said information, which means acceptance of the certificate otherwise, the CM or the Subject will have to make a new certificate request and the certificate generated will not give rise to any refund.

Once the certificate accepted, the certificate is available to the CM or the Subject either on his customer area or on a cryptographic device. the installation of the certificate is done under the sole responsibility of the CM or the Subject. In case of any difficulty during this last phase, the CM or the Subject can contact the CA at the telephone number and the email address indicated above or via contact details available on the DRA website. The CA does not guarantee the operation of the certificate in the case of use outside the uses provided for in chapter 1.5 hereof.

The warranty is valid for the worldwide outside the USA and Canada.

# 9.8 Limitations of Liability

The CA is subject to a general obligation of means. The CA cannot be held liable for the CM, the Subject, or the Subscriber for direct damage that may be attributed to it for the services entrusted to it under these TCSU.

The CA's responsibility cannot be sought for any indirect loss, such as, in particular, loss of turnover, loss of profit, loss of orders, loss of data, loss of opportunity, disturbance to the image or any other special damage or events beyond its control or any fact not attributable to it.

The CA is only responsible for the tasks specifically assigned to it under this CP/CPS.

The CA cannot be held responsible in any way for the use made by the CM or the Subject of the certificates, nor the contents of the documents and the data which are given to it by the CM, the Subject or the applicant.

In any case, the responsibility of the CA cannot be sought in case of:

- Fault, negligence, omission or default of the CA, which would constitute the exclusive cause of the occurrence of the damage,
- Malfunction or unavailability of tangible or intangible property in the case where it has been provided by the Subject,
- Delay in providing the data to be processed due to the Subject;
- Loss of the qualification of a third-party provider that is beyond the control of CERTIGNA (ex: the supplier of cryptographic support).

By express agreement between the CA and the Subject, the liability of the CA is limited, by certificate request, all damages, to the sum of two (2) times the amount paid under the certificate request.

#### 9.9 Indemnities

CERTIGNA signed a contract of "liability insurance".



The CA understands and acknowledges that the Application Software Suppliers who have a Root Certificate distribution agreement in place with the Root CA do not assume any obligation or potential liability of the CA under these Requirements or that otherwise might exist because of the issuance or maintenance of Certificates or reliance thereon by Relying Parties or others.

The CA defends, indemnifies, and holds harmless each Application Software Supplier for any and all claims, damages, and losses suffered by such Application Software Supplier related to a Certificate issued by the CA, regardless of the cause of action or legal theory involved. This does not apply, however, to any claim, damages, or loss suffered by such Application Software Supplier related to a Certificate issued by the CA where such claim, damage, or loss was directly caused by such Application Software Supplier's software displaying as not trustworthy a Certificate that is still valid, or displaying as trustworthy a Certificate that has expired, or a Certificate that has been revoked (but only in cases where the revocation status is currently available from the CA online, and the application software either failed to check such status or ignored an indication of revoked status).

#### 9.9.1 Indemnification by CM or Subject

No stipulation.

#### 9.9.2 Indemnification by Relying Parties

No stipulation.

#### 9.10 Term and Termination

#### 9.10.1 Term

CA's CP remain in effect at least until the end of life of the last certificate issued under this CP.

#### 9.10.2 Termination

The publication of a new version of the documents mentioned at chapter 1.1 may result, depending on the changes made, the need for the CA to evolve its corresponding CP. In this case, such compliance will not impose the early renewal of licenses already issued, except in exceptional cases linked to security.

Finally, the validity of the CP/CPS can happen prematurely in case of cessation of trading of the CA (see section 5.8).

#### 9.10.3 Effect of termination and Survival

The end of validity of the CP/CPS also terminates all clauses within it.



# 9.11 Individual Notices and Communications with Participants

In case of change of any kind involved in the composition of the PKI, the CA will:

- Validate later than one month before the start of the operation, this change through technical expertise to assess the impacts on the quality and safety functions of the CA and its various components;
- Inform, within one month after the end of the operation, the evaluation body.

#### 9.12 Amendments

#### 9.12.1 Procedure for Amendment

The CA conducts any change in the specifications stipulated in the CP/CPS and / or components of the CA that appears necessary to improve the quality of certification services and the security of processes, remaining however meets the requirements of RGS and additional documents to the latter. A review and an update of the CP/CPS are annually carried out and when needed.

The CA also conducts any changes to the specifications stipulated in the CP/CPS and / or components of the CA that is made necessary by legislation, regulations or by the results of checks.

#### 9.12.2 Notification Mechanism and Period

The CA communicates via its website <a href="https://www.certigna.com">https://www.certigna.com</a> the evolution of the CP/CPS based on its amendments.

### 9.12.3 Circumstances under which OID Must Be Changed

The OID of the CA's CP/CPS being registered in the certificates it issues, evolution in this CP/CPS has a major impact on the certificates already issued (e.g., increase in registration requirements of subjects, which cannot be applied to certificates already issued) must result in a change of the OID, so that users can clearly distinguish which certificates correspond to which requirements.

When the change of the CP/CPS is typographical or it does not impact the quality and safety of the functions of the CA and the RA, the OID of the CP/CPS are not changed.

# 9.13 Dispute Resolution Provisions

The validity of this CP/CPS and any other question or dispute relating to its interpretation, execution or termination will be governed by French law.

The CA and the CM or the Subject commit themselves to devote their best efforts to the amicable resolution of all the questions or the litigation which could divide them, before the seizure of the jurisdiction hereinafter designated.



The CA and the CM or the Subject agree, in the event that an amicable agreement is impossible to stop, that the courts of Lille will have exclusive jurisdiction to hear any dispute resulting from the validity, interpretation, execution or termination hereof, and more generally from any dispute arising herein that could divide them, notwithstanding pluralities of defendants or warranty claim.

To bring a complaint to CERTIGNA's attention, please use the contact form available at the following address https://www.certigna.com/contactez-nous/ and select the "Réclamation" reason.

You can also make a complaint to our customer service department using the following contact details:

- Contact e-mail: contact@certigna.fr;
- Telephone: 0 806 115 115 (Free service) available Monday to Friday from 09:00 to 18:00;
- Chat on the https://www.certigna.com website, available Monday to Friday from 9am to 18:00;
- Mail addressed to

# CERTIGNA 20 allée de la Râperie Zone de la plaine 59650 Villeneuve d'Ascq, France

Information on the processing of your personal data is available in the Policy on the use of personal data, which can be accessed at the following address: <a href="https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/">https://www.certigna.com/politique-dutilisation-des-donnees-personnelles/</a>.

# 9.14 Governing Law

Any dispute concerning the validity, interpretation, execution of this CP/CPS will be submitted to the courts of Lille.

# 9.15 Compliance with Applicable Law

This CP/CPS is subject to French law and applicable legislative texts for this CP/CPS.

The trust service practices under which the CA operates are non-discriminatory.

#### 9.16 Miscellaneous Provisions

#### 9.16.1 Entire Agreement

This document contains all the provisions governing the PKI.

#### 9.16.2 Assignment

Cf. chapter 5.8.



# 9.16.3 Severability

In case of an invalid clause, the other clauses are not questioned.

In the event of a conflict between the requirements of this CP/CPS and a law, regulation or government order (hereinafter 'Law') of any jurisdiction in which the CA operates or issues certificates, CA modifies any conflicting requirement to the minimum extent necessary to make the requirement valid and legal in the jurisdiction. This applies only to operations or certificate issuances that are subject to that Law. In such event, CA immediately include in this section (and prior to issuing a certificate under the modified requirement) a detailed reference to the Law requiring a modification of these requirements and the specific modification to these Requirements implemented by the CA.

The CA notifies the CA/Browser Forum and ANSSI (prior to issuing a certificate under the modified requirement) of the relevant information newly added to this CP/CPS by sending a message to questions@cabforum.org (or such other email addresses and links as the Forum may designate) leading to a confirmation.

Any modification to CA practice enabled under this section is discontinued if and when the Law no longer applies, or these requirements are modified to make it possible to comply with both them and the Law simultaneously. An appropriate change in practice, modification to the CP/CPS of CA and a notice to the CA/Browser Forum are made within 90 days.

#### 9.16.4 Enforcement

No renunciation of any of his rights shall be allowed to take place tacitly. To be opposable to the AC a renunciation must have been made in writing. Such waiver shall not constitute a renunciation of future rights audits.

#### 9.16.5 Force Majeure

The CA will not be held responsible for any delay or failure in the performance of any of its obligations under this CP/CPS, if the delay or failure is due to the occurrence of a case of force majeure usually recognized by the jurisprudence of French courts and tribunals.

# 9.17 Other Provisions

#### 9.17.1 Additional testing

Certificates issued on the production environment are used for testing purpose and conform with the requirements of this document and are not used outside of the testing scope.



# 10 APPENDIX 1: SECURITY REQUIREMENTS FOR THE CA'S CRYPTOGRAPHIC MODULE

# 10.1 Security Objectives Requirements

The cryptographic module used by the CA to generate and implement its signature keys (for the generation of electronic certificates, CRL, and OCSP responses), must meet the following security requirements:

- Ensuring the confidentiality and integrity of the CA's signature private keys throughout their lifecycle, and ensuring their secure destruction at their end-of-life;
- Being able to identify and authenticate its users;
- Limiting access to its services per the user and role assigned;
- Ability to carry out a series of tests to verify that it is running correctly and enter in a secure status if an error is detected;
- Create a secure electronic signature to sign the certificates generated by the CA, that does not reveal the CA's private keys and that cannot be falsified without knowing these private keys;
- Creating audit records for each modification relating to security;
- If a backup and restoration function for the CA's private keys is offered, guaranteeing the confidentiality and integrity of the backed-up data and demanding at least a double control of the backup and restoration operations.

# 10.2 Qualification Requirements

The cryptographic module used by the CA is:

- Common Criteria at EAL 4+ level or FIPS 140-2 Level 3.



# 11 APPENDIX 2: SECURITY REQUIREMENTS FOR THE DEVISE USED BY THE SUBJECT

# 11.1 Security objectives requirements

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA	Seal for mails
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA	Seal for Mails
RGS *	
RGS **	

The device used by the seal service to store and implement its private key, and, where appropriate, generate its key pair, must meet the following security requirements:

- If the seal service key pair is generated by the device, guaranteeing that this generation is implemented exclusively by authorized users and guaranteeing the cryptographic sturdiness of the generated key pair;
- Ensuring the correspondence between the private key and the public key;
- Generating a seal which cannot be falsified without knowing the private key;
- Detecting defects during the initialization, customization and operation phases, and ensuring secure techniques for the destruction of the private key in case of re-generation of the private key;
- Guaranteeing the private key's confidentiality and integrity;
- Ensuring the public key's authenticity and integrity when exported outside of the device;
- Ensuring for the legitimate server only, the electronic seals generation function, and protecting the private key against any usage by third parties.

, , , , , , ,	
CERTIGNA EMAIL PROTECTION NATURAL PERSON CA	Authentication/signature
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA	Authentication/signature
CERTIGNA IDENTITY PLUS CA	Authentication/signature
RGS *	
RGS **	
RGS ***	

The device used by the subject to store and implement its private key, and, where appropriate, generate its key pair, must meet the following security requirements:

- If the Subject key pair is generated by the device, guaranteeing that this generation is implemented exclusively by authorized users and guaranteeing the cryptographic sturdiness of the generated key pair;
- Detecting defects during the initialization, customization and operation phases, and ensuring secure techniques for the destruction of the private key in case of re-generation of the private key:
- Guaranteeing the private key's confidentiality and integrity;
- Ensuring the correspondence between the private key and the public key;
- Generating a security function which cannot be falsified without knowing the private key;
- Ensuring for the legitimate subject only, the security function, and protecting the private key against any usage by third parties;
- Ensuring the public key's authenticity and integrity when exported outside of the device.



# 11.2 Qualification Requirements

CERTIGNA EMAIL PROTECTION LEGAL PERSON CA
CERTIGNA EMAIL PROTECTION LEGAL PERSON EU CA

Seal for mails Seal for Mails

#### EN 319 411-2 QCP-I-qscd

The Key pair protection device provided by CA or used by the Certificate Manager is qualified as a « Qualified Seal Creation Device » (QSCD).

#### RGS \*

#### **RGS** \*\*

The key pair protection device used by the CA or the Certificate Manager is:

- Either a hardware device such as a smart card or a cryptographic module qualified by ANSSI;
- Or a software solution complying with the requirements of chapter 11.1 via the implementation
  of additional security measures specific to the environment in which the private key is deployed.
   This environment in which the private key is deployed must have undergone a security audit.

CERTIGNA EMAIL PROTECTION NATURAL PERSON CA
CERTIGNA EMAIL PROTECTION NATURAL PERSON EU CA

Authentication/signature
Authentication/signature

#### CERTIGNA IDENTITY PLUS CA

Authentication/signature

#### EN 319 411-2 QCP-n-qscd

The Key pair protection device provided by CA or used by the subject is qualified as a « Qualified Signature Creation Device » (QSCD).

#### **RGS** \*\*\*

The Key pair protection device provided by CA or used by the subject is qualified at least at the « Enforced » level by the ANSSI.

#### **RGS** \*\*

The Key pair protection device provided by CA or used by the subject is qualified at least at the « Standard » level by the ANSSI.

#### RGS \*

The Key pair protection device provided by CA or used by the subject is qualified at least at the « Elementary » level by the ANSSI.





www.certigna.com

© Certigna, Services de confiance numérique